

Compound Solution Pack

Overview

The Compound Solution pack module adds the ability to create what are called "compound objects." Compound objects gather together objects created with any other Islandora solution pack. When you create a compound object, a generic parent-child relationship is authored between the existing objects and the new compound object (implying a sibling relationship between the objects gathered as "children" of the new compound). These objects are ordered as part of the compound (so an object becomes "part one" of the compound object). This is reflected in the RELS-EXT datastream.

The object view of a compound object is replaced by the view of its first child object. After a compound object is created, the "Islandora Compound Object Navigation" block must be activated and set in an appropriate region. When a user navigates to a compound object, this block will render a thumbnail view of all the additional objects linked via the compound object. In addition, a "Compound" management tab allows for the addition, removal, and reordering of objects from the compound object.

Configuration options are available through the Compound objects administrative menu ([admin/islandora/solution_pack_config/compound_object](#))

Dependencies

- [Islandora](#)
- [JAIL](#) library
 - If utilizing the lazy loading image ability of the solution pack, enable the "Islandora Compound Object JAIL Display" block and ensure the JAIL library is present within `sites/all/libraries/JAIL`.

Downloads

[Release Notes and Downloads](#)

Installation

Enable the Islandora compound object module ([admin/modules](#)). There exists two block options for displaying compound objects within Islandora: The first is the default "Islandora Compound Object Navigation" block. Go to [admin/structure/block/manage/islandora_compound_object/compound_navigation/configure](#) to find navigation controls and load all objects related to the parent compound. The "Islandora Compound Object JAIL Display" block ([admin/structure/block/manage/islandora_compound_object/compound_jail_display/configure](#)) uses the [JAIL](#) library which allows for lazy loading of images. This allows the block to load images only when they are being accessed which will greatly increase performance on compounds with many children.

Usage

To create a compound object:

- Go to parent collection.
- Click "Manage".
- Enable the "Compound Object" object under "Collection" tab, then click "Update Collection Policy".
- After adding compound objects to your Collection Policy, you will be able to click the "Overview" tab and "Add an Object".
- Select "Compound Object" then "Next".
- Select "Compound Object MODS form" then "Next".
- Fill in the form then click "Next". Note that you will not be ingesting an object datastream at this point, you are just creating an empty "parent" compound object that you will then be able to add "child" objects to.
- After the compound object has been created, you can add "child" objects under "Manage" > "Compound".
- Under the "Add Child Object" field, enter the PID for each object to be added to the compound object, then click submit. If you do not use drush, you must do this one-at-a-time for each PID. An autocomplete will also allow you to search for the object by its label if this is relevant. Once a child has been added to the compound, the view of the compound will use the metadata and thumbnail from the first object to render the main object view.

Configuration

The module has documented configuration options at [admin/islandora/solution_pack_config/compound_object](#).

By default, compound objects will be filtered from Solr search results. To change this, go to "Islandora" > "Solution pack configuration" > "Compound Object Solution Pack" > and uncheck the "Hide child objects in Solr results."

Compound Object Solution Pack

[Home](#) » [Administration](#) » [Islandora](#) » [Solution pack configuration](#)

☒ Only allow compound objects to have child objects associated with them

If unchecked, all objects may have child objects.

☒ Generate a thumbnail for compound objects from their first child

If checked, the thumbnail for a compound object will be generated from its first child object.

☐ Hide child objects in RI results

If checked, child objects will be hidden. Only visible within the compound context.

☐ Hide child objects in Solr results

← Uncheck to allow child objects to appear in search results

If checked, child objects will be hidden. Only visible within the compound context.

Child relationship predicate *

isConstituentOf

Changing this after objects have been created will break functionality. Should be part of info:fedora

☒ Use alternative, autoloading display for compounds?

Requires [JAIL](#) library to be present.

Save configuration

Customization

The "Islandora Compound Object Navigation" block can be themed. See `theme_islandora_compound_prev_next()`.

Drush

A Drush command has been added, to be run from the command line (Terminal), that will update the existing rel-predicate of existing compound objects to 'isConstituentOf'. It can be run with the drush command 'drush update_rels_predicate'. This command accpets no arguments.

Content Models, Prescribed Datastreams and Forms

The Compound Solution Pack comes with the following objects in `http://path.to.your.site/admin/islandora/solution_packs`:

- Islandora Compound Object Content Model (islandora:compoundCModel)
- Compound Collection (islandora:compound_collection)

An image object created using the Compound Solution Pack's content model will have the following datastreams:

RELS-EXT	Default Fedora relationship metadata
MODS	MODS record, created at time of ingest
DC	Dublin Core record
TN	Thumbnail image, created at time of ingest

The Compound Solution Pack comes with the Compound Object MODS form.