# **Configuration Reference**

There are a numbers of ways in which DSpace may be configured and/or customized. This chapter of the documentation will discuss the configuration of the software and will also reference customizations that may be performed in the chapter following.

For ease of use, the Configuration documentation is broken into several parts:

- General Configuration addresses general conventions used with configuring the local.cfg file, dspace.cfg and other configuration files which use similar conventions.
- The local.cfg Configuration Properties File describes how to use the local.cfg file to store all your locally customized configurations
- The dspace.cfg Configuration Properties File specifies the basic dspace.cfg file settings (these settings specify the default configuration for DSpace)
- Optional or Advanced Configuration Settings contain other more advanced settings that are optional in the dspace.cfg configuration file.

The full table of contents follows:

Error rendering macro 'toc'

null

# **General Configuration**

In the following sections you will learn about the different configuration files that you will need to edit so that you may make your DSpace installation work.

DSpace provides a number of textual configuration files which may be used to configure your site based on local needs. These include:

- [dspace]/config/dspace.cfg: The primary configuration file, which contains the main configurations for DSpace.
- [dspace]/config/modules/\*.cfg: Module configuration files, which are specific to various modules/features within DSpace.
- [dspace]/config/local.cfg: A (optional, but highly recommended) localized copy of configurations/settings specific to your DSpace (see T he local.cfg Configuration Properties File below)
- Additional feature-specific configuration files also exist under [dspace]/config/, some of these include:
  - default.license: the default deposit license used by DSpace during the submission process (see Submission User Interface documentation)
  - o hibernate.cfg.xml: The Hibernate class configuration for the DSpace database (almost never requires changing)
  - input-forms.xml: The default deposit input forms for DSpace (see Submission User Interface documentation)
  - ° item-submission.xml: the default item submission process for DSpace (see Submission User Interface documentation)
  - launcher.xml: The configuration of the DSpace command-line "launcher" ([dspace]/bin/dspace, see the DSpace Command Launcher documentation)
  - log4j.properties: The default logging settings for DSpace log files (usually placed in [dspace]/log)
  - news-side.html and news-top.html: HTML news configuration files for the JSPUI homepage (see JSPUI Configuration and Customization)
  - o news-xmlui.xml: News configuration file for the XMLUI homepage (see XMLUI Configuration and Customization)
  - workflow.xml: Configuration for the Configurable Workflow feature (not used by default)
  - xmlui.xconf: Configuration for the XMLUI (see XMLUI Configuration and Customization)

As most of these configurations are detailed in other areas of the DSpace documentation (see links above), this section concentrates primarily on the "\*. cfg" configuration files (namely dspace.cfg and local.cfg).

### **Configuration File Syntax**

We will use the dspace.cfg as our example for input conventions used throughout the system. These same input conventions apply to all DSpace \*.cfg files.

All DSpace \*.cfg files use the Apache Commons Configuration properties file syntax. This syntax is very similar to a standard Java properties file, with a few notable enhancements described below.

- Comments all start with a "#" symbol. These lines are ignored by DSpace.
- Other settings appear as property/value pairs of the form: property.name = property value
- · Certain special characters (namely commas) MUST BE escaped. See the "Special Characters" section below
- Values assigned in the same \*.cfg file are "additive", and result in an array of values. See "Specifying Multiple Values for Properties" below.

Some property defaults are "commented out". That is, they have a "#" preceding them, and the DSpace software ignores the config property. This may cause the feature not to be enabled, or, cause a default property to be used.

The property value may contain references to other configuration properties, in the form \${property.name}. A property may not refer to itself. Examples:

```
dspace.dir = /path/to/dspace
dspace.name = My DSpace
# property.name will be equal to "My DSpace is great!"
property.name = ${dspace.name} is great!
# property2.name will be equal to "/path/to/dspace/rest/of/path"
property2.name = ${dspace.dir}/rest/of/path
# However, this will result in an ERROR, as the property cannot reference itself
property3.name = ${property3.name}
```

#### **Special Characters**

Certain characters in \*.cfg files are considered special characters, and **must** be escaped in any values. The most notable of these special characters include:

- Commas (,) : as they represent lists or arrays of values (see "Specifying Multiple Values for Properties" below)
- Backslashes (\) : as this is the escape character

This means that if a particular setting needs to use one of these special characters in its value, it must be escaped. Here's a few examples:

```
# WRONG SETTING
# This setting is INVALID. DSpace is expecting your site name to be a single value,
# But, this setting would create an array of two values: "DSpace" and "My Institution"
dspace.name = DSpace, My Institution
# CORRECT SETTING (commas is escaped)
# Instead, if the name of your DSpace includes a comma, you need to escape it with "\,"
dspace.name = DSpace\, My Institution
# WRONG SETTING
# As the backslash is the escape character, this won't work
property.name = \some\path
# CORRECT SETTING
# If you want a literal backslash, you need to escape it with "\\"
# So, the below value will be returned as "\some\path"
property.name = \\some\\path
```

Additional examples of escaping special characters are provided in the documentation of the Apache Commons Configuration properties file syntax.

#### **Specifying Multiple Values for Properties**

Because DSpace supports the Apache Commons Configuration properties file syntax, it is much easier to specify multiple values for a single setting. All you have to do is repeat the same property name multiple times in the same \*.cfg file.

#### For example:

# The below settings define \*two\* AuthenticationMethods that will be enabled, LDAP and Password authentication # Notice how the same property name is simply repeated, and passed different values. plugin.sequence.org.dspace.authenticate.AuthenticationMethod = org.dspace.authenticate.LDAPAuthentication plugin.sequence.org.dspace.authenticate.AuthenticationMethod = org.dspace.authenticate.PasswordAuthentication # Alternatively, you can also define them as a comma-separated list # (In this scenario, you would NOT escape the comma, as you want them to be considered multiple values) # So, this single line is exactly equavalent to the settings above: plugin.sequence.org.dspace.authenticate.AuthenticationMethod = org.dspace.authenticate.LDAPAuthentication, org. dspace.authenticate.PasswordAuthentication

Please be aware that this ONLY works if you are reusing the exact same configuration in the same configuration file. This causes the values to be "additive" (i.e they are appended to the same list).

However, as you'll see below, the local.cfg file always *overrides* settings elsewhere. So, if the above "AuthenticationMethod" plugin was specified in both your authentication.cfg and your local.cfg, the value(s) in your local.cfg would *override* the defaults in your authentication.cfg (more on that below).

Additional examples of creating lists or arrays of values are provided in the documentation of the Apache Commons Configuration properties file syntax.

#### **Including other Property Files**

Because DSpace supports the Apache Commons Configuration properties file syntax, it also can include/embed property files within other property files by using the "include=" setting.

For example, the dspace.cfg includes/embeds all of the default config/modules/\*.cfg files via a series of "include=" settings near the bottom of the dspace.cfg. As an example, here's a small subset of those include calls:

```
# defines our modules subdirectory
module_dir = modules
# The following lines include specific "authentication*.cfg" files inside your dspace.cfg
# This essentially "embeds" their configurations into your dspace.cfg,
# treating them as if they were a single configuration file.
include = ${module_dir}/authentication.cfg
include = ${module_dir}/authentication-ip.cfg
include = ${module_dir}/authentication-ldap.cfg
include = ${module_dir}/authentication-password.cfg
include = ${module_dir}/authentication-shibboleth.cfg
```

This ability to include properties files within others is very powerful, as it allows you to inherit settings from other files, or subdivide large configuration files. Be aware that this essentially causes DSpace to treat all included configurations as *if they were part of the parent file*. This means that, in the above example, as far as DSpace is concerned, all the settings contained within the authentication\*.cfg files "appear" as though they are specified in the main dspace.cfg.

This ability to include other files is also possible with the local.cfg file, should you want to subdivide your localized settings into several locally specific configuration files.

#### **Configuration Scheme for Reloading and Overriding**

In DSpace 6.0, while the DSpace API supports dynamically reloading configurations, the user interfaces (e.g. XMLUI and JSPUI) still cache some configuration settings. This means that while the API layer may reload a new value, that new value may not always affect/change the behavior of your user interface (until you restart Tomcat). This is something we are working to correct in future versions of DSpace.

Because DSpace supports the Apache Commons Configuration, its configurations can now be reloaded without restarting your servlet container (e.g. Tomcat). By default, DSpace checks for changes to any of its runtime configuration files every 5 seconds. If a change has been made, the configuration file is reloaded. The 5 second interval is configurable in the config-definition.xml (which defines the configuration scheme DSpace uses).

Additionally, DSpace provides the ability to easily override default configuration settings (in dspace.cfg or modules/\*.cfg) using a local.cfg file (see The local.cfg Configuration Properties File) or using System Properties / Environment Varilables.

Both of these features are defined in DSpace's default "configuration scheme" or "configuration definition" in the [dspace]/configdefinition.xml file. This file defines the Apache Commons Configuration settings that DSpace utilizes by default. It is a valid "configuration definition" file as defined by Apache Commons Configuration. See their Configuration Definition File Documentation for more details.

You are welcome to customize the config-definition.xml to customize your local configuration scheme as you see fit. Any customizations to this file will require restarting your servlet container (e.g. Tomcat).

By default, the DSpace config-definition.xml file defines the following configuration scheme:

- Configuration File Syntax/Sources: All DSpace configurations are loaded via Properties files (using the Configuration File Syntax detailed above)

   Note: Apache Commons Configuration does support other configuration sources such as XML configurations or database configurations (see its Overview documentation). At this time, DSpace does not utilize these other sorts of configurations by default. However, it would be possible to customize your local config-definition.xml to load settings from other locations.
- · Configuration Files/Sources: By default, only two configuration files are loaded into Apache Commons Configuration for DSpace:
  - local.cfg (see The local.cfg Configuration Properties File documentation below)
    - dspace.cfg (NOTE: all modules/\*.cfg are loaded by dspace.cfg via "include=" statements at the end of that configuration file. They are essentially treated as sub-configs which are embedded/included into the dspace.cfg)
- Configuration Override Scheme: The configuration override scheme is defined as follows. Configurations specified in earlier locations will
  automatically override any later values:
  - System Properties (-D[setting]=[value]) override all other options
  - Environment Variables
  - <sup>0</sup> local.cfg
  - dspace.cfg (and all modules/\*.cfg files) contain the default values for all settings.
- Configuration Auto-Reload: By default, all configuration files are automatically checked every 5 seconds for changes. If they have changed, they are automatically reloaded.

For more information on customizing our default config-definition.xml file, see the Apache Commons Configuration decumentation on the configuration definition file. Internally, DSpace simply uses the DefaultConfigurationBuilder class provided by Apache Commons Configuration to initialize our configuration scheme (and load all configuration files).

Customizing the default configuration scheme

Because the config-definition.xml file is just a Configuration Definition file for Apache Commons Configuration, you can also choose to customize the above configuration scheme based on your institution's local needs. This includes, but is not limited to, changing the name of "local.cfg", adding additional configuration files/sources, or modifying the override or auto-reload schemes. For more information, see the Configuration Definition File Documentation from Apache Commons Configuration.

### Why are there multiple copies of some config files?

It is important to remember that there are multiple copies of each configuration files in an installation of DSpace. The primary ones to be aware of are:

- 1. The "source" configuration file(s) are found under in [dspace-source]/dspace/config/ or subdirectories. This also includes the [dspace-source]/local.cfg
- 2. The "runtime" configuration file(s) that are found in [dspace]/config/

The DSpace server (webapp) and command line programs only look at the runtime configuration file(s).

When you are revising/changing your configuration values, it may be tempting to *only edit the runtime file*. **DO NOT** do this. Whenever you rebuild DSpace, it will "reset" your runtime configuration to whatever is in your source directories (the previous runtime configuration is copied to a date suffixed file, should you ever need to restore it).

Instead, we recommend to **always make the same changes to the source version** of the configuration file in addition to the runtime file. In other words, the source and runtime files should always be identical / kept in sync.

One way to keep the two files in synchronization is to edit your files in [dspace-source]/dspace/config/ and then run the following commands to rebuild DSpace and install the updated configs:

```
cd [dspace-source]/dspace/
mvn package
cd [dspace-source]/dspace/target/dspace-installer
ant update_configs
```

This will copy the source configuration files into the runtime ([dspace]/config) directory. Another option to manually sync the files by copying them to each directory.

Please note that there are additional "ant" commands to help with configuration management:

- "ant update\_configs" ==> Moves existing configs in [dspace]/config/ to \*.old files and replaces them with what is in [dspace-source] /dspace/config/
- "ant -Doverwrite=false update\_configs" ==> Leaves existing configs in [dspace]/config/ intact. Just copies new configs from [dspace-source]/dspace/config/ over to \*.new files.

### The local.cfg Configuration Properties File

build.properties has been replaced by local.cfg

As of DSpace 6, the old "build.properties" configuration file has been replaced by this new "local.cfg" configuration file. For individuals who are familiar with the old build.properties file, this new local.cfg differs in a few key ways:

- Unlike build.properties, the local.cfg file can be used to override ANY setting in any other configuration file (dspace.cfg or modules /\*.cfg). To override a default setting, simply copy the configuration into your local.cfg and change its value(s).
- Unlike build.properties, the local.cfg file is not utilized during the compilation process (e.g. mvn package). But, it is automatically copied alongside the final dspace.cfg into your installation location ([dspace]/config/), where it overrides default DSpace settings with your locally specific settings at runtime.
- Like build.properties, the local.cfg file is expected to be specified in the source directory by default ([dspace-source]). There is an example ([dspace-source]/dspace/config/local.cfg.EXAMPLE) provided which you can use to create a [dspace-source]/dspace/config/local.cfg.

Many configurations have changed names between DSpace 5 (and below) and DSpace 6

If you are upgrading from an earlier version of DSpace, you will need to be aware that *many* configuration names/keys have changed. Because Apache Commons Configuration allows for auto-overriding of configurations, all configuration names/keys in different \*.cfg files MUST be uniquely named (otherwise accidental, unintended overriding may occur).

In order to create this powerful ability to override configurations in your local.cfg, all modules/\*.cfg files had their configurations renamed to be prepended with the module name. As a basic example, all the configuration settings within the modules/oai.cfg configuration now start with "oai.".

Additionally, while the local.cfg may look similar to the old build.properties, many of its configurations have slightly different names. So, simply copying your build.properties into a local.cfg will NOT work.

This means that DSpace 5.x (or below) configurations are NOT guaranteed compatible with DSpace 6. While you obviously can use your old configurations as a reference, you will need to start with fresh copy of all configuration files, and reapply any necessary configuration changes (this has always been the recommended procedure). However, as you'll see below, you'll likely want to do that anyways in order to take full advantage of the new lo cal.cfg file.

As of DSpace 6, it is now possible to easily override default DSpace configurations (from dspace.cfg or modules/\*.cfg files) in your own local.cfg configuration file.

A example [dspace-source]/dspace/config/local.cfg.EXAMPLE is provided with DSpace. The example only provides a few key configurations which most DSpace sites are likely to need to customize. However, you may add (or remove) any other configuration to your local.cfg to customize it as you see fit.

To get started, simply create your own [dspace-source]/dspace/config/local.cfg based on the example, e.g.

cd [dspace-source]/dspace/config/
cp local.cfg.EXAMPLE local.cfg

You can then begin to edit your local.cfg with your local settings for DSpace. There are a few key things to note about the local.cfg file:

- Override any default configurations: Any setting in your local.cfg will automatically OVERRIDE a setting of the same name in the dspace.cfg or any modules/\*.cfg file. This also means that you can copy ANY configuration (from dspace.cfg or any modules/\*.cfg file) into your local.cfg to specify a new value.
  - ° For example, specifying dspace.url in local.cfg will override the default value of dspace.url in dspace.cfg.
- Also, specifying oai.solr.url in local.cfg will override the default value of oai.solr.url in config/modules/oai.cfg
   Configuration Syntax: The local.cfg file uses the Apache Commons Configuration Property file syntax (like all \*.cfg files). For more information see the section on Configuration File Syntax above.
- This means the local.cfg also supports enhanced features like the ability to include other config files (via "include=" statements).
   Override local.cfg via System Properties: As needed, you also are able to OVERRIDE settings in your local.cfg by specifying them as System Properties or Environment Variables.
  - For example, if you wanted to change your dspace.dir in development/staging environment, you could specify it as a System Property (e.g. -Ddspace.dir=[new-location]). This new value will override any value in *both* local.cfg and dspace.cfg.

When you build DSpace (e.g. mvn package), this local.cfg file will be automatically copied to [dspace]/config/local.cfg. Similar to the dspace .cfg, the "runtime" configuration (used by DSpace) is the one in [dspace]/config/local.cfg. See the Why are there multiple copies of some config files? question above for more details on the runtime vs source configuration.

Here's a very basic example of settings you could place into your local.cfg file (with inline comments):

```
# This is a simple example local.cfg file which shows off options
# for creating your own local.cfg
# This overrides the default value of "dspace.dir" in dspace.cfg
dspace.dir = C:/dspace/
# This overrides the default value of "dspace.baseUrl" in dspace.cfg
dspace.baseUrl = http://dspace.myuniversity.edu
# The overrides the default "dspace.url" setting it to the same value as my "baseUrl" above
dspace.url = ${dspace.baseUrl}
# If our database settings are the same as the default ones in dspace.cfg,
# then, we may be able to simply customize the db.username and db.password
db.username = myuser
db.password = mypassword
# For DSpace, we want the LDAP and Password authentication plugins enabled
# This overrides the default AuthenticationMethod in /config/modules/authentication.cfg
# Since we specified the same key twice, these two values are appended (see Configuration File Syntax above)
plugin.sequence.org.dspace.authenticate.AuthenticationMethod = org.dspace.authenticate.LDAPAuthentication
plugin.sequence.org.dspace.authenticate.AuthenticationMethod = org.dspace.authenticate.PasswordAuthentication
# For the example, we'll override the default oai.url in /config/modules/oai.cfg
oai.url = ${dspace.baseUrl}/oaipmh
# We'll also override the default oai.solr.url in /config/modules/oai.cfg
# Notice here we're referencing a configuration (solr.server) that only exists in dspace.cfg
# This is allowed. Your local.cfg can reference configs from other *.cfg files.
oai.solr.url=${solr.server}/oaipmh
# Finally, this local.cfg also supports adding "include=" statements, to include
# additional local configuration files.
# In this example, a local-rest.cfg and local-curate.cfg (in the same directory)
# will automatically be included as part of this local.cfg.
# This allows you to subdivide you local configs in as many (or few) config files
# as you desire.
include = local-rest.cfg
include = local-curate.cfg
```

### The dspace.cfg Configuration Properties File

Any dspace.cfg setting can be overridden in your local.cfg

Remember, any of the below dspace.cfg settings can be copied into your local.cfg configuration file and overridden. So, rather than editing the dspace.cfg (or any of the modules/\*.cfg), it's recommended to simply override the default values in your local.cfg. That way, your local.cfg can serve as the record of which configurations you have actually tweaked in your DSpace, which may help to simplify future upgrades.

The dspace.cfg contains basic information about a DSpace installation, including system path information, network host information, and other like items. It is the default configuration file for DSpace, used by DSpace when it is actively running. However, as noted above, any of these default configurations may be overridden in your own local.cfg configuration file.

### Main DSpace Configurations

Prope rty:	dspace.dir
Exam ple Value:	/dspace
Infor matio nal Note:	Root directory of DSpace installation. Omit the trailing slash '/. Note that if you change this, there are several other parameters you will probably want to change to match, e.g. assetstore.dir. (On Windows be sure to use forward slashes for the directory path! For example: "C:/dspace" is a valid path for Windows.)
Prope rty:	dspace.hostname

Exam ple Value:	dspace.hostname = dspace.mysu.edu
Infor matio nal Note:	Fully qualified hostname; do not include port number.
Prope rty:	dspace.baseUrl
Exam ple Value:	http://dspacetest.myu.edu:8080
Infor matio nal Note:	Main URL at which DSpace Web UI webapp is deployed. Include any port number, but do not include the trailing '/'.
Prope rty:	dspace.url
Exam ple Value:	<pre>dspace.url = http://dspacetest.myu.edu:8080/xmlui</pre>
Infor matio nal note	URL that determines whether JSPUI or XMLUI will be loaded by default. Include port number etc., but NOT trailing slash. Alternatively to the example, this url can have /jspui at the end if you are using jspui instead of xmlui. You can also opt to run your UI app as your servlet engine's "ROOT" webapp. In that case, ensure that you remove /xmlui or /jspui.
Prope rty:	dspace.name
Exam ple Value:	dspace.name = DSpace at My University
Infor matio nal Note:	Short and sweet site name, used throughout Web UI, e-mails and elsewhere (such as OAI protocol)

## **DSpace Database Configuration**

Many of the database configurations are software-dependent. That is, it will be based on the choice of database software being used. Currently, DSpace properly supports PostgreSQL and Oracle.

Property:	db.url
Example Value:	db.url = jdbc:postgresql://localhost:5432/dspace
Informatio nal Note:	The above value is the default value when configuring with PostgreSQL. When using Oracle, use this value: jbdc.oracle.thin:@//host:port/dspace
Property:	db.username
Example Value:	db.username = dspace
Informatio nal Note:	In the installation directions, the administrator is instructed to create the user "dspace" who will own the database "dspace".
Property:	db.password
Example Value:	db.password = dspacepassword
Informatio nal Note:	This is the password that was prompted during the installation process (cf. 3.2.3. Installation)
Property:	db.schema
Example Value:	db.schema = public

Informatio nal Note:	If your database contains multiple schemas, you can avoid problems with retrieving the definitions of duplicate objects by specifying the schema name here that is used for DSpace by uncommenting the entry. This property is optional.
Property:	db.maxconnections
Example Value:	db.maxconnections = 30
Informatio nal Note:	Maximum number of Database connections in the connection pool
Property:	db.maxwait
Example Value:	db.maxwait = 5000
Informatio nal Note:	Maximum time to wait before giving up if all connections in pool are busy (in milliseconds).
Property:	db.maxidle
Example Value:	db.maxidle = -1
Informatio nal Note:	Maximum number of idle connections in pool. (-1 = unlimited)
Property:	db.statementpool
Example Value:	db.statementpool = true
Informatio nal Note:	Determines if prepared statement should be cached. (Default is set to true)
Property:	db.poolname
Example Value:	db.poolname = dspacepool
Informatio nal Note:	Specify a name for the connection pool. This is useful if you have multiple applications sharing Tomcat's database connection pool. If nothing is specified, it will default to 'dspacepool'

#### To provide the database connection pool externally

Alternately, you may supply a configured connection pool out of JNDI. The object must be named jdbc/dspace (the full path is java:comp/env/jdbc/dspace). DSpace will always look up this name and, if found, will use the returned object as its database connection pool. If not found, the above db.\* properties will be used to create the pool.

If you are using Tomcat, then the object might be defined using a <Resource> element, or connected to a <Resource> child of <GlobalNamingResour ces> using a <ResourceLink> element. See your Servlet container's documentation for details of configuring the JNDI initial context.

Earlier releases of DSpace provided a configuration property db.jndi to specify the name to be looked up, but that has been removed. The name is specified in config/spring/api/core-hibernate.xml if you really need to change it.

### **DSpace Email Settings**

The configuration of email is simple and provides a mechanism to alert the person(s) responsible for different features of the DSpace software.

DSpace will look up a javax.mail.Session object in JNDI and, if found, will use that to send email. Otherwise it will create a Session using some of the properties detailed below.

Prope rty:	mail.server
Exam ple Value:	<pre>mail.server = smtp.my.edu</pre>
Infor matio nal Note:	The address on which your outgoing SMTP email server can be reached.
Prope rty:	mail.server.username

Exam ple Value:	mail.server.username = myusername
Infor matio nal Note:	SMTP mail server authentication username, if required. This property is optional.
Prope rty:	mail.server.password
Exam ple Value:	<pre>mail.server.password = mypassword</pre>
Infor matio nal Note:	SMTP mail server authentication password, if required. This property is optional.
Prope rty:	mail.server.port
Exam ple Value:	<pre>mail.server.port = 25</pre>
Infor matio nal Note:	The port on which your SMTP mail server can be reached. By default, port 25 is used, port 587 is commonly used for TLS connections. Change this setting if your SMTP mailserver is running on another port. This property is optional.
Prope rty:	mail.from.address
Exam ple Value:	<pre>mail.from.address = dspace-noreply@myu.edu</pre>
Infor matio nal Note:	The "From" address for email. Change the 'myu.edu' to the site's host name.
Prope rty:	feedback.recipient
Exam ple Value:	feedback.recipient = dspace-help@myu.edu
Infor matio nal Note:	When a user clicks on the feedback link/feature, the information will be sent to the email address of choice. This configuration is currently limited to only one recipient. Since DSpace 4.0, this is also the email address displayed on the contacts page.
Prope rty:	mail.admin
Exam ple Value:	mail.admin = dspace-help@myu.edu
Infor matio nal Note:	Email address of the general site administrator (Webmaster)
Prope rty:	alert.recipient
Exam ple Value:	alert.recipient = john.doe@myu.edu

Infor matio nal Note:	Enter the recipient for server errors and alerts. This property is optional.
Prope rty:	registration.notify
Exam ple Value:	registration.notify = mike.smith@myu.edu
Infor matio nal Note:	Enter the recipient that will be notified when a new user registers on DSpace. This property is optional.
Prope rty:	mail.charset
Exam ple Value:	mail.charset = UTF-8
Infor matio nal Note:	Set the default mail character set. This may be over-ridden by providing a line inside the email template ' <i>charset: <encoding></encoding></i> ', otherwise this default is used.
Prope rty:	mail.allowed.referrers
Exam ple Value:	<pre>mail.allowed.referrers = localhost</pre>
Infor matio nal Note:	A comma separated list of hostnames that are allowed to refer browsers to email forms. Default behavior is to accept referrals only from <i>dspace</i> . <i>hostname</i> . This property is optional.
Prope rty:	mail.extraproperties
Exam ple Value:	<pre>mail.extraproperties = mail.smtp.socketFactory.port=465, \     mail.smtp.socketFactory.class=javax.net.ssl.SSLSocketFactory, \     mail.smtp.socketFactory.fallback=false</pre>
Infor matio nal Note:	If you need to pass extra settings to the Java mail library. Comma separated, equals sign between the key and the value. This property is optional.
Prope rty:	mail.server.disabled
Exam ple Value:	<pre>mail.server.disabled = false</pre>
Infor matio nal Note:	An option is added to disable the mailserver. By default, this property is set to 'false'. By setting value to 'true', DSpace will not send out emails. It will instead log the subject of the email which should have been sent. This is especially useful for development and test environments where production data is used when testing functionality. This property is optional.
Prope rty:	mail.session.name
Exam ple Value:	mail.session.name = myDSpace
Infor matio nal Note:	Specifies the name of a javax.mail.Session object stored in JNDI under java:comp/env/mail. The default value is "Session".

Prope rty:	default.language
Exam ple Value:	default.language = en_US
Infor matio nal Note:	If no other language is explicitly stated in the <i>input-forms.xml</i> , the default language will be attributed to the metadata values.

#### Wording of E-mail Messages

Sometimes DSpace automatically sends e-mail messages to users, for example, to inform them of a new work flow task, or as a subscription e-mail alert. The wording of emails can be changed by editing the relevant file in [dspace]/config/emails. Each file is commented. Be careful to keep the right number 'placeholders' (e.g. {2}).

Note: You should replace the contact-information "dspace-help@myu.edu or call us at xxx-555-xxxx" with your own contact details in: config/emails/change\_password config/emails/register

#### Format of E-mail Messages

The files in dspace/config/emails are templates with a specific structure.

- A line beginning with "#" is a comment and will not be included in the message.
- A line beginning with "Subject: " will set the Subject: header of the message and will not be included in the body.
- A line beginning with "Charset: " will set the character set in which the subject and single message bodypart are assumed to be encoded, will be used as the value of the charset parameter of the Content-Encoding header for the message, and will not be included in the body. If the message has multiple bodyparts (i.e. attachments are included) then all are assumed to be encoded in US-ASCII and the "Charset: " line has no effect on them (but still affects the subject).
- A number enclosed in braces, such as {2}, anywhere in a non-comment line, will be replaced with the corresponding parameter which was supplied to the message when the message formatter was called. Parameter numbers are 0-based. Refer to the comments in the template or to the code which uses it for the meaning of each parameter.

#### Using an external mail server

If you want to use an external mail server setting the value of mail.server to the domain name is enough if authentication is not required. Most external SMTP mail servers will however require authentication for obvious reasons. To enable TLS encryption you will typically have to set the mail.server. port to the secure default 587 and for the mail.server.username and mail.server.password to be set. In addition you will need to enable TLS by setting the following extra properties:

Note that as of January 2020 Microsoft has started to remove support for Transport Layer Security (TLS) versions 1.0 and 1.1 in Office 365 and Office 365 GCC (see more information here). This necessitates using TLS 1.2 then. Some users have reported being able to use the following configuration successfully (see discussion):

### **File Storage**

Beginning with DSpace 6, your file storage location (aka bitstore) is now defined in the [dspace]/config/spring/api/bitstore.xml Spring configuration file. By default it is defined as the [dspace]/assetstore/. More information on modifying your file storage location can be found at Configuring the Bitstream Store in the Storage Layer documentation.

DSpace supports multiple options for storing your repository bitstreams (uploaded files). The files are not stored in the database, instead they are provided via a configured "assetstore" or "bitstore".

By default, the assetstore is simply a directory on your server ([dspace]/assetstore/) under which bitstreams (files) are stored by DSpace.

At this time, DSpace supports two primary locations for storing your files:

- 1. Your local filesystem (used by default), specifically under the [dspace]/assetstore/ directory
- 2. OR, Amazon S3 (requires your own Amazon S3 account)

More information on configuring or customizing the storage location of your files can be found in the Storage Layer documentation.

## Logging Configuration

Proper ty:	log.init.config
Exam ple Value:	<pre>log.init.config = \${dspace.dir}/config/log4j.properties</pre>
Inform ational Note:	This is where your logging configuration file is located. You may override the default log4j configuration by providing your own. Existing alternatives are:
	<pre>log.init.config = \${dspace.dir}/config/log4j.properties log.init.config = \${dspace.dir}/config/log4j-console.properties</pre>
Proper ty:	log.dir
Exam ple value:	<pre>log.dir = \${dspace.dir}/log</pre>
Inform ational Note:	This is where to put the logs. (This is used for initial configuration only)
Proper ty:	<pre>loglevel.dspace (defined in log4j.properties)</pre>
Exam ple value:	loglevel.dspace = INFO
Inform ational Note:	Log level for all DSpace-specific code (org.dspace.* packages). By default, DSpace only provides general INFO logs (in order to keep log sizes reasonable). As necessary, you can temporarily change this setting to any of the following (ordered for most information to least): DEBUG , INFO, WARN, ERROR, FATAL
	Please be aware we do not recommend running at the DEBUG level in Production for significant periods of time, as it will cause the logs to be extremely large in size.
Proper ty:	loglevel.other (defined in log4j.properties)
Exam ple value:	loglevel.other = INFO
Inform ational Note:	Log level for other third-party tools/APIs used by DSpace (non-DSpace specific code). By default, DSpace only provides general INFO logs (in order to keep log sizes reasonable). As necessary, you can temporarily change this setting to any of the following (ordered for most information to least): DEBUG, INFO, WARN, ERROR, FATAL
	Please be aware we do not recommend running at the DEBUG level in Production for significant periods of time, as it will cause the logs to be extremely large in size.

Previous releases of DSpace provided an example \${dspace.dir}/config/log4j.xml as an alternative to log4j.properties. This caused some confusion and has been removed. log4j continues to support both Properties and XML forms of configuration, and you may continue (or begin) to use any form that log4j supports.

### **General Plugin Configuration**

Property:	plugin.classpath
Example Value:	/opt/dspace/plugins/aPlugin.jar:/opt/dspace/moreplugins
Information al Note:	Search path for third-party plugin classes. This is a colon-separated list of directories and JAR files, each of which will be searched for plugin classes after looking in all the places where DSpace classes are found. In this way you can designate one or more locations for plugin files which will not be affected by DSpace upgrades.

**Configuring the Search Engine** Since DSpace 4.0 the advanced search module named Discovery (based on Apache SOLR) is the default search provider. It provides up-to-date features, such as filtering/faceting, hit highlighting, search snippets, etc.

Detailed documentation is available for customization, see Discovery.

### Handle Server Configuration

The CNRI Handle system is a 3rd party service for maintaining persistent URL's. For a nominal fee, you can register a handle prefix for your repository. As a result, your repository items will be also available under the links http://handle.net/<<handle prefix>>/<<item id>>. As the base url of your repository might change or evolve, the persistent handle.net URL's secure the consistency of links to your repository items. For complete information regarding the Handle server, the user should consult The Handle Server section of Installing DSpace.

Pr op ert y:	handle.canonical.prefix
Ex a m ple Va lue	handle.canonical.prefix = http://hdl.handle.net/ handle.canonical.prefix = \${dspace.url}/handle/
Inf or m ati on al No te:	Canonical Handle URL prefix. By default, DSpace is configured to use http://hdl.handle.net/ as the canonical URL prefix when generating dc. identifier.uri during submission, and in the 'identifier' displayed in item record pages. If you do not subscribe to CNRI's handle service, you can change this to match the persistent URL service you use, or you can force DSpace to use your site's URL, e.g. handle.canonical. prefix = \${dspace.url}/handle/. Note that this will not alter dc.identifer.uri metadata for existing items (only for subsequent submissions).
Pr op ert y:	handle.prefix
Ex a m ple Va lue	handle.prefix = 1234.56789
Inf or m ati on al No te:	The default installed by DSpace is 123456789 but you will replace this upon receiving a handle from CNRI.
Pr op ert y:	handle.dir
Ex a ple Va lue:	handle.dir = \${dspace.dir}/handle-server
Inf or m ati on al No te:	The default files, as shown in the Example Value is where DSpace will install the files used for the Handle Server.

Pr op erty	handle.additional.prefixes
Ex a m ple Va lue	handle.additional.prefixes = 1234.56789.0, 1234.56789.1, 987
Inf or m ati on al No te:	List any additional prefixes that need to be managed by this handle server. For example, any handle prefixes that came from an external repository whose items have now been added to this DSpace. Multiple additional prefixes may be added in a comma separated list.

### **Delegation Administration: Authorization System Configuration**

It is possible to delegate the administration of Communities and Collections. This functionality eliminates the need for an Administrator Superuser account for these purposes. An EPerson that will be attributed Delegate Admin rights for a certain community or collection will also "inherit" the rights for underlying collections and items. As a result, a community admin will also be collection admin for all underlying collections. Likewise, a collection admin will also gain admin rights for all the items owned by the collection.

Authorization to execute the functions that are allowed to user with WRITE permission on an object will be attributed to be the ADMIN of the object (e.g. community/collection/admin will be always allowed to edit metadata of the object). The default will be "true" for all the configurations.

Community Administration: Subcommunities and Collections	
Property:	core.authorization.community-admin.create-subelement
Example Value:	<pre>core.authorization.community-admin.create-subelement = true</pre>
Informational Note:	Authorization for a delegated community administrator to create subcommunities or collections.
Property:	core.authorization.community-admin.delete-subelement
Example Value:	<pre>core.authorization.community-admin.delete-subelement = true</pre>
Informational Note:	Authorization for a delegated community administrator to delete subcommunities or collections.
Community Administration: Policies and The group of administrators	
Property:	core.authorization.community-admin.policies
Example Value:	<pre>core.authorization.community-admin.policies = true</pre>
Informational Note:	Authorization for a delegated community administrator to administrate the community policies.
Property:	core.authorization.community-admin.admin-group
Example Value:	<pre>core.authorization.community-admin.admin-group = true</pre>
Informational Note:	Authorization for a delegated community administrator to edit the group of community admins.
Community Administration: Collections in the above Community	
Property:	core.authorization.community-admin.collection.policies
Example Value:	<pre>core.authorization.community-admin.collection.policies = true</pre>
Informational Note:	Authorization for a delegated community administrator to administrate the policies for underlying collections.
Property:	core.authorization.community-admin.collection.template- item

Example Value:	<pre>core.authorization.community-admin.collection.template- item = true</pre>
Informational Note:	Authorization for a delegated community administrator to administrate the item template for underlying collections.
Property:	core.authorization.community-admin.collection.submitters
Example Value:	<pre>core.authorization.community-admin.collection.submitters = true</pre>
Informational Note:	Authorization for a delegated community administrator to administrate the group of submitters for underlying collections.
Property:	core.authorization.community-admin.collection.workflows
Example Value:	<pre>core.authorization.community-admin.collection.workflows = true</pre>
Informational Note:	Authorization for a delegated community administrator to administrate the workflows for underlying collections.
Property:	core.authorization.community-admin.collection.admin-group
Example Value:	<pre>core.authorization.community-admin.collection.admin- group = true</pre>
Informational Note:	Authorization for a delegated community administrator to administrate the group of administrators for underlying collections.
Community Administration: Items Owned by Collections in the Above Community	
Property:	core.authorization.community-admin.item.delete
Example Value:	<pre>core.authorization.community-admin.item.delete = true</pre>
Informational Note:	Authorization for a delegated community administrator to delete items in underlying collections.
Property:	core.authorization.community-admin.item.withdraw
Example Value:	<pre>core.authorization.community-admin.item.withdraw = true</pre>
Informational Note:	Authorization for a delegated community administrator to withdraw items in underlying collections.
Property:	core.authorization.community-admin.item.reinstate
Example Value:	<pre>core.authorization.community-admin.item.reinstate = true</pre>
Informational Note:	Authorization for a delegated community administrator to reinstate items in underlying collections.
Property:	core.authorization.community-admin.item.policies
Example Value:	<pre>core.authorization.community-admin.item.policies = true</pre>
Informational Note:	Authorization for a delegated community administrator to administrate item policies in underlying collections.
Community Administration: Bundles of Bitstreams, related to items owned by collections in the above Community	
Property:	core.authorization.community-admin.item.create-bitstream
Example Value:	<pre>core.authorization.community-admin.item.create-bitstream = true</pre>
Informational Note:	Authorization for a delegated community administrator to create additional bitstreams in items in underlying collections.
Property:	core.authorization.community-admin.item.delete-bitstream
Example Value:	<pre>core.authorization.community-admin.item.delete-bitstream = true</pre>
Informational Note:	Authorization for a delegated community administrator to delete bitstreams from items in underlying collections.

Property:	core.authorization.community-admin.item.cc-license
Example Value:	<pre>core.authorization.community-admin.item.cc-license = true</pre>
Informational Note:	Authorization for a delegated community administrator to administer licenses from items in underlying collections.
Community Administration: The properties for collection administrators work similar to those of community administrators, with respect to collection administration.	core.authorization.collection-admin.policies core.authorization.collection-admin.template-item core.authorization.collection-admin.submitters core.authorization.collection-admin.workflows core.authorization.collection-admin.admin-group
Collection Administration: Item owned by the above CollectionThe properties for collection administrators work similar to those of community administrators, with respect to administration of items in underlying collections.	<pre>core.authorization.collection-admin.item.delete core.authorization.collection-admin.item.withdraw core.authorization.collection-admin.item.reinstatiate core.authorization.collection-admin.item.policies</pre>
Collection Administration: Bundles of bitstreams, related to items owned by collections in the above Community. The properties for collection administrators work similar to those of community administrators, with respect to administration of bitstreams related to items in underlying collections.	<pre>core.authorization.collection-admin.item.create- bitstream core.authorization.collection-admin.item.delete- bitstream core.authorization.collection-admin.item-admin.cc- license</pre>
Item Administration. The properties for item administrators work similar to those of community and collection administrators, with respect to administration of items in underlying collections.	core.authorization.item-admin.policies
Item Administration: Bundles of bitstreams, related to items owned by collections in the above Community. The properties for item administrators work similar to those of community and collection administrators, with respect to administration of bitstreams related to items in underlying collections.	core.authorization.item-admin.create-bitstream core.authorization.item-admin.delete-bitstream core.authorization.item-admin.cc-license

### Login as feature

Proper ty:	webui.user.assumelogin
Examp le Value:	webui.user.assumelogin = true
Inform ational Note:	Determine if super administrators (those whom are in the Administrators group) can login as another user from the "edit eperson" page. This is useful for debugging problems in a running dspace instance, especially in the workflow process. The default value is false, i.e., no one may assume the login of another user.
	Please note that this configuration parameter has changed name in DSpace 4.0 from xmlui.user.assumelogin to webui.user. assumelogin as it is now supported also in the JSP UI

### **Restricted Item Visibility Settings**

By default RSS feeds and subscription emails will include ALL items regardless of permissions set on them. If you wish to only expose items through these channels where the ANONYMOUS user is granted READ permission, then set the following options to false.

Property:	harvest.includerestricted.rss
Example Value:	harvest.includerestricted.rss = true
Informational Note:	When set to 'true' (default), items that haven't got the READ permission for the ANONYMOUS user, will be included in RSS feeds anyway.

Property:	harvest.includerestricted.subscription
Example Value:	harvest.includerestricted.subscription = true
Informational Note:	When set to true (default), items that haven't got the READ permission for the ANONYMOUS user, will be included in Subscription emails anyway.

### **Proxy Settings**

These settings for proxy are commented out by default. Uncomment and specify both properties if proxy server is required for external http requests. Use regular host name without port number.

Prop erty:	http.proxy.host
Exa mple Value	http.proxy.host = proxy.myu.edu
Infor mati onal Note	Enter the host name without the port number.
Prop erty:	http.proxy.port
Exa mple Value	http.proxy.port = 2048
Infor mati onal Note	Enter the port number for the proxy server.
Prop erty	useProxies
Exa mple Valu e:	useProxies = true
Infor mati onal Note:	If your DSpace instance is protected by a proxy server, in order for log4j to log the correct IP address of the user rather than of the proxy, it must be configured to look for the X-Forwarded-For header. This feature can be enabled by ensuring this setting is set to <i>true (default is false)</i> . This also affects IPAuthentication, and should be enabled for that to work properly if your installation uses a proxy server.

### **Configuring Media Filters**

Media or Format Filters are classes used to generate derivative or alternative versions of content or bitstreams within DSpace. For example, the PDF Media Filter will extract textual content from PDF bitstreams, the JPEG Media Filter can create thumbnails from image bitstreams.

Media Filters are configured as Named Plugins, with each filter also having a separate configuration setting (in *dspace.cfg*) indicating which formats it can process. The default configuration is shown below.

Property:	filter.plugins
Example Value:	filter.plugins = PDF Text Extractor, Html Text Extractor, \ Word Text Extractor, JPEG Thumbnail
Informatio nal Note:	Place the names of the enabled MediaFilter or FormatFilter plugins. To enable Branded Preview, comment out the previous one line and then uncomment the two lines in found in <i>dspace.cfg</i> .
	Word Text Extractor, JPEG Thumbnail,\ Branded Preview JPEG
Property:	plugin.named.org.dspace.app.mediafilter.FormatFilter

Example Value:	<pre>plugin.named.org.dspace.app.mediafilter.FormatFilter = \     org.dspace.app.mediafilter.PDFFilter = PDF Text Extractor, \     org.dspace.app.mediafilter.HTMLFilter = HTML Text Extractor, \     org.dspace.app.mediafilter.WordFilter = Word Text Extractor, \     org.dspace.app.mediafilter.JPEGFilter = JPEG Thumbnail, \     org.dspace.app.mediafilter.BrandedPreviewJPEGFilter = Branded Preview JPEG</pre>
Informatio nal Note:	Assign "human-understandable" names to each filter
Property:	<pre>filter.org.dspace.app.mediafilter.PDFFilter.inputFormats filter.org.dspace.app.mediafilter.HTMLFilter.inputFormats filter.org.dspace.app.mediafilter.WordFilter.inputFormats filter.org.dspace.app.mediafilter.JPEGFilter.inputFormats filter.org.dspace.app.mediafilter.BrandedPreviewJPEGFilter.inputFormats</pre>
Example Value:	<pre>filter.org.dspace.app.mediafilter.PDFFilter.inputFormats = Adobe PDF filter.org.dspace.app.mediafilter.HTMLFilter.inputFormats = HTML, Text filter.org.dspace.app.mediafilter.WordFilter.inputFormats = Microsoft Word filter.org.dspace.app.mediafilter.JPEGFilter.inputFormats = BMP, GIF, JPEG, \</pre>
Informatio nal Note:	Configure each filter's input format(s)
Property:	pdffilter.largepdfs
Example Value:	pdffilter.largepdfs = true
Informatio nal Note:	It this value is set for "true", all PDF extractions are written to temp files as they are indexed. This is slower, but helps to ensure that PDFBox software DSpace uses does not eat up all your memory.
Property:	pdffilter.skiponmemoryexception
Example Value:	pdffilter.skiponmemoryexception = true
Informatio nal Note:	If this value is set for "true", PDFs which still result in an "Out of Memory" error from PDFBox are skipped over. These problematic PDFs will never be indexed until memory usage can be decreased in the PDFBox software.

Names are assigned to each filter using the plugin.named.org.dspace.app.mediafilter.FormatFilter field (e.g. by default the PDFilter is named "PDF Text Extractor".

Finally, the appropriate filter.<class path>.inputFormats defines the valid input formats which each filter can be applied. These format names **m** ust match the short description field of the Bitstream Format Registry.

You can also implement more dynamic or configurable Media/Format Filters which extend SelfNamedPlugin .

More Information on MediaFilters

For more information on Media/Format Filters, see the section on Mediafilters for Transforming DSpace Content.

### **Crosswalk and Packager Plugin Settings**

The subsections below give configuration details based on the types of crosswalks and packager plugins you need to implement.

More Information on Packagers & Crosswalks

For more information on using Packagers and Crosswalks, see the section on Importing and Exporting Content via Packages.

#### **Configurable MODS Dissemination Crosswalk**

The MODS crosswalk is a self-named plugin. To configure an instance of the MODS crosswalk, add a property to the DSpace configuration starting with "c rosswalk.mods.properties."; the final word of the property name becomes the plugin's name. For example, a property name crosswalk.mods. properties.MODS defines a crosswalk plugin named "MODS".

The value of this property is a path to a separate properties file containing the configuration for this crosswalk. The pathname is relative to the DSpace configuration directory, i.e. the config subdirectory of the DSpace install directory. Example from the dspace.cfg file:

Properties:	crosswalk.mods.properties.MODS crosswalk.mods.properties.mods
Example Values:	<pre>crosswalk.mods.properties.MODS = crosswalks/mods.properties crosswalk.mods.properties.mods = crosswalks/mods.properties</pre>
Information al Note:	This defines a crosswalk named MODS whose configuration comes from the file [dspace]/config/crosswalks/mods.properties . (In the above example, the lower-case name was added for OAI-PMH)

The MODS crosswalk properties file is a list of properties describing how DSpace metadata elements are to be turned into elements of the MODS XML output document. The property name is a concatenation of the metadata schema, element name, and optionally the qualifier. For example, the *contributor. author* element in the native Dublin Core schema would be: *dc.contributor.author*. The value of the property is a line containing two segments separated by the vertical bar ("|"\_\_): The first part is an XML fragment which is copied into the output document. The second is an XPath expression describing where in that fragment to put the value of the metadata element. For example, in this property:

Some of the examples include the string "%s" in the prototype XML where the text value is to be inserted, but don't pay any attention to it, it is an artifact that the crosswalk ignores. For example, given an author named *Jack Florey*, the crosswalk will insert

into the output document. Read the example configuration file for more details.

#### XSLT-based Crosswalks

The XSLT crosswalks use XSL stylesheet transformation (XSLT) to transform an XML-based external metadata format to or from DSpace's internal metadata. XSLT crosswalks are much more powerful and flexible than the configurable MODS and QDC crosswalks, but they demand some esoteric knowledge (XSL stylesheets). Given that, you can create all the crosswalks you need just by adding stylesheets and configuration lines, without touching any of the Java code.

The default settings in the dspace.cfg file for submission crosswalk:

Properties:	crosswalk.submission.MODS.stylesheet
Example Value:	<pre>crosswalk.submission.MODS.stylesheet = crosswalks/mods-submission.xsl</pre>
Informational Note:	Configuration XSLT-driven submission crosswalk for MODS

As shown above, there are three (3) parts that make up the properties "key":

crosswalk first part of the property key.

submission second part of the property key.

crosswalk.submission.LOM.stylesheet = crosswalks/d-lom.xsl

A dissemination crosswalk can be configured by starting with the property key crosswalk.dissemination. Example:

crosswalk.dissemination.PluginName.stylesheet = path

The PluginName is the name of the plugin (!). The path value is the path to the file containing the crosswalk stylesheet (relative to /[dspace]/config).

PluginName is the name of the plugin. The *path* value is the path to the file containing the crosswalk stylesheet (relative to /[dspace]/config). Here is an example that configures a crosswalk named "LOM" using a stylesheet in [dspace]/config/crosswalks/d-lom.xsl:

You can make two different plugin names point to the same crosswalk, by adding two configuration entries with the same path:

The dissemination crosswalk must also be configured with an XML Namespace (including prefix and URI) and an XML schema for its output format. This is configured on additional properties in the DSpace configuration:

#### For example:

```
crosswalk.dissemination.qdc.namespace.dc = http://purl.org/dc/elements/1.1/
    crosswalk.dissemination.qdc.namespace.dcterms = http://purl.org/dc/terms/
    crosswalk.dissemination.qdc.schemalocation = http://purl.org/dc/elements/1.1/ \
    http://dublincore.org/schemas/xmls/qdc/2003/04/02/qualifieddc.xsd
```

If you remove all XSLTDisseminationCrosswalks please disable the XSLTDisseminationCrosswalk in the list of selfnamed plugins. If no XSLTDisseminationCrosswalks are configured but the plugin is loaded the PluginManager will log an error message ("Self-named plugin class "org.dspace. content.crosswalk.XSLTDisseminationCrosswalk" returned null or empty name list!").

#### Testing XSLT Crosswalks

The XSLT crosswalks will automatically reload an XSL stylesheet that has been modified, so you can edit and test stylesheets without restarting DSpace. You can test a crosswalk by using a command-line utility. To test a dissemination crosswalk you have to run:

[dspace]/bin/dspace dsrun org.dspace.content.crosswalk.XSLTDisseminationCrosswalk <plugin name> <handle> [output-file]

#### For example, you can test the marc plugin on the handle 123456789/3 with:

```
[dspace]/bin/dspace dsrun org.dspace.content.crosswalk.XSLTDisseminationCrosswalk marc 123456789/3
```

Informations from the script will be printed to stderr while the XML output of the dissemination crosswalk will be printed to stdout. You can give a third parameter containing a filename to write the output into a file, but be careful: the file will be overwritten if it exists.

Testing a submission crosswalk works quite the same way. Use the following command-line utility, it calls the crosswalk plugin to translate an XML document you submit, and displays the resulting intermediate XML (DIM). Invoke it with:

[dspace]/bin/dspace dsrun org.dspace.content.crosswalk.XSLTIngestionCrosswalk [-1] <plugin name> <input-file>

where <plugin name> is the name of the crosswalk plugin to test (e.g. "LOM"), and <input-file> is a file containing an XML document of metadata in the appropriate format.

Add the -1 option to pass the ingestion crosswalk a list of elements instead of a whole document, as if the List form of the ingest() method had been called. This is needed to test ingesters for formats like DC that get called with lists of elements instead of a root element.

#### Configurable Qualified Dublin Core (QDC) dissemination crosswalk

The QDC crosswalk is a self-named plugin. To configure an instance of the QDC crosswalk, add a property to the DSpace configuration starting with "cros swalk.gdc.properties."; the final word of the property name becomes the plugin's name. For example, a property name crosswalk.gdc.properties.QDC defines a crosswalk plugin named "QDC".

#### The following is from dspace.cfg file:

Properties:	crosswalk.qdc.namspace.qdc.dc
Example Value:	<pre>crosswalk.qdc.namspace.qdc.dc = http://purl.org/dc/elements/1.1_</pre>
Properties:	crosswalk.qdc.namspace.qdc.dcterms
Example Value:	crosswalk.qdc.namspace.qdc.dc = http://purl.org/dc/terms/_

Properties:	crosswalk.qdc.schemaLocation.QDC
Example Value:	<pre>crosswalk.qdc.schemaLocation.QDC = http://www.purl.org/dc/terms \     http://dublincore.org/schemas/xmls/qdc/2006/01/06/dcterms.xsd \     http://purl.org/dc/elements/1.1 \     http://dublincore.org/schemas/xmls/qdc/2006/01/06/dc.xsd</pre>
Properties:	crosswalk.qdc.properties.QDC
Example Value:	crosswalk.qdc.properties.QDC = crosswalks/QDC.properties
Informational Note:	Configuration of the QDC Crosswalk dissemination plugin for Qualified DC. (Add lower-case name for OAI-PMH. That is, change QDC to gdc.)}}

In the property key "crosswalk.gdc.properties.QDC" the value of this property is a path to a separate properties file containing the configuration for this crosswalk. The pathname is relative to the DSpace configuration directory /[dspace]/config. Referring back to the "Example Value" for this property key, one has crosswalks/qdc.properties which defines a crosswalk named QDC whose configuration comes from the file [dspace] /config/crosswalks/qdc.properties.

You will also need to configure the namespaces and schema location strings for the XML output generated by this crosswalk. The namespaces properties names are formatted:

crosswalk.qdc.namespace.prefix = uri

where *prefix* is the namespace prefix and *uri* is the namespace URI. See the above Property and Example Value keys as the default dspace.cfg has been configured.

The QDC crosswalk properties file is a list of properties describing how DSpace metadata elements are to be turned into elements of the Qualified DC XML output document. The property name is a concatenation of the metadata schema, element name, and optionally the qualifier. For example, the contributor.author element in the native Dublin Core schema would be: dc.contributor.author.The value of the property is an XML fragment, the element whose value will be set to the value of the metadata field in the property key.

For example, in this property:

dc.coverage.temporal = <dcterms:temporal />

the generated XML in the output document would look like, e.g.: <dcterms:temporal>Fall, 2005</dcterms:temporal>

#### **Configuring Crosswalk Plugins**

Ingestion crosswalk plugins are configured as named or self-named plugins for the interface org.dspace.content.crosswalk. IngestionCrosswalk. Dissemination crosswalk plugins are configured as named or self-named plugins for the interface org.dspace.content.crosswalk.DisseminationCrosswalk.

You can add names for existing crosswalks, add new plugin classes, and add new configurations for the configurable crosswalks as noted below.

#### **Configuring Packager Plugins**

Package ingester plugins are configured as named or self-named plugins for the interface org.dspace.content.packager.PackageIngester. Package disseminator plugins are configured as named or self-named plugins for the interface org.dspace.content.packager. PackageDisseminator.

You can add names for the existing plugins, and add new plugins, by altering these configuration properties. See the Plugin Manager architecture for more information about plugins.

### **Event System Configuration**

If you are unfamiliar with the Event System in DSpace, and require additional information with terms like "Consumer" and "Dispatcher" please refer to Event SystemPrototype.

Property:	event.dispatcher.default.class
Example Value:	<pre>event.dispatcher.default.class = org.dspace.event.BasicDispatcher</pre>
Informational Note:	This is the default synchronous dispatcher (Same behavior as traditional DSpace).
Property:	event.dispatcher.default.consumers
Example Value:	<pre>event.dispatcher.default.consumers = search, browse, eperson</pre>
Informational Note:	This is the default synchronous dispatcher (Same behavior as traditional DSpace).

Property:	event.dispatcher.noindex.class
Example Value:	<pre>event.dispatcher.noindex.class = org.dspace.event.BasicDispatcher</pre>
Informational Note:	The noindex dispatcher will not create search or browse indexes (useful for batch item imports).
Property:	event.dispatcher.noindex.consumers
Example Value:	<pre>event.dispatcher.noindex.consumers = eperson</pre>
Informational Note:	The noindex dispatcher will not create search or browse indexes (useful for batch item imports).
Property:	event.consumer.search.class
Example Value:	<pre>event.consumer.search.class = org.dspace.search.SearchConsumer</pre>
Informational Note:	Consumer to maintain the search index.
Property:	event.consumer.search.filters
Example Value:	<pre>{{event.consumer.search.filters = }} Community   Collection   Item   Bundle+Add   Create   Modify   Modify_Metadata   Delete   Remove</pre>
Informational Note:	Consumer to maintain the search index.
Property:	event.consumer.browse.class
Example Value:	event.consumer.browse.class = org.dspace.browse.BrowseConsumer
Informational Note:	Consumer to maintain the browse index.
Property:	event.consumer.browse.filters
Example Value:	event.consumer.browse.filters = Community   Collection   Item   Bundle+Add   Create   Modify   Modify_Metadata   Delete   Remove
Informational Note:	Consumer to maintain the browse index.
Property:	event.consumer.eperson.class
Example Value:	<pre>event.consumer.eperson.class = org.dspace.eperson.EPersonConsumer</pre>
Informational Note:	Consumer related to EPerson changes
Property:	event.consumer.eperson.filters
Example Value:	<pre>event.consumer.eperson.filters = EPerson+Create</pre>
Informational Note:	Consumer related to EPerson changes
Property:	event.consumer.test.class
Example Value:	<pre>event.consumer.test.class = org.dspace.event.TestConsumer</pre>
Informational Note:	Test consumer for debugging and monitoring. Commented out by default.
Property:	event.consumer.test.filters
Example Value:	event.consumer.test.filters = All+All
Informational Note:	Test consumer for debugging and monitoring. Commented out by default.
Property:	testConsumer.verbose
Example Value:	testConsumer.verbose = true
Informational Note:	Set this to true to enable testConsumer messages to standard output. Commented out by default.

### Embargo

DSpace embargoes utilize standard metadata fields to hold both the "terms" and the "lift date". Which fields you use are configurable, and no specific metadata element is dedicated or predefined for use in embargo. Rather, you specify exactly what field you want the embargo system to examine when it needs to find the terms or assign the lift date.

Propert	embargo.field.terms
y:	

Exampl	embargo.field.terms = SCHEMA.ELEMENT.QUALIFIER
e Value:	
Informa tional Note:	Embargo terms will be stored in the item metadata. This property determines in which metadata field these terms will be stored. An example could be dc.embargo.terms
Propert y:	embargo.field.lift
Exampl e Value:	embargo.field.lift = SCHEMA.ELEMENT.QUALIFIER
Informa tional Note:	The Embargo lift date will be stored in the item metadata. This property determines in which metadata field the computed embargo lift date will be stored. You may need to create a DC metadata field in your Metadata Format Registry if it does not already exist. An example could be dc.embargo.liftdate
Propert y:	embargo.terms.open
Exampl e Value:	embargo.terms.open = forever
Informa tional Note:	You can determine your own values for the embargo.field.terms property (see above). This property determines what the string value will be for indefinite embargos. The string in terms field to indicate indefinite embargo.
Propert y:	plugin.single.org.dspace.embargo.EmbargoSetter
Exampl e Value:	<pre>plugin.single.org.dspace.embargo.EmbargoSetter = org.dspace.embargo.DefaultEmbargoSetter</pre>
Informa tional Note:	To implement the business logic to set your embargos, you need to override the EmbargoSetter class. If you use the value DefaultEmbargoSetter, the default implementation will be used.
Propert y:	plugin.single.org.dspace.embargo.EmbargoLifter
Exampl e Value:	<pre>plugin.single.org.dspace.embargo.EmbargoLifter = org.dspace.embargo.DefaultEmbargoLifter</pre>
Informa tional Note:	To implement the business logic to lift your embargos, you need to override the EmbargoLifter class. If you use the value DefaultEmbargoLifter, the default implementation will be used.
More Emb	argo Details

More details on Embargo configuration, including specific examples can be found in the Embargo section of the documentation.

### **Checksum Checker Settings**

DSpace now comes with a Checksum Checker script ([dspace]/bin/dspace checker) which can be scheduled to verify the checksum of every item within DSpace. Since DSpace calculates and records the checksum of every file submitted to it, this script is able to determine whether or not a file has been changed (either manually or by some sort of corruption or virus). The idea being that the earlier you can identify a file has changed, the more likely you'd be able to recover it (assuming it was not a wanted change).

Propert y:	plugin.single.org.dspace.checker.BitstreamDispatcher
Exampl e Value:	<pre>plugin.single.org.dspace.checker.BitstreamDispatcher = org.dspace.checker.SimpleDispatcher</pre>
Informa tional Note:	The Default dispatcher is case non is specified.
Propert y:	checker.retention.default

Exampl e Value:	checker.retention.default = 10y
Informa tional Note:	This option specifies the default time frame after which all checksum checks are removed from the database (defaults to 10 years). This means that after 10 years, all successful or unsuccessful matches are removed from the database.
Propert y:	checker.retention.CHECKSUM_MATCH
Exampl e Value:	checker.retention.CHECKSUM_MATCH = 8w
Informa tional Note:	This option specifies the time frame after which a successful match will be removed from your DSpace database (defaults to 8 weeks). This means that after 8 weeks, all successful matches are automatically deleted from your database (in order to keep that database table from growing too large).
More Che	cksum Checking Details

For more information on using DSpace's built-in Checksum verification system, see the section on Validating CheckSums of Bitstreams.

### Item Export and Download Settings

It is possible for an authorized user to request a complete export and download of a DSpace item in a compressed zip file. This zip file may contain the following: dublin\_core.xml license.txt contents (*listing of the contents*)

handle file itself and the extract file if available

The configuration settings control several aspects of this feature:

Property:	org.dspace.app.itemexport.work.dir
Example Value:	<pre>org.dspace.app.itemexport.work.dir = \${dspace.dir}/exports</pre>
Informati onal Note:	The directory where the exports will be done and compressed.
Property:	org.dspace.app.itemexport.download.dir
Example Value:	<pre>org.dspace.app.itemexport.download.dir = \${dspace.dir}/exports/download</pre>
Informati onal Note	The directory where the compressed files will reside and be read by the downloader.
Property:	org.dspace.app.itemexport.life.span.hours
Example Value:	<pre>org.dspace.app.itemexport.life.span.hours = 48</pre>
Informati onal Note	The length of time in hours each archive should live for. When new archives are created this entry is used to delete old ones.
Property:	org.dspace.app.itemexport.max.size
Example Value:	org.dspace.app.itemexport.max.size = 200
Informati onal Note	The maximum size in Megabytes (Mb) that the export should be. This is enforced before the compression. Each bitstream's size in each item being exported is added up, if their cumulative sizes are more than this entry the export is not kicked off.

### **Subscription Emails**

DSpace, through some advanced installation and setup, is able to send out an email to collections that a user has subscribed. The user who is subscribed to a collection is emailed each time an item id added or modified. The following property key controls whether or not a user should be notified of a modification.

Property:	eperson.subscription.onlynew
Example Value:	eperson.subscription.onlynew = true

Informational	For backwards compatibility, the subscription emails by default include any modified items. The property key is COMMENTED OUT
Note:	by default.

### **Hiding Metadata**

It is now possible to hide metadata from public consumption that is only available to the Administrator.

Proper ty:	metadata.hide.dc.description.provenance
Examp le Value:	<pre>metadata.hide.dc.description.provenance = true</pre>
Inform ational Note:	<ul> <li>Hides the metadata in the property key above except to the administrator. Fields named here are hidden in the following places UNLESS the logged-in user is an Administrator:</li> <li>1. XMLUI metadata XML view, and Item splash pages (long and short views).</li> <li>2. JSPUI Item splash pages</li> <li>3. OAI-PMH server.</li> </ul>
	To designate a field as hidden, add a property here in the form: metadata.hide.SCHEMA.ELEMENT.QUALIFIER = true. This default configuration hides the dc.description.provenance field, since that usually contains email addresses which ought to be kept private and is mainly of interest to administrators.

### **Settings for the Submission Process**

These settings control three aspects of the submission process: thesis submission permission, whether or not a bitstream file is required when submitting to a collection and whether to show a progress bar during the file upload.

Property:	webui.submit.blocktheses
Example Value:	webui.submit.blocktheses = false
Informati onal Note:	Controls whether or not the UI blocks a submission which is marked as a thesis.
Property:	webui.submit.upload.required
Example Value:	<pre>webui.submit.upload.required = true</pre>
Informati onal Note:	Whether or not a file is <b>required</b> to be uploaded during the "Upload" step in the submission process. The default is true. If set to "false", then the submitter (human being) has the option to skip the uploading of a file.
Property:	webui.submit.upload.html5
Example Value:	<pre>webui.submit.upload.html5 = true</pre>
Informati onal Note:	If the browser supports it, JSPUI uses html5 File API to enhance file upload. If this property is set to false the enhanced file upload is not used even if the browser would support it.
Property:	webui.submit.upload.progressbar
Example Value:	webui.submit.upload.progressbar = true
Informati onal Note:	Whether to show a progress bar during file upload. Please note that to work this feature requires a JSON endpoint (json/uploadProgress) that is enabled by default. See the named plugin for the interface org.dspace.app.webui.json.JSONRequest org.dspace.app.webui.json.UploadProgressJSON = uploadProgress
	This property is actually supported only by the JSPUI. The XMLUI doesn't yet provide a progress bar indicator for file upload.

Configuring the Sherpa/RoMEO Publishers Policy Database Integration

DSpace Repository	<u>Profile: atmire nv</u> l <u>Logout</u>
DSpace Home → TestComm → testCol → Item submission	
Item submission	Search DSpace
Describe   Describe   Describe   Uploed   Review   License   Complete  Complete	Go
Upload File(s)	Search DSpace     This Collection
File:	Advanced Search
Please enter the full path of the file on your computer corresponding to your item. If you click "Browse", a new window will allow you to select the file from your computer.	Browse
Choose File No file chosen File Description: Optionally, provide a brief description of the file, for example "Main article", or "Experiment	All of DSpace Communities & Collections By Issue Date Authors Titles Subjects
data readings".	Subjects This Collection By Issue Date Authors Titles Subjects
	My Account
Publisher information	Logout Profile Submissions
Information from Journal: A Life in the Day (1366-6882) Publisher Information: Emerald RoMEO Colour: green Mare mini	Context
Journal: A obra nasce (1645-8729) Publisher Information: <u>Edições Universidade Fernando Pessoa</u> RoMEO Colour: <mark>blue</mark> (More Info)	Edit Collection Item Mapper Export Collection Export Metadata
Journal: AAOHN Journal (0891-0162) Publisher information: <u>Slack</u> RoMEO Colour: initin ( <u>More into</u> )	Administrative
Journal: Abacus (0001-3072) Publisher information: <u>Wiley</u> RoMEO Colour: <mark>yellow</mark> ( <u>More info</u> )	People Groups Authorizations Registries
To check the copyright and self-archiving policies per journal or publisher, please consult <u>SHERPA/RoMEO</u> .	Items Withdrawn Items
Files Uploaded	
Primary File Size Description Format	Curation Tasks

DSpace 4.0 introduced integration with the Sherpa/RoMEO Publishers Policy Database in order to allow displaying the publisher policy in the submission upload step. The submission step interface is available in JSPUI (since DSpace 4.0) and in XMLUI (since DSpace 5.0) and enabled by default, however to use it in production (over 500 requests per day), you must register for a free API key (see below for details).

Property:	webui.submission.sherparomeo-policy-enabled
Example Value:	webui.submission.sherparomeo-policy-enabled = true
Informational Note:	Controls whether or not the UI submission should try to use the Sherpa/RoMEO Publishers Policy Database Integration (default true )
Property:	sherpa.romeo.url
Example Value:	sherpa.romeo.url = http://www.sherpa.ac.uk/romeo/api29.php
Informational Note:	The Sherpa/RoMEO endpoint. Shared with the authority control feauture for Journal Title autocomplete see AuthorityControlSettings
Property:	sherpa.romeo.apikey
Example Value:	sherpa.romeo.apikey = YOUR-API-KEY
Informational	Allow to use a specific API key to raise the usage limit (500 calls/day for unregistred user).
	You can register for a free api access key at http://www.sherpa.ac.uk/news/romeoapikeys.htm

The functionality rely on understanding to which Journal (ISSN) is related the submitting item. This is done out of box looking to some item metadata but a different strategy can be used as for example look to a metadata authority in the case that the Sherpa/RoMEO autocomplete for Journal is used (see AuthorityControlSettings)

The strategy used to discover the Journal related to the submission item is defined in the spring file /config/spring/api/sherpa.xml

```
<bean class="org.dspace.app.sherpa.submit.SHERPASubmitConfigurationService"</pre>
                  id="org.dspace.app.sherpa.submit.SHERPASubmitConfigurationService">
                  <property name="issnItemExtractors"></property name="issnItemExtractors">
                           <list>
                                     <bean class="org.dspace.app.sherpa.submit.MetadataValueISSNExtractor">
                                              <property name="metadataList"></property name="metadataList">
                                                       <list>
                                                                <value>dc.identifier.issn</value>
                                                       </list>
                                              </property>
                                     </bean>
                                     <!-- Use the follow if you have the SHERPAROMEOJournalTitle enabled
                                     <br/>vbean class="org.dspace.app.sherpa.submit.MetadataAuthorityISSNExtractor">
                                              <property name="metadataList">
                                                       <list>
                                                                <value>dc.title.alternative</value>
                                                       </list>
                                              </property>
                                     </bean> -->
                           </list>
                  </property>
         </bean>
```

### **Configuring Creative Commons License**

The following configurations are for the Creative Commons license step in the submission process. Submitters are given an opportunity to select a Creative Common license to accompany the item. Creative Commons licenses govern the use of the content. For further details, refer to the Creative Commons website at <a href="http://creativecommons.org">http://creativecommons.org</a>.

Creative Commons licensing is optionally available and may be configured for any given collection that has a defined submission sequence, or be part of the "default" submission process. This process is described in the Submission User Interface section of this manual. There is a Creative Commons step already defined (step 5), but it is commented out, so enabling Creative Commons licensing is typically just a matter of uncommenting the CC License step.

Since DSpace 5.6 Creative Commons licensing is captured in exactly the same way in each UI. The Creative Commons REST API is utilized. This allows DSpace to store metadata references to the selected CC license, while also storing the CC License as a bitstream. The following CC License information are captured:

- The URL of the CC License is stored in the "dc.rights.uri" metadata field (or whatever field is configured in the "cc.license.uri" setting below)
- The name of the CC License is stored in the "dc.rights" metadata field (or whatever field is configured in the "cc.license.name" setting below). This
  only occurs if "cc.submit.setname=true" (default value)
- The RDF version of the CC License is stored in a bitstream named "license\_rdf" in the CC-LICENSE bundle (as long as "cc.submit. addbitstream=true", which is the default value)

#### Behaviour change

Since DSpace 5.6 Creative Commons licensing is captured in exactly the same way in each UI and some fix has been introduced.

For JSPUI users this mean:

- The full (HTML) text of the CC License is not longer stored in a bitstream named "license\_txt" in the CC-LICENSE bundle
- Previous existent license\_txt remain untouched but new item will not receive such bitstream

For XMLUI users:

Commons API XML envelop (
 Unable to locate
 Jira server for this macro. It may be due to Application Link configuration.
 st than 5.6 remain untouched

#### The following configurations (in dspace.cfg) relate to the Creative Commons license process:

Propert y:	cc.api.rooturl
Exampl e Value:	<pre>cc.api.rooturl = http://api.creativecommons.org/rest/1.5</pre>

Informa tional Note:	Generally will never have to assign a different value - this is the base URL of the Creative Commons service API.
Propert y:	cc.license.uri
Exampl e Value:	cc.license.uri = dc.rights.uri
Informa tional Note:	The field that holds the Creative Commons license URI. If you change from the default value (dc.rights. uri), you will have to reconfigure the XMLUI for proper display of license data
Propert y:	cc.license.name
Exampl e Value:	cc.license.name = dc.rights
Informa tional Note:	The field that holds the Creative Commons license Name. If you change from the default value (dc. rights), you will have to reconfigure the XMLUI for proper display of license data
Propert y:	cc.submit.setname
Exampl e Value:	cc.submit.setname = true
Informa tional Note:	If true, the license assignment will add the field configured with the "cc.license.name" with the name of the CC license; if false, only "cc.license.uri" field is added.
Propert y:	cc.submit.addbitstream
Exampl e Value:	cc.submit.addbitstream = true
Informa tional Note:	If true, the license assignment will add a bitstream with the CC license RDF; if false, only metadata field(s) are added.
Propert y:	cc.license.classfilter
Exampl e Value:	cc.license.classfilter = recombo,mark
Informa tional Note:	This list defines the values that will be excluded from the license (class) selection list, as defined by the web service at the URL: http://api.creativecommons.org/rest/1.5/classes
Propert y:	cc.license.jurisdiction
Exampl e Value:	cc.license.jurisdiction = nz
Informa tional Note:	Should a jurisdiction be used? If so, which one? See http://creativecommons.org/international/ for a list of possible codes (e.g. nz = New Zealand, uk = England and Wales, jp = Japan) Commenting out this field will cause DSpace to select the latest, unported CC license (currently version 4.0). However, as Creative Commons 4.0 does not provide jurisdiction specific licenses, if you specify this setting, your DSpace will continue to use older, Creative Commons 3.0 jurisdiction licenses.

### WEB User Interface Configurations

General Web User Interface Configurations In this section of Configuration, we address the agnostic WEB User Interface that is used for JSPUI and XMLUI. Some of the configurations will give information towards customization or refer you to the appropriate documentation.

Prope rty:	webui.licence_bundle.show
Exam ple Value:	<pre>webui.licence_bundle.show = false</pre>
Inform ationa I Note:	Sets whether to display the contents of the license bundle (often just the deposit license in the standard DSpace installation).
Prope rty:	webui.browse.thumbnail.show
Exam ple Value:	<pre>webui.browse.thumbnail.show = true</pre>
Inform ationa I Note:	Controls whether to display thumbnails on browse and search result pages. If you have customized the Browse columnlist, then you must also include a "thumbnail" column in your configuration. (This configuration property key is not used by XMLUI. To show thumbnails using XMLUI, you need to create a theme which displays them).
Prope rty:	webui.browse.thumbnail.maxheight
Exam ple Value:	<pre>webui.browse.thumbnail.maxheight = 80</pre>
Inform ationa I Note:	This property determines the maximum height of the browse/search thumbnails in pixels (px). This only needs to be set if the thumbnails are required to be smaller than the dimensions of thumbnails generated by MediaFilter.
Prope rty:	webui.browse.thumbnail.maxwidth
Exam ple Value:	<pre>webui.browse.thumbnail.maxwidth = 80</pre>
Inform ationa I Note:	This determines the maximum width of the browse/search thumbnails in pixels (px). This only needs to be set if the thumbnails are required to be smaller than the dimensions of thumbnails generated by MediaFilter.
Prope rty:	webui.item.thumbnail.show
Exam ple Value:	<pre>webui.item.thumbnail.show = true</pre>
Inform ationa I Note:	This determines whether or not to display the thumbnail against each bitstream. (This configuration property key is not used by XMLUI. To show thumbnails using XMLUI, you need to create a theme which displays them).
Prope rty:	webui.browse.thumbnail.linkbehavior
Exam ple Value:	<pre>webui.browse.thumbnail.linkbehavior = item</pre>
Inform ationa I Note:	This determines where clicks on the thumbnail in browse and search screens should lead. The only values currently supported are "item" or "bitstream", which will either take the user to the item page, or directly download the bitstream.
Prope rty:	thumbnail.maxwidth
Exam ple Value:	thumbnail.maxwidth = 80
Inform ationa I Note:	This property sets the maximum width of generated thumbnails that are being displayed on item pages.

Exam ple Value:	thumbnail.maxheight = 80
Inform ationa I Note:	This property sets the maximum height of generated thumbnails that are being displayed on item pages.
Prope rty:	webui.preview.enabled
Exam ple Value:	<pre>webui.preview.enabled = false</pre>
Inform ationa I Note:	Whether or not the user can "preview" the image.
Prope rty:	webui.preview.maxwidth
Exam ple Value:	<pre>webui.preview.maxwidth = 600</pre>
Inform ationa I Note:	This property sets the maximum width for the preview image.
Prope rty:	webui.preview.maxheight
Exam ple Value:	<pre>webui.preview.maxheight = 600</pre>
Inform ationa I Note:	This property sets the maximum height for the preview image.
Prope rty:	webui.preview.brand
Exam ple Value:	<pre>webui.preview.brand = My Institution Name</pre>
Inform ationa I Note:	This is the brand text that will appear with the image.
Prope rty:	webui.preview.brand.abbrev
Exam ple Value:	webui.preview.brand.abbrev = MyOrg
Inform ationa I Note:	An abbreviated form of the full Branded Name. This will be used when the preview image cannot fit the normal text.
Prope rty:	webui.preview.brand.height
Exam ple Value:	<pre>webui.preview.brand.height = 20</pre>
Inform ationa I Note:	The height (in px) of the brand.
Prope rty:	webui.preview.brand.font
Exam ple Value:	<pre>webui.preview.brand.font = SansSerif</pre>

Inform ationa I Note:	This property sets the font for your Brand text that appears with the image.
Prope rty:	webui.preview.brand.fontpoint
Exam ple Value:	<pre>webui.preview.brand.fontpoint = 12</pre>
Inform ationa I Note:	This property sets the font point (size) for your Brand text that appears with the image.
Prope rty:	webui.preview.dc
Exam ple Value:	webui.preview.dc = rights
Inform ationa I Note:	The Dublin Core field that will display along with the preview. This field is optional.
Prope rty:	webui.strengths.show
Exam ple Value:	<pre>webui.strengths.show = false</pre>
Inform ationa I Note:	Determines if communities and collections should display item counts when listed. The default behavior if omitted, is false.
Prope rty:	webui.strengths.cache
Exam ple Value:	webui.strengths.cache = false
Inform ationa I Note:	When showing the strengths (i.e. item counts), should they be counted in real time, or fetched from the cache. Counts fetched in real time will perform an actual count of the index contents every time a page with this feature is requested, which may not scale. If you set the property key is set to cache ("true"), the counts will be cached on first load

### **Browse Index Configuration**

The browse indexes for DSpace can be extensively configured. These configurations are used by Discovery. This section of the configuration allows you to take control of the indexes you wish to browse, and how you wish to present the results. The configuration is broken into several parts: defining the indexes, defining the fields upon which users can sort results, defining truncation for potentially long fields (e.g. authors), setting cross-links between different browse contexts (e.g. from an author's name to a complete list of their items), how many recent submissions to display, and configuration for item mapping browse.

Property:	webui.browse.index. <n></n>	
Example Value:	<pre>webui.browse.index.1 = dateissued:item:dateissued webui.browse.index.2 = author:metadata:dc.contributor.*,dc.creator:text</pre>	
Informational Note:	This is an example of how one "Defines the Indexes". See "Defining the Indexes" in the next sub-section.	
Property:	webui.itemlist.sort-option. <n></n>	
Example Value:	<pre>webui.itemlist.sort-option.1 = title:dc.title:title</pre>	
Informational Note:	This is an example of how one "Defines the Sort Options". See "Defining Sort Options" in the following sub-section.	

#### Defining the storage of the Browse Data

Optionally, you may configure a custom implementation use for the Browse DAOs both for read operations (create/update operations are handled by Event Consumers). However, as of DSpace 6, DSpace only includes one out-of-the-box option:

 SOLR Browse Engine (SOLR DAOs), default since DSpace 4.0 - This enables Apache Solr to be utilized as a backend for all browsing of DSpace. This option requires that you have Discovery (Solr search/browse engine) enabled in your DSpace.

Property:	browseDAO.class
Example Value:	browseDAO.class = org.dspace.browse.SolrBrowseDAO
Information al Note:	This property configures the Java class that is used for READ operations by the Browse System. You need to have Discovery enabled (this is the default since DSpace 4.0) to use the Solr Browse DAOs

**Defining the Indexes** If you make changes in this section be sure to update your SOLR indexes running the Discovery Maintenance Script, see Discovery

DSpace comes with four default indexes pre-defined: author, title, date issued, and subjects. Users may also define additional indexes or re-configure the current indexes for different levels of specificity. For example, the default entries that appear in the dspace cfg as default installation:

```
webui.browse.index.1 = dateissued:item:dateissued
webui.browse.index.2 = author:metadata:dc.contributor.*,dc.creator:text
webui.browse.index.3 = title:item:title
webui.browse.index.4 = subject:metadata:dc.subject.*:text
#webui.browse.index.5 = dateaccessioned:item:dateaccessioned
```

There are two types of indexes which are provided in this default integration:

- "item" indexes which have a format of webui.browse.index.<n> = <index-name> : item : <sort-type> : (asc | desc) • "metadata" indexes which have a format of webui.browse.index.<n> = <index-name> : metadata : <comma-separated-list
  - of-metadata-fields> : (date | text) : (asc | dec) : <sort-type>

Please notice that the punctuation is paramount in typing this property key in the dspace.cfg file. The following table explains each element:

Element	Definition and Options (if available)
webui. browse. index. <n></n>	<i>n</i> is the index number. The index numbers must start from 1 and increment continuously by 1 thereafter. Deviation from this will cause an error during install or a configuration update. So anytime you add a new browse index, remember to increase the number. (Commented out index numbers may be used over again).
<index- name&gt;</index- 	The name by which the index will be identified. In order for the DSpace UI to display human-friendly description for this index, you'll need to update either your Messages.properties (JSPUI) or messages.xml (XMLUI) with new message keys referencing this <index-name>.</index-name>
	JSPUI Example (Messages.properties):
	• browse.type.metadata. <index-name> = My New Field</index-name>
	XMLUI Example (messages.xml):
	<pre>• <message key="xmlui.ArtifactBrowser.Navigation.browse_&lt;index-name&gt;">My New Fields</message> • <message key="xmlui.ArtifactBrowser.ConfigurableBrowse.title.metadata.&lt;index-name&gt;">Browsing { 0 } by My New Field { 1 }</message></pre>
	<ul> <li><message key="xmlui.ArtifactBrowser.ConfigurableBrowse.trail.metadata.&lt;index-name&gt;">Browsing { 0 } by My New Field</message></li> </ul>
	• <message key="xmlui.ArtifactBrowser.ConfigurableBrowse.&lt;index-name&gt;.column_heading">My New Field&lt; /message&gt;</message>
(metadat a item)	<ul> <li>Only two options are available: "metadata" or "item"</li> <li>"metadata" indexes allow you to index all items based on one or more metadata fields. The list of fields should be provided as part of the "metadata" configuration. Only items which have values for these fields will appear in this index (e.g. if you have a "metadata" index for "dc.subject.*", an item will not appear in that browse/search if it doesn't have a "dc.subject.*" value). The browse index will have to parts: first it lists all values of the specified metadata fields. If the user select one of these values the index lists all items in which the specified metadata field is assigned with the selected value.</li> <li>Note: If you set a <sort-type> to be used, this sort type is not used on the values of the metadata fields but on the order of the items when listing all items that have a specific value of the metadata field.</sort-type></li> <li>"item" indexes provide you with a browseable list of ALL items in the site, sorted by a particular metadata field. The field this index is sorted by is referenced by <sort-option-name> (which should refer to a corresponding "webui.itemlist.sort-option.<n>" setting see Defining Sort Options below for more information)</n></sort-option-name></li> </ul>
<schema- prefix&gt;</schema- 	(Only for "metadata" indexes) The schema used for the field to be index. The default is dc (for Dublin Core).
<element></element>	(Only for "metadata" indexes) The schema element. In Dublin Core, for example, the author element is referred to as "Contributor". The user should consult the default Dublin Core Metadata Registry table in Appendix A.

<qualifi er&gt;</qualifi 	(Only for "metadata" indexes) This is the qualifier to the <element> component. The user has two choices: an asterisk "" or a proper qualifier of the element. The asterisk is a wildcard and causes DSpace to index all types of the schema element. For example, if you have the element "contributor" and the qualifier "" then you would index all contributor data regardless of the qualifier. Another example, you have the element "subject" and the qualifier "lcsh" would cause the indexing of only those fields that have the qualifier "lcsh". (This means you would only index Library of Congress Subject Headings and not all data elements that are subjects.</element>
<sort- type&gt;</sort- 	<ul> <li>(Optional, should be set for "item" indexes) This refers to the sort type / data type of the field:</li> <li>date the index type will be treated as a date object and sorted as such</li> <li>text the index type will be treated as plain text and sorted as such</li> <li>(any other value refers to a custom <sort-type> which should be defined in a corresponding webui.itemlist.sort-option.<n> setting. See Defining Sort Options below for more information.)</n></sort-type></li> </ul>
<sort- order&gt;</sort- 	(Optional) The default sort order. Choose asc (ascending) or desc (descending). Ascending is the default value, but descending may be useful for date-based indexes (e.g. to display most recent submissions first)

#### **Defining Sort Options**

If you make changes in this section be sure to update your SOLR indexes running the Discovery Maintenance Script, see Discovery

Sort options/types will be available when browsing a list of items (either on "item" index type above or after selecting a specific value for "metadata" indexes). You can define an arbitrary number of fields to sort on. For example, the default entries that appear in the *dspace.cfg* as default installation:

```
webui.itemlist.sort-option.1 = title:dc.title:title
webui.itemlist.sort-option.2 = dateissued:date.issued:date
webui.itemlist.sort-option.3 = dateaccessioned:dc.date.accessioned:date
```

The format of each entry is web.browse.sort-option.<n> = <sort-type-name>:<schema-prefix>.<element>.<qualifier>:<datatype> . Please notice the punctuation used between the different elements. The following table explains the each element:

Element	Definition and Options (if available)
<pre>webui.itemlist. sort-option.<n></n></pre>	<i>n</i> is an arbitrary number you choose.
<sort-type-name></sort-type-name>	The name by which the sort option will be identified. This is the name by which it is referred in the "webui.browse.index" settings (see Defining the Indexes).
<schema-prefix></schema-prefix>	The schema used for the field to be sorted on in the index. The default is dc (for Dublin Core).
<element></element>	The schema element. In Dublin Core, for example, the author element is referred to as "Contributor". The user should consult the default Dublin Core Metadata Registry table in Appendix A.
<qualifier></qualifier>	This is the qualifier to the <element> component. The user has two choices: an asterisk "*" or a proper qualifier of the element.</element>
<datatype></datatype>	This refers to the datatype of the field: date the sort field will be treated as a date object text the sort field will be treated as plain text. title the sort field will be treated like a title, which will include a link to the item page

#### **Other Browse Options**

We set other browse values in the following section.

Pro pert y:	<pre>webui.browse.metadata.show-freq.&lt; n &gt;</pre>
Exa mpl e Val ue:	webui.browse.metadata.show-freq.1 = false
Info rma tion al Not e:	This enable/disable the show of frequencies (count) in metadata browse <n> refers to the browse configuration. As default frequencies are shown for all metadata browse</n>

Pro pert y:	plugin.named.org.dspace.sort.OrderFormatDelegate
Exa mpl e Val ue:	<pre>plugin.named.org.dspace.sort.OrderFormatDelegate = \ org.dspace.sort.OrderFormatTitleMarc21=title</pre>
Info rma tion al Not e:	This sets the option for how the indexes are sorted. All sort normalizations are carried out by the OrderFormatDelegate. The plugin manager can be used to specify your own delegates for each datatype. The default datatypes (and delegates) are:
	<pre>author = org.dspace.sort.OrderFormatAuthor title = org.dspace.sort.OrderFormatTitle text = org.dspace.sort.OrderFormatText</pre>
	If you redefine a default datatype here, the configuration will be used in preferences to the default. However, if you do not explicitly redefine a datatype, then the default will still be used in addition to the datatypes you do specify. As of DSpace release 1.5.2, the multi-lingual MARC21 title ordering is configured as default, as shown in the example above. To use the previous title ordering (before release 1.5.2), comment out the configuration in your <i>dspace.cfg</i> file.

### **Browse Index Authority Control Configuration**

Property:	webui.browse.index. <n></n>	
Example Value:	<pre>webui.browse.index.5 = lcAuthor:metadataAuthority:dc.contributor.author:authority</pre>	
Informational Note:		

#### Tag cloud

Apart from the single (type=metadata) and full (type=item) browse pages, tag cloud is a new way to display the unique values of a metadata field.

To enable "tag cloud" browsing for a specific index you need to declare it in the dspace.cfg configuration file using the following option:

Property:	webui.browse.index.tagcloud. <n></n>	
Example Value:	webui.browse.index.tagcloud.1 = true	
Informational Note:	formational Enable/Disable tag cloud in browsing for a specific index. 'n' is the index number of the specific index which needs to be of type ote:	
	Possible values: true, false	
	Default value is false.	
	If no option exists for a specific index, it is assumed to be false. You do not have to re-index discovery when you change this configuration	

#### Tag cloud configuration

The appearance configuration for the tag cloud is located in the Discovery xml configuration file (*dspace/config/spring/api/discovery.xml*). Without configuring the appearance, the default one will be applied to the tag cloud

In this file, there must be a bean named "browseTagCloudConfiguration" of class "org.dspace.discovery.configuration.TagCloudConfiguration". This bean can have any of the following properties. If some is missing, the default value will be applied.

displayScore	Should display the score of each tag next to it? Default: false	
shouldCenter	Should display the tag as center aligned in the page or left aligned? Possible values: true   false. Default: true	
totalTags	How many tags will be shown. Value -1 means all of them. Default: -1	
cloudCase	The letter case of the tags.	
	Possible values: Case.LOWER   Case.UPPER   Case.CAPITALIZATION   Case.PRESERVE_CASE   Case.CASE_SENSITIVE	
	Default: Case.PRESERVE_CASE	
randomColo rs	If the 3 css classes of the tag cloud should be independent of score (random=yes) or based on the score. Possible values: true   false . Default: true	
fontFrom	The font size (in em) for the tag with the lowest score. Possible values: any decimal. Default: 1.1	

fontTo	The font size (in em) for the tag with the lowest score. Possible values: any decimal. Default: 3.2	
cuttingLevel	The score that tags with lower than that will not appear in the rag cloud. Possible values: any integer from 1 to infinity. Default: 0	
ordering	The ordering of the tags (based either on the name or the score of the tag)	
	Possible values: Tag.NameComparatorAsc   Tag.NameComparatorDesc   Tag.ScoreComparatorAsc   Tag.ScoreComparatorDesc	
	Default: Tag.GreekNameComparatorAsc	

When tagCloud is rendered there are some CSS classes that you can change in order to change the tagcloud appearance.

Class	Note
tagcloud	General class for the whole tagcloud
tagcloud_1	Specific tag class for tag of type 1 (based on score)
tagcloud_2	Specific tag class for tag of type 2 (based on score)
tagcloud_3	Specific tag class for tag of type 3 (based on score)

### Author (Multiple metadata value) Display

This section actually applies to any field with multiple values, but authors are the define case and example here.

Property:	webui.browse.author-field
Example Value:	<pre>webui.browse.author-field = dc.contributor.*</pre>
Informational Note:	This defines which field is the author/editor, etc. listing.

Replace dc.contributor.\* with another field if appropriate. The field should be listed in the configuration for webui.itemlist.columns, otherwise you will not see its effect. It must also be defined in webui.itemlist.columns as being of the datatype *text* otherwise the functionality will be overridden by the specific data type feature. (This setting is not used by the XMLUI as it is controlled by your theme).

Now that we know which field is our author or other multiple metadata value field we can provide the option to truncate the number of values displayed by default. We replace the remaining list of values with "et al" or the language pack specific alternative. Note that this is just for the default, and users will have the option of changing the number displayed when they browse the results. See the following table:

Property:	webui.browse.author-limit
Example Value:	<pre>webui.browse.author-limit = &lt; n &gt;</pre>
Informational Note:	Where $< n >$ is an integer number of values to be displayed. Use $-1$ for unlimited (the default value).

### Links to Other Browse Contexts

We can define which fields link to other browse listings. This is useful, for example, to link an author's name to a list of just that author's items. The effect this has is to create links to browse views for the item clicked on. If it is a "single" type, it will link to a view of all the items which share that metadata element in common (i.e. all the papers by a single author). If it is a "full" type, it will link to a view of the standard full browse page, starting with the value of the link clicked on.

Prop erty:	<pre>webui.browse.link.<n></n></pre>
Exa mple Valu e:	<pre>webui.browse.link.1 = author:dc.contributor.*</pre>
Infor mati onal Note:	This is used to configure which fields should link to other browse listings. This should be associated with the name of one of the browse indexes ( <pre>webui.browse.index.n</pre> with a metadata field listed in <pre>webui.itemlist.columns</pre> above. If this condition is not fulfilled, cross-linking will not work. Note also that crosslinking only works for metadata fields not tagged as title in <pre>webui.itemlist.columns</pre> .

The format of the property key is *webui.browse.link.<n> = <index name>:<display column metadata>* Please notice the punctuation used between the elements.

Element	Definition and Options (if available)
webui.browse.link. n	{{ <i>n</i> is an arbitrary number you choose

<index name=""></index>	This need to match your entry for the index name from webui.browse.index property key.
<display column="" metadata=""></display>	Use the DC element (and qualifier)

Examples of some browse links used in a real DSpace installation instance:

webui.browse.link.1 = author:dc.contributor.\* Creates a link for all types of contributors (authors, editors, illustrators, others, etc.) webui.browse.link.2 = subject:dc.subject.lcsh Creates a link to subjects that are Library of Congress only. In this case, you have a browse index that contains only LC Subject Headings webui.browse.link.3 = series:dc.relation.ispartofseries Creates a link for the browse index "Series". Please note this is again, a customized browse index and not part of the DSpace distributed release.

### **Recent Submissions**

Since DSpace 4.0 this applies only to JSPUI. XMLUI uses Discovery to configure the recent submissions.

This allows us to define which index to base Recent Submission display on, and how many we should show at any one time. This uses the PluginManager to automatically load the relevant plugin for the Community and Collection home pages. Values given in examples are the defaults supplied in dspace.cfg

Property:	recent.submission.sort-option
Example Value:	recent.submission.sort-option = dateaccessioned
Informational Note:	Define the sort name (from webui.browse.sort-options) to use for displaying recent submissions. (Only used by JSPUI)
Property:	recent.submissions.count
Example Value:	recent.submissions.count = 5
Informational Note:	Defines how many recent submissions should be displayed at any one time. (Only used by JSPUI)

There will be the need to set up the processors that the PluginManager will load to actually perform the recent submissions query on the relevant pages. This is already configured by default *dspace.cfg* so there should be no need for the administrator/programmer to worry about this.

### **Submission License Substitution Variables**

Property:	plugin.named.org.dspace.content.license. LicenseArgumentFormatter
	(property key broken up for display purposes only)
Example Value:	<pre>plugin.named.org.dspace.content.license.LicenseArgumentFormatter = \     org.dspace.content.license.SimpleDSpaceObjectLicenseFormatter = collection, \     org.dspace.content.license.SimpleDSpaceObjectLicenseFormatter = item, \     org.dspace.content.license.SimpleDSpaceObjectLicenseFormatter = eperson</pre>
Informational Note:	It is possible include contextual information in the submission license using substitution variables. The text substitution is driven by a plugin implementation.

### Syndication Feed (RSS) Settings

This will enable syndication feeds, links display on community and collection home pages. This setting is not used by the XMLUI, as you enable feeds in your theme.

Pro pert y:	webui.feed.enable
Exa mpl e Val ue:	webui.feed.enable = true
Info rma tion al Not e:	By default, RSS feeds are set to true (on) . Change key to "false" to disable.
Pro pert y:	webui.feed.items
Exa mpl e Val ue:	<pre>webui.feed.items = 4</pre>
Info rma tion al Not e:	Defines the number of DSpace items per feed (the most recent submissions)
Pro pert y:	webui.feed.cache.size
Exa mpl e Val ue:	webui.feed.cache.size = 100
Info rma tion al Not e:	Defines the maximum number of feeds in memory cache. Value of "0" will disable caching.
Pro pert y:	webui.feed.cache.age
Exa mpl e Val ue:	webui.feed.cache.age = 48
Info rma tion al Not e:	Defines the number of hours to keep cached feeds before checking currency. The value of "O" will force a check with each request.
Pro pert y:	webui.feed.formats
Exa mpl e Val ue:	<pre>webui.feed.formats = rss_1.0,rss_2.0,atom_1.0</pre>

Info rma tion al Not e:	Defines which syndication formats to offer. You can use more than one; use a comma-separated list. The following list are the available values: rss_0.90, rss_0.91, rss_0.92, rss_0.93, rss_0.94, rss_1.0, rss_2.0, atom_1.0.
Pro pert y:	webui.feed.localresolve
Exa mpl e Val ue:	webui.feed.localresolve = false
Info rma tion al Not e:	By default, (set to false), URLs returned by the feed will point at the global handle resolver (e.g. http://hdl.handle.net/123456789/1). If set to <i>true</i> th e local server URLs are used (e.g. http://myserver.myorg/handle/123456789/1).
Pro pert y:	webui.feed.item.title
Exa mpl e Val ue:	webui.feed.item.title = dc.title
Info rma tion al Not e:	This property customizes each single-value field displayed in the feed information for each item. Each of the fields takes a <b>single</b> metadata field. The form of the key is <scheme prefix="">.<element>.<qualifier> In place of the qualifier, one may leave it blank to exclude any qualifiers or use the wildcard "*" to include all qualifiers for a particular element.</qualifier></element></scheme>
Pro pert y:	webui.feed.item.date
Exa mpl e Val ue:	webui.feed.item.date = dc.date.issued
Info rma tion al Not e:	This property customizes each single-value field displayed in the feed information for each item. Each of the fields takes a <b>single</b> metadata field. The form of the key is <scheme prefix="">.<element>.<qualifier> In place of the qualifier, one may leave it blank to exclude any qualifiers or use the wildcard "*" to include all qualifiers for a particular element.</qualifier></element></scheme>
Pro pert y:	webui.feed.item.description
Exa mpl e Val ue:	<pre>webui.feed.item.description = dc.title, dc.contributor.author, \</pre>
Info rma tion al Not e:	One can customize the metadata fields to show in the feed for each item's description. Elements are displayed in the order they are specified in <i>ds</i> pace.cfg.Like other property keys, the format of this property key is: <i>webui.feed.item.description</i> = <i><scheme i="" prefix<="">&gt;.<i><element< i="">&gt;.<i><qualifier></qualifier></i>. In place of the qualifier, one may leave it blank to exclude any qualifiers or use the wildcard "*" to include all qualifiers for a particular element.</element<></i></scheme></i>
Pro pert y:	webui.feed.item.author

Exa mpl e Val ue:	<pre>webui.feed.item.author = dc.contributor.author</pre>
Info rma tion al Not e:	The name of field to use for authors (Atom only); repeatable.
Pro pert y:	webui.feed.logo.url
Exa mpl e Val ue:	<pre>webui.feed.logo.url = \${dspace.url}/themes/mysite/images/mysite-logo.png</pre>
Info rma tion al Not e:	Customize the image icon included with the site-wide feeds. This must be an absolute URL.
Pro pert y:	webui.feed.item.dc.creator
Exa mpl e Val ue:	<pre>webui.feed.item.dc.creator = dc.contributor.author</pre>
Info rma tion al Not e:	This optional property adds <i>structured</i> DC elements as XML elements to the feed description. They are not the same thing as, for example, <i>webui</i> . <i>feed.item.description</i> . Useful when a program or stylesheet will be transforming a feed and wants separate author, description, date, etc.
Pro pert y:	webui.feed.item.dc.date
Exa mpl e Val ue:	<pre>webui.feed.item.dc.date = dc.date.issued</pre>
Info rma tion al Not e:	This optional property adds <i>structured</i> DC elements as XML elements to the feed description. They are not the same thing as, for example, <i>webui</i> . <i>feed.item.description</i> . Useful when a program or stylesheet will be transforming a feed and wants separate author, description, date, etc.
Pro pert y:	webui.feed.item.dc.description
Exa mpl e Val ue:	<pre>webui.feed.item.dc.description = dc.description.abstract</pre>

Info rma tion al Not e:	This optional property adds <i>structured</i> DC elements as XML elements to the feed description. They are not the same thing as, for example, <i>webui</i> . <i>feed.item.description</i> . Useful when a program or stylesheet will be transforming a feed and wants separate author, description, date, etc.
Pro pert y:	webui.feed.podcast.collections
Exa mpl e Val ue:	webui.feed.podcast.collections = 1811/45183,1811/47223
Info rma tion al Not e:	This optional property enables Podcast Support on the RSS feed for the specified collection handles. The podcast is iTunes compatible and will expose the bitstreams in the items for viewing and download by the podcast reader. Multiple values are separated by commas. For more on using /enabling Media RSS Feeds to share content via iTunesU, see: Enable Media RSS Feeds
Pro pert y:	webui.feed.podcast.communities
Exa mpl e Val ue:	webui.feed.podcast.communities = 1811/47223
Info rma tion al Not e:	This optional property enables Podcast Support on the RSS feed for the specified community handles. The podcast is iTunes compatible and will expose the bitstreams in the items for viewing and download by the podcast reader. Multiple values are separated by commas. For more on using /enabling Media RSS Feeds to share content via iTunesU, see: Enable Media RSS Feeds
Pro pert y:	webui.feed.podcast.mimetypes
Exa mpl e Val ue:	<pre>webui.feed.podcast.mimetypes = audio/x-mpeg,application/pdf</pre>
Info rma tion al Not e:	This optional property for Podcast Support, allows you to choose which MIME types of bitstreams are to be enclosed in the podcast feed. Multiple values are separated by commas. For more on using/enabling Media RSS Feeds to share content via iTunesU, see: Enable Media RSS Feeds
Pro pert y:	webui.feed.podcast.sourceuri
Exa mpl e Val ue:	webui.feed.podcast.sourceuri = dc.source.uri
Info rma tion al Not e:	This optional property for the Podcast Support will allow you to use a value for a metadata field as a replacement for actual bitstreams to be enclosed in the RSS feed. A use case for specifying the external sourceuri would be if you have a non-DSpace media streaming server that has a copy of your media file that you would prefer to have the media streamed from. For more on using/enabling Media RSS Feeds to share content via iTunesU, see: Enable Media RSS Feeds

**OpenSearch Support** 

OpenSearch is a small set of conventions and documents for describing and using "search engines", meaning any service that returns a set of results for a query. See extensive description in the *Business Layer section* of the documentation.

Please note that for result data formatting, OpenSearch uses Syndication Feed Settings (RSS). So, even if Syndication Feeds **are not** enable, they **must** be configured to enable OpenSearch. OpenSearch uses all the configuration properties for DSpace RSS to determine the mapping of metadata fields to feed fields. Note that a new field for authors has been added (used in Atom format only).

Property:	websvc.opensearch.enable
Example Value:	<pre>websvc.opensearch.enable = false</pre>
Information al Note:	Whether or not OpenSearch is enabled. By default, the feature is disabled. Change the property key to "true" to enable.
Property:	websvc.opensearch.uicontext
Example Value:	websvc.opensearch.uicontext = simple-search
Information al Note:	Context for HTML request URLs. Change only for non-standard servlet mapping. IMPORTANT: If you are using XMLUI and have Discovery enabled, this property's value should be changed to <i>discover</i> .
Property:	websvc.opensearch.svccontext
Example Value:	<pre>websvc.opensearch.svccontext = open-search/</pre>
Information al Note:	Context for RSS/Atom request URLs. Change only for non-standard servlet mapping. IMPORTANT: If you are using XMLUI and have Discovery enabled, this property's value should be changed to open-search/ <i>discover</i> .
Property:	websvc.opensearch.autolink
Example Value:	<pre>websvc.opensearch.autolink = true</pre>
Information al Note:	Present autodiscovery link in every page head.
Property:	websvc.opensearch.validity
Example Value:	<pre>websvc.opensearch.validity = 48</pre>
Information al Note:	Number of hours to retain results before recalculating. This applies to the Manakin interface only.
Property:	websvc.opensearch.shortname
Example Value:	websvc.opensearch.shortname = DSpace
Information al Note:	A short name used in browsers for search service. It should be sixteen (16) or fewer characters.
Property:	websvc.opensearch.longname
Example Value:	<pre>websvc.opensearch.longname = \${dspace.name}</pre>
Information al Note:	A longer name up to 48 characters.
Property:	websvc.opensearch.description
Example Value:	<pre>websvc.opensearch.description = \${dspace.name} DSpace repository</pre>
Information al Note:	Brief service description
Property:	websvc.opensearch.faviconurl
Example Value:	_websvc.opensearch.faviconurl = http://www.dspace.org/images/favicon.ico_
Information al Note:	Location of favicon for service, if any. They must by 16 x 16 pixels. You can provide your own local favicon instead of the default.

Property:	websvc.opensearch.samplequery
Example Value:	<pre>websvc.opensearch.samplequery = photosynthesis</pre>
Information al Note:	Sample query. This should return results. You can replace the sample query with search terms that should actually yield results in your repository.
Property:	websvc.opensearch.tags
Example Value:	websc.opensearch.tags = IR DSpace
Information al Note:	Tags used to describe search service.
Property:	websvc.opensearch.formats
Example Value:	<pre>websvc.opensearch.formats = html,atom,rss</pre>
Information al Note:	Result formats offered. Use one or more comma-separated from the list: html, atom, rss. Please note that html is required for auto discovery in browsers to function, and must be the first in the list if present.

### **Content Inline Disposition Threshold**

The following configuration is used to change the disposition behavior of the browser. That is, when the browser will attempt to open the file or download it to the user-specified location. For example, the default size is 8MB. When an item being viewed is larger than 8MB, the browser will download the file to the desktop (or wherever you have it set to download) and the user will have to open it manually.

Property:	webui.content_disposition_threshold
Example value:	<pre>webui.content_disposition_threshold = 8388608</pre>
Informational Note:	The default value is set to 8MB. This property key applies to the JSPUI interface.
Property:	xmlui.content_disposition_threshold
Example Value:	<pre>xmlui.content_disposition_threshold = 8388608</pre>
Informational Note:	The default value is set to 8MB. This property key applies to the XMLUI (Manakin) interface.

Other values are possible: 4 MB = 41943048 MB = 838860816 MB = 16777216

### Multi-file HTML Document/Site Settings

The setting is used to configure the "depth" of request for html documents bearing the same name.

Pr op er ty:	webui.html.max-depth-guess
E xa pl e V al ue:	<pre>webui.html.max-depth-guess = 3</pre>
Inf or m ati on al N ot e:	When serving up composite HTML items in the JSP UI, how deep can the request be for us to serve up a file with the same name? For example, if one receives a request for "foo/bar/index.html" and one has a bitstream called just "index.html", DSpace will serve up the former bitstream (foo/bar /index.html) for the request if webui.html.max-depth-guess is 2 or greater. If webui.html.max-depth-guess is 1 or less, then DSpace would not serve that bitstream, as the depth of the file is greater. If webui.html.max-depth-guess is zero, the request filename and path must always exactly match the bitstream name. The default is set to 3.

Pr op er ty:	xmlui.html.max-depth-guess
E xa pl e V al ue:	<pre>xmlui.html.max-depth-guess = 3</pre>
Inf or m ati on al N ot e:	When serving up composite HTML items in the XMLUI, how deep can the request be for us to serve up a file with the same name? For example, if one receives a request for "foo/bar/index.html" and one has a bitstream called just "index.html", DSpace will serve up the former bitstream (foo/bar /index.html) for the request if <i>webui.html.max-depth-guess</i> is 2 or greater. If <i>xmlui.html.max-depth-guess</i> is 1 or less, then DSpace would not serve that bitstream, as the depth of the file is greater. If _webui.html.max-depth-guess _is zero, the request filename and path must always exactly match the bitstream name. The default is set to 3.

### **Sitemap Settings**

To aid web crawlers index the content within your repository, you can make use of sitemaps.

Pro per ty:	sitemap.dir
Ex am ple Val ue:	<pre>sitemap.dir = \${dspace.dir}/sitemaps</pre>
Inf or ma tio nal Not e:	The directory where the generate sitemaps are stored.
Pro per ty:	sitemap.engineurls
Ex am ple Val ue:	sitemap.engineurls = http://www.google.com/webmasters/sitemaps/ping?sitemap=
Inf or ma tio nal Not e:	Comma-separated list of search engine URLs to "ping" when a new Sitemap has been created. Include everything except the Sitemap UL itself (which will be URL-encoded and appended to form the actual URL "pinged").Add the following to the above parameter if you have an application ID with Yahoo: http://search.yahooapis.com/SiteExplorererService/V1/updateNotification?appid=REPLACE_ME?url= (Replace the component _REPLACE_ME with your application ID). There is no known "ping" URL for MSN/Live search.

### **Authority Control Settings**

Two features fall under the header of Authority Control: Choice Management and Authority Control of Item ("DC") metadata values. Authority control is a fully optional feature in DSpace 1.6. Implemented out of the box are the Library of Congress Names service, and the Sherpa Romeo authority plugin.

For an in-depth description of this feature, please consult: Authority Control of Metadata Values

Prop plugin.named.org.dspace.content.authority.ChoiceAuthority
erty:

Exam ple Value:	<pre>plugin.named.org.dspace.content.authority.ChoiceAuthority = \     org.dspace.content.authority.SampleAuthority = Sample, \     org.dspace.content.authority.LCNameAuthority = LCNameAuthority, \     org.dspace.content.authority.SHERPAROMEOPublisher = SRPublisher, \     org.dspace.content.authority.SHERPAROMEOJournalTitle = SRJournalTitle</pre>
Infor matio nal Note:	
Prop erty:	plugin.selfnamed.org.dspace.content.authority.ChoiceAuthority
Exam ple Value:	<pre>plugin.selfnamed.org.dspace.content.authority.ChoiceAuthority = \</pre>
Prop erty:	lcname.url
Exam ple	<pre>lcname.url = http://alcme.oclc.org/srw/search/lcnaf_</pre>
Value:	The Linked Data Service at the Library of Congress might be a better, and more stable, option: http://id.loc.gov/authorities/names.html
Infor matio nal Note:	Location (URL) of the Library of Congress Name Service
Prop erty:	sherpa.romeo.url / sherpa.romeo.apikey
Infor matio nal Note:	Please refers to the Sherpa/RoMEO Publishers Policy Database Integration section for details about such properties. See Configuring the Sherpa/RoMEO Publishers Policy Database Integration
Prop erty:	orcid.api.url
Exam ple Value:	<pre>orcid.api.url = https://pub.orcid.org/v2.1</pre>
Infor matio nal Note:	Location (URL) of the ORCID v2 Public API
Prop erty:	authority.minconfidence
Exam ple Value:	<pre>authority.minconfidence = ambiguous</pre>
Infor matio nal Note:	This sets the default lowest confidence level at which a metadata value is included in an authority-controlled browse (and search) index. It is a symbolic keyword, one of the following values (listed in descending order): accepted, uncertain, ambiguous, notfound, failed, rejected, novalue, unset. See org.dspace.content.authority.Choices source for descriptions.
Prop erty:	xmlui.lookup.select.size
Exam ple Value:	xmlui.lookup.select.size = 12
Infor matio nal Note:	This property sets the number of selectable choices in the Choices lookup popup

### **Configuring Multilingual Support**

[i18n - Locales]

#### Setting the Default Language for the Application

Prope rty:	default.locale
Exam ple Value:	default.locale = en
Infor matio nal Note:	The default language for the application is set with this property key. This is a locale according to i18n and might consist of country, country_language or country_language_variant. If no default locale is defined, then the server default locale will be used. The format of a local specifier is described here: http://java.sun.com/j2se/1.4.2/docs/api/java/util/Locale.html

#### **Supporting More Than One Language**

#### Changes in dspace.cfg

Property:	webui.supported.locales
Example Value:	webui.supported.locales = en, de
or perhaps	<pre>webui.supported.locales = en, en_ca, de</pre>
Informational Note:	All the locales that are supported by this instance of DSpace. Comma separated list.

The table above, if needed and is used will result in:

- · a language switch in the default header
- the user will be enabled to choose his/her preferred language, this will be part of his/her profile
- wording of emails
  - mails to registered users, e.g. alerting service will use the preferred language of the user
  - ° mails to unregistered users, e.g. suggest an item will use the language of the session
- · according to the language selected for the session, using dspace-admin Edit News will edit the news file of the language according to session

#### **Related Files**

If you set webui.supported.locales make sure that all the related additional files for each language are available. LOCALE should correspond to the locale set in *webui.supported.locales*, e. g.: for webui.supported.locales = en, de, fr, there should be:

- [dspace-source]/dspace/modules/jspui/src/main/resources/Messages.properties
- [dspace-source]/dspace/modules/jspui/src/main/resources/Messages\_en.properties
- [dspace-source]/dspace/modules/jspui/src/main/resources/Messages\_de.properties
- [dspace-source]/dspace/modules/jspui/src/main/resources/Messages\_fr.properties Files to be localized:
- [dspace-source]/dspace/modules/jspui/src/main/resources/Messages\_LOCALE.properties
- [dspace-source]/dspace/config/input-forms\_LOCALE.xml
- [dspace-source]/dspace/config/default\_LOCALE.license should be pure ASCII
- [dspace-source]/dspace/config/news-top\_LOCALE.html
- [dspace-source]/dspace/config/news-side\_LOCALE.html
- [dspace-source]/dspace/config/emails/change\_password\_LOCALE
- [dspace-source]/dspace/config/emails/feedback\_LOCALE
- [dspace-source]/dspace/config/emails/internal\_error\_LOCALE
- [dspace-source]/dspace/config/emails/register\_LOCALE
- [dspace-source]/dspace/config/emails/submit\_archive\_LOCALE
- [dspace-source]/dspace/config/emails/submit\_reject\_LOCALE
- [dspace-source]/dspace/config/emails/submit\_task\_LOCALE
- [dspace-source]/dspace/config/emails/subscription\_LOCALE
- [dspace-source]/dspace/config/emails/suggest\_LOCALE
- [dspace]/webapps/jspui/help/collection-admin\_LOCALE.html in html keep the jump link as original; must be copied to [dspace-source]/dspace/modules/jspui/src/main/webapp/help
- [dspace]/webapps/jspui/help/index\_LOCALE.html must be copied to [dspace-source]/dspace/modules/jspui/src /main/webapp/help
- [dspace]/webapps/jspui/help/site-admin\_LOCALE.html must be copied to [dspace-source]/dspace/modules/jspui /src/main/webapp/help

### **JSPUI Upload File Settings**

To alter these properties for the XMLUI, please consult the Cocoon specific configuration at /WEB-INF/cocoon/properties/core.properties.

Property:	upload.temp.dir
Example Value:	upload.temp.dir = \${dspace.dir}/upload
Informational Note:	This property sets where DSpace temporarily stores uploaded files.
Property:	upload.max
Example Value:	upload.max = 536870912
Informational Note:	Maximum size of uploaded files in bytes. A negative setting will result in no limit being set. The default is set for 512Mb.

### JSP Web Interface (JSPUI) Settings

The following section is limited to JSPUI. If the user wishes to use XMLUI settings, please refer to Chapter 7: XMLUI Configuration and Customization.

```
Ρ
    webui.itemdisplay.default
r
0
р
е
rt
y:
Е
     webui.itemdisplay.default = dc.title, dc.title.alternative, \
х
                  dc.contributor.*, dc.subject, dc.data.issued(date), \
а
                  dc.publisher, dc.identifier.citation, \setminus
m
pl
                  dc.relation.ispartofseries, dc.description.abstract, \
e
V
                  dc.description, dc.identifier.govdoc, \
                  dc.identifier.uri(link), dc.identifier.isbn, \
al
                  dc.identifier.issn, dc.identifier.ismn, dc.identifier
u
e:
   This is used to customize the DC metadata fields that display in the item display (the brief display) when pulling up a record. The format is: <schema
In
    >.<element>.<_optional_qualifier> . In place of the qualifier, one can use the wildcard "*" to include all fields of the same element, or,
fo
r
    leave it blank for unqualified elements. Additionally, two additional options are available for behavior/rendering: (date) and (link). See the following
m
   examples:
at
   dc.title = Dublin Core element "title" (unqualified)
io
   dc.title.alternative = DC element "title", qualifier "alternative"
n
al
   dc.title.* = All fields with Dublin Core element 'title' (any or no qualifier)
Ν
   dc.identifier.uri(link) = DC identifier.uri, rendered as a link
ot
    dc.date.issued(date) = DC date.issued, rendered as a date
e:
   The Messages.properties file controls how the fields defined above will display to the user. If the field is missing from the Messages.properties
   file, it will not be displayed. Look in Messages.properties under the metadata.dc.<field>. Example:
    metadata.dc.contributor.other = Authors
   metadata.dc.contributor.author = Authors
    metadata.dc.title.* = Title
    Please note: The order in which you place the values to the property key control the order in which they will display to the user on the outside
    world. (See the Example Value above).
Ρ
     webui.resolver.1.urn
r
     webui.resolver.1.baseurl
0
р
     webui.resolver.2.urn
     webui.resolver.2.baseurl
е
rt
y:
Е
     webui.resolver.1.urn = doi
х
     webui.resolver.1.baseurl = http://dx.doi.org/
а
     webui.resolver.2.urn = hdl
m
     webui.resolver.2.baseurl = http://hdl.handle.net/
pl
ė
V
al
u
e:
```

In fo r m at io n al N ot e:	When using "resolver" in <i>webui.itemdisplay</i> to render identifiers as resolvable links, the base URL is taken from <code>webui.resolver.<n>. baseurl<code> where <code>webui.resolver.<n>.baseurl<code> matches the urn specified in the metadata value. The value is appended to the "baseurl" as is, so the baseurl needs to end with the forward slash almost in any case. If no urn is specified in the value it will be displayed as simple text. For the doi and hdl urn defaults values are provided, respectively http://dc.doi.org and http://hdl.handle.net are used. If a metadata value with style "doi", "handle" or "resolver" matches a URL already, it is simply rendered as a link with no other manipulation.</code></n></code></code></n></code>
P r o p e rt y:	webui.preferred.identifier
E x m pl e V al u e:	webui.preferred.identifier = handle
In fo r m at io n al N ot e:	At the top of the item view a persistent identifier is shown to be used to refer to this item. If you use Item Level Versioning and DSpace is configured to, it shows a version history. Per default DSpace uses handle as preferred identifier. If you've configured DSpace to register DOIs you can decide to use DOIs instead of handles at the top of the item view and within the version history. Set the property webui.preferred.identifier = doi to do so.
P r o p e rt y:	webui.identifier.strip-prefixes
E x m pl e V al u e:	webui.identifier.strip-prefixes = true
In fo r m at io n al N ot e:	In the version history Persistent Identifiers can be shown with or without their prefixes, e.g. a handle can be shown as handle:10673/6 or just as 10673/6. A DOI can be can be shown as 10.5072/example-doi-123 or as doi:105072/example-doi-123. This property controlls whether the handles are stripped (default) or not.

P r o p e rt y:	plugin.single.org.dspace.app.webui.util.StyleSelection
E x m pl e V al u e:	<pre>plugin.single.org.dspace.app.webui.util.StyleSelection = \     org.dspace.app.web.util.CollectionStyleSelection     #org.dspace.app.web.util.MetadataStyleSelection</pre>
In fo r m at io n al N ot e:	Specify which strategy to use for select the style for an item.
P r o p e rt y:	webui.itemdisplay.thesis.collections
E x m pl e V al u e:	<pre>webui.itemdisplay.thesis.collections = 123456789/24, 123456789/35</pre>
In fo r m at io n al N ot e:	Specify which collections use which views by Handle.
P r o p e rt y:	webui.itemdisplay.label.restricted.bitstreams

E x m pl e V al u e:	webui.:	itemdisplay.label	restricted.	bitst	reams = tr	ue				
In fo r mat io n al N ot e:	If set to all, all use rs will get a war nin g if acc ess rest ricti ons are in pla ce for an bitstre "all" shown as	Cancel      C	Collection Grindelohe und Klau collection Grindelohe und Klau Autzucht knallnümpfiger Ki Hagrid, Rubeus 1883 Description	nmervlecher. öter Size 3 MB DS ched st as sucl e policy	Q       Log         In order to accept the task         Format         Adobe PDF         Space Software Copyright Space S	ged in as p.becker@u-berl of checking this item, please of view/Open Accept This Taak 2002-2013 Duraspace - Feec bonymous users all bitstreams wi access for anor	etback	Alton Orean (1999)     Alton (1999)	Dear Digital     Sector Digital     control of digital control     angles, mpegis and data sets      control of digital control     control     control of digital control     contro     control     control     contro     control     control     c	
P r o p e rt y:	webui webui	.itemdisplay.meta .itemdisplay.meta	adata-style adata-style							
E x a pl e V al u e:	webui webui	.itemdisplay.meta .itemdisplay.meta	adata-style = adata-style =	= sche = dc.t	ema.element ype	[.qualifier	.*]			
In fo r m at io n al N ot e:	Specify v	vhich metadata to use	as name of the	style						

P r p e rt y:	webui.itemlist.columns
E x a m pl e V al u e:	<pre>webui.itemlist.columns = thumbnail, dc.date.issued(date), dc.title, \</pre>
In fo r m at io n al N ot e:	Customize the DC fields to use in the item listing page. Elements will be displayed left to right in the order they are specified here. The form is <schema prefix="">.<element>[.<qualifier>   .*][(date)], Although not a requirement, it would make sense to include among the listed fields at least the date and title fields as specified by the webui . browse.index configuration options in the next section mentioned. (cf.) If you have enabled thumbnails (webui.browse.thumbnail.show), you must also include a 'thumbnail' entry in your columns, this is where the thumbnail will be displayed.</qualifier></element></schema>
P r o p e rt y:	webui.itemlist.width
E x a m pl e V al u e:	webui.itemlist.width = *, 130, 60%, 40%
In fo r m at io n al N ot e:	You can customize the width of each column with the following lineyou can have numbers (pixels) or percentages. For the 'thumbnail' column, a setting of '*' will use the max width specified for browse thumbnails (cf. webui.browse.thumbnail.maxwidth, thumbnail.maxwidth)
P r o p e rt y:	<pre>webui.itemlist.browse.<index name="">.sort.<sort name="">.columns webui.itemlist.sort.<sort name="">.columns webui.itemlist.browse.<browse name="">.columns webui.itemlist.<sort index="" name="" or="">.columns</sort></browse></sort></sort></index></pre>

E x m pl e V al u e:	
In fo r at io n al N ot e:	You can override the DC fields used on the listing page for a given browse index and/or sort option. As a sort option or index may be defined on a field that isn't normally included in the list, this allows you to display the fields that have been indexed/sorted on. There are a number of forms the configuration can take, and the order in which they are listed below is the priority in which they will be used (so a combination of an index name and sort name will take precedence over just the browse name). In the last case, a sort option name will always take precedence over a browse index name. Note also, that for any additional columns you list, you will need to ensure there is an <i>itemlist.<field name=""></field></i> entry in the messages file.
P r o p e rt y:	webui.itemlist.dateaccessioned.columns
E x a m pl e V al u e:	webui.itemlist.dateaccessioned.columns = thumbnail, dc.date.accessioned(date), dc.title, dc.contributor.*
In fo r m at io n al N ot e:	This would display the date of the accession in place of the issue date whenever the dateaccessioned browsed index or sort option is selected. Just like webui.itemlist.columns, you will need to include a 'thumbnail' entry to display the thumbnails in the item list.
P r o p e rt y:	webui.itemlist.dateaccessioned.widths
E x m pl e V al u e:	<pre>webui.itemlist.dateaccessioned.widths = *, 130, 60%, 40%</pre>

In fo r m at io n al N ot e:	As in the aforementioned property key, you can customize the width of the columns for each configured column list, substituting ".widths" for ". columns" in the property name. See the setting for webui.itemlist.widths for more information.
P r o p e rt y:	webui.itemlist.tablewidth
E x a m pl e V al u e:	webui.itemlist.tablewidth = 100%
In fo r m at io n al N ot e:	You can also set the overall size of the item list table with the following setting. It can lead to faster table rendering when used with the column widths above, but not generally recommended.
P r o p e rt y:	webui.session.invalidate
E x m pl e V al u e:	webui.session.invalidate = true
In fo r m at io n al N ot e:	Enable or disable session invalidation upon login or logout. This feature is enabled by default to help prevent session hijacking but may cause problems for shibboleth, etc. If omitted, the default value is " <i>true</i> ". [Only used for JSPUI authentication].

P r o p e rt y:	jspui.google.analytics.key
E x m pl e V al u e:	jspui.google.analytics.key = UA-XXXXXX-X
In fo r at io n al N ot e:	If you would like to use Google Analytics to track general website statistics then use the following parameter to provide your Analytics key.

### **JSPUI Item Mapper**

Because the item mapper requires a primitive implementation of the browse system to be present, we simply need to tell that system which of our indexes defines the author browse (or equivalent) so that the mapper can list authors' items for mapping

Define the index name (from *webui.browse.index*) to use for displaying items by author.

Property:	itemmap.author.index
Example Value:	<pre>itemmap.author.index = author</pre>
Informational Note:	If you change the name of your author browse field, you will also need to update this property key.

### **Display of Group Membership**

Property:	webui.mydspace.showgroupmembership
Example Value:	<pre>webui.mydspace.showgroupmembership = false</pre>
Informational Note:	To display group membership set to "true". If omitted, the default behavior is false.

### JSPUI / XMLUI SFX Server

SFX Server is an OpenURL Resolver.

Property:	sfx.server.url
Example Value:	<pre>sfx.server.url = http://sfx.myu.edu:8888/sfx?</pre>
	<pre>sfx.server.url = http://worldcatlibraries.org/registry/gateway?</pre>
Informational Note:	SFX query is appended to this URL. If this property is commented out or omitted, SFX support is switched off.

All the parameters mapping are defined in [dspace]/config/sfx.xml file. The program will check the parameters in sfx.xml and retrieve the correct metadata of the item. It will then parse the string to your resolver.

For the following example, the program will search the first query-pair which is DOI of the item. If there is a DOI for that item, your retrieval results will be, for example:

http://researchspace.auckland.ac.nz/handle/2292/5763

Example. For setting DOI in sfx.xml

```
<query-pairs>
<field>
<querystring>rft_id=info:doi/</querystring>
<dc-schema>dc</dc-schema>
<dc-element>identifier</dc-element>
<dc-qualifier>doi</dc-qualifier>
</field>
</query-pairs>
```

If there is no DOI for that item, it will search next query-pair based on the [dspace]/config/sfx.xml and then so on.

#### Example of using ISSN, volume, issue for item without DOI

[http://researchspace.auckland.ac.nz/handle/2292/4947]

```
For parameter passing to the <querystring>
```

<querystring>rft\_id=info:doi/</querystring>

#### Please refer to these:

[http://ocoins.info/cobgbook.html]
[http://ocoins.info/cobg.html]

Program assume won't get empty string for the item, as there will at least author, title for the item to pass to the resolver.

For contributor author, program maintains original DSpace SFX function of extracting author's first and last name.

```
<field>

<querystring>rft.aulast=</querystring>

<dc-schema>dc</dc-schema>

<dc-element>contributor</dc-element>

<dc-qualifier>author</dc-qualifier>

</field>

<field>

<querystring>rft.aufirst=</querystring>

<dc-schema>dc</dc-schema>

<dc-element>contributor</dc-element>

<dc-qualifier>author</dc-qualifier>

</field>
```

### **JSPUI Item Recommendation Setting**

Property:	webui.suggest.enable
Example Value:	webui.suggest.enable = true
Informational Note:	Show a link to the item recommendation page from item display page.
Property:	webui.suggest.loggedinusers.only
Example Value: webui.sug	<pre>webui.suggest.loggedinusers.only = true</pre>
Informational Note:	Enable only if the user is logged in. If this key commented out, the default value is false.

### **Controlled Vocabulary Settings**

DSpace now supports controlled vocabularies to confine the set of keywords that users can use while describing items.

Property:	webui.controlledvocabulary.enable
Example Value:	<pre>webui.controlledvocabulary.enable = true</pre>
Informational Note:	Enable or disable the controlled vocabulary add-on. WARNING: This feature is not compatible with WAI (it requires JavaScript to function).

The need for a limited set of keywords is important since it eliminates the ambiguity of a free description system, consequently simplifying the task of finding specific items of information.

The controlled vocabulary add-on allows the user to choose from a defined set of keywords organized in an tree (taxonomy) and then use these keywords to describe items while they are being submitted.

We have also developed a small search engine that displays the classification tree (or taxonomy) allowing the user to select the branches that best describe the information that he/she seeks.

The taxonomies are described in XML following this (very simple) structure:

You are free to use any application you want to create your controlled vocabularies. A simple text editor should be enough for small projects. Bigger projects will require more complex tools. You may use Protegé to create your taxonomies, save them as OWL and then use a XML Stylesheet (XSLT) to transform your documents to the appropriate format. Future enhancements to this add-on should make it compatible with standard schemas such as OWL or RDF.

In order to make DSpace compatible with WAI 2.0, the add-on is **turned off** by default (the add-on relies strongly on JavaScript to function). It can be activated by setting the following property in dspace.cfg:

```
webui.controlledvocabulary.enable = true
```

New vocabularies should be placed in [dspace]/config/controlled-vocabularies/ and must be according to the structure described. A validation XML Schema (named controlledvocabulary.xsd) is also available in that directory.

Vocabularies need to be associated with the correspondent DC metadata fields. Edit the file [dspace]/config/input-forms.xml and place a "vocabu lary" tag under the "field" element that you want to control. Set value of the "vocabulary" element to the name of the file that contains the vocabulary, leaving out the extension (the add-on will only load files with extension "\*.xml"). For example:

```
<field>
        <dc-schema>dc</dc-schema>
        <dc-element>subject</dc-element>
        <dc-qualifier></dc-qualifier>
        <!-- An input-type of twobox MUST be marked as repeatable --->
        <repeatable>true</repeatable>
        <label>Subject Keywords</label>
        <input-type>twobox</input-type>
        <hint> Enter appropriate subject keywords or phrases below. </hint>
        <required></required>
        <vocabulary [closed="false"]>nsi</vocabulary>
        </field>
```

The vocabulary element has an optional boolean attribute **closed** that can be used to force input only with the JavaScript of controlled-vocabulary add-on. The default behavior (i.e. without this attribute) is as set **closed="false"**. This allow the user also to enter the value in free way.

The following vocabularies are currently available by default:

- nsi nsi.xml The Norwegian Science Index
- srsc srsc.xml Swedish Research Subject Categories

3. JSPUI Session Invalidation

Property:	webui.session.invalidate
Example Value:	webui.session.invalidate = true
Information al Note:	Enable or disable session invalidation upon login or logout. This feature is enabled by default to help prevent session hijacking but may cause problems for shibboleth, etc. If omitted, the default value is 'true'.

### **XMLUI Specific Configuration**

The DSpace digital repository supports two user interfaces: one based upon JSP technologies and the other based upon the Apache Cocoon framework. This section describes those configurations settings which are specific to the XMLUI interface based upon the Cocoon framework. (*Prior to DSpace Release 1.5.1 XMLUI was referred to Manakin. You may still see references to "Manakin"*)

Pro per ty:	xmlui.force.ssl
Ex am ple Val ue:	xmlui.force.ssl = true
Inf or ma tion al Not e:	Force all authenticated connections to use SSL, only non-authenticated connections are allowed over plain http. If set to true, then you need to ensure that the " <i>dspace.hostname</i> " parameter is set correctly.
Pro per ty:	xmlui.user.registration
Ex am ple Val ue:	<pre>xmlui.user.registration = true</pre>
Inf or ma tion al Not e:	Determine if new users should be allowed to register. This parameter is useful in conjunction with Shibboleth where you want to disallow registration because Shibboleth will automatically register the user. Default value is true.
Pro	xmlui.user.editmetadata
ty:	
Ex am ple Val ue:	xmlui.user.editmetadata = true
Ex am ple Val ue: Inf or ma tion al Not e:	xmlui.user.editmetadata = true         Determines if users should be able to edit their own metadata. This parameter is useful in conjunction with Shibboleth where you want to disable the user's ability to edit their metadata because it came from Shibboleth. Default value is true.
Ex am ple Val ue: Inf or ma tion al Not e: Pro per ty:	xmlui.user.editmetadata = true         Determines if users should be able to edit their own metadata. This parameter is useful in conjunction with Shibboleth where you want to disable the user's ability to edit their metadata because it came from Shibboleth. Default value is true.         xmlui.session.ipcheck
ty: Ex am ple Val ue: Inf or ma tion al Not e: Pro per ty: Ex am ple Val ue:	xmlui.user.editmetadata = true         Determines if users should be able to edit their own metadata. This parameter is useful in conjunction with Shibboleth where you want to disable the user's ability to edit their metadata because it came from Shibboleth. Default value is true.         xmlui.session.ipcheck         xmlui.session.ipcheck = true

Pro per ty:	xmlui.user.loginredirect
Ex am ple Val ue:	<pre>xmlui.user.loginredirect = /profile</pre>
Inf or ma tion al Not e:	After a user has logged into the system, which url should they be directed? Leave this parameter blank or undefined to direct users to the homepage, or <i>/profile</i> for the user's profile, or another reasonable choice is <i>/submissions</i> to see if the user has any tasks awaiting their attention. The default is the repository home page.
Pro per ty:	xmlui.theme.allowoverrides
Ex am ple Val ue:	<pre>xmlui.theme.allowoverrides = false</pre>
Inf or ma tion al Not e:	Allow the user to override which theme is used to display a particular page. When submitting a request add the HTTP parameter "themepath" which corresponds to a particular theme, that specified theme will be used instead of the any other configured theme. Note that this is a potential security hole allowing execution of unintended code on the server, this option is only for development and debugging it should be turned off for any production repository. The default value unless otherwise specified is "false".
Pro per ty:	xmlui.theme.enableConcatenation
Ex am ple Val ue:	xmlui.theme.enableConcatenation = false
Inf or ma tion al Not e:	Enabling this property will concatenate CSS, JS and JSON files where possible. CSS files can be concatenated if multiple CSS files with the same media attribute are used in the same page. Links to the CSS files are automatically referring to the concatenated resulting CSS file. The theme sitemap should be updated to use the ConcatenationReader for all js, css and json files before enabling this property.
Pro per ty:	xmlui.theme.enableMinification
Ex am ple Val ue:	xmlui.theme.enableMinification = false
Inf or ma tion al Not e:	Enabling this property will minify CSS, JS and JSON files where possible. The theme sitemap should be updated to use the ConcatenationReader for all js, css and json files before enabling this property.
Pro per ty:	xmlui.theme.mirage.item-list.emphasis

Ex am ple Val ue:	xmlui.theme.mirage.item-list.emphasis = file
Inf or ma tion al Not e:	When set to "file" the item listings in your repository will include the generated thumbnails of uploaded files. Alternatively, you can set this parameter to metadata to put more emphasis on the metadata and effectively hide the thumbnails. The default value is "metadata".
Pro per ty:	mirage2.item-view.bitstream.href.label.1 mirage2.item-view.bitstream.href.label.2
Ex am ple Val ue:	mirage2.item-view.bitstream.href.label.1 = label mirage2.item-view.bitstream.href.label.2 = title
Inf	Mirage 2 theme ONLY
ma tion al Not e:	Determines if the bitstream filename (title) or description (label) is being used as the display label on the hyperlinks to download the actual files. By default, the file description (label) will be shown. If this value is empty, the filename (title) will be used as a fallback. More information and screenshots.
Pro per ty:	xmlui.bundle.upload
Ex am ple Val ue:	xmlui.bundle.upload = ORIGINAL, METADATA, THUMBNAIL, LICENSE, CC_LICENSE
Inf or ma tion al Not e:	Determine which bundles administrators and collection administrators may upload into an existing item through the administrative interface. If the user does not have the appropriate privileges (add and write) on the bundle then that bundle will not be shown to the user as an option.
Pro per ty:	xmlui.community-list.render.full
Ex am ple Val ue:	xmlui.community-list.render.full = true
Inf or ma tion al Not e:	On the community-list page should all the metadata about a community/collection be available to the theme. This parameter defaults to true, but if you are experiencing performance problems on the community-list page you should experiment with turning this option off.
Pro per ty:	xmlui.community-list.cache
Ex am ple Val ue:	xmlui.community-list.cache = 12 hours

Inf or ma tion al Not e:	Normally, the XMLUI will fully verify any cache pages before using a cache copy. This means that when the community-list page is viewed the database is queried for each community/collection to see if their metadata has been modified. This can be expensive for repositories with a large community tree. To help solve this problem you can set the cache to be assumed valued for a specific set of time. The downside of this is that new or editing communities/collections may not show up the website for a period of time.
Pro per ty:	xmlui.bitstream.mods
Ex am ple Val ue:	xmlui.bitstream.mods = true
Inf or ma tion al Not e:	Optionally, you may configure XMLUI to take advantage of metadata stored as a bitstream. The MODS metadata file must be inside the "METADATA" bundle and named MODS.xml. If this option is set to 'true' and the bitstream is present then it is made available to the theme for display.
Pro per ty:	xmlui.bitstream.mets
Ex am ple Val ue:	xmlui.bitstream.mets = true
Inf or ma tion al Not e:	Optionally, you may configure Manakin to take advantage of metadata stored as a bitstream. The METS metadata file must be inside the "METADATA" bundle and named METS.xml. If this option is set to "true" and the bitstream is present then it is made available to the theme for display.
Pro per ty:	xmlui.google.analytics.key
Ex am ple Val ue:	xmlui.google.analytics.key = UA-XXXXXX-X
Inf or ma tion al Not e:	If you would like to use Google Analytics to track general website statistics then use the following parameter to provide your analytics key. First sign up for an account at <a href="http://analytics.google.com">http://analytics.google.com</a> , then create an entry for your repositories website. Google Analytics will give you a snippet of javascript code to place on your site, inside that snip it is your Google Analytics key usually found in the line: _uacct = "UA-XXXXXX-X" Take this key (just the UA-XXXXXX-X part) and place it here in this parameter.
Pro per ty:	xmlui.controlpanel.activity.max
Ex am ple Val ue:	xmlui.controlpanel.activity.max = 250
Inf or ma tion al Not e:	Assign how many page views will be recorded and displayed in the control panel's activity viewer. The activity tab allows an administrator to debug problems in a running DSpace by understanding who and how their dspace is currently being used. The default value is 250.

Pro per ty:	xmlui.controlpanel.activity.ipheader
Ex am ple Val ue:	xmlui.controlpanel.activity.ipheader = X-Forward-For
Inf or ma tion al Not e:	Determine where the control panel's activity viewer receives an events IP address from. If your DSpace is in a load balanced environment or otherwise behind a context-switch then you will need to set the parameter to the HTTP parameter that records the original IP address.
Pro per ty:	xmlui.search.metadata_export
Ex am ple Val ue:	xmlui.search.metadata_export = admin
Inf or ma tion al Not e:	Determine the access rights necessary to export DSpace metadata from search results in a CSV format (compatible with Batch Metadata Editing tool). By default, only Administrators can export metadata from search results. Other options include: <ul> <li>admin = Administrative users only</li> <li>user = Any logged in user</li> <li>anonymous = Anyone in the world</li> </ul>

### Optional or Advanced Configuration Settings

The following section explains how to configure either optional features or advanced features that are not necessary to make DSpace "out-of-the-box"

### The Metadata Format and Bitstream Format Registries

The [dspace]/config/registries directory contains three XML files. These are used to load the *initial* contents of the Dublin Core Metadata registry and Bitstream Format registry and SWORD metadata registry. After the initial loading (performed by *ant fresh\_install* above), the registries reside in the database; the XML files are not updated.

In order to change the registries, you may adjust the XML files before the first installation of DSpace. On an already running instance it is recommended to change bitstream registries via DSpace admin UI, but the metadata registries can be loaded again at any time from the XML files without difficult. The changes made via admin UI are not reflected in the XML files.

#### **Metadata Format Registries**

The default metadata schema is Dublin Core, so DSpace is distributed with a default Dublin Core Metadata Registry. Currently, the system requires that every item have a Dublin Core record.

There is a set of Dublin Core Elements, which is used by the system and should not be removed or moved to another schema, see Appendix: Default Dublin Core Metadata registry.

Note: altering a Metadata Registry has no effect on corresponding parts, e.g. item submission interface, item display, item import and vice versa. Every metadata element used in submission interface or item import must be registered before using it.

Note also that deleting a metadata element will delete all its corresponding values.

If you wish to add more metadata elements, you can do this in one of two ways. Via the DSpace admin UI you may define new metadata elements in the different available schemas. But you may also modify the XML file (or provide an additional one), and re-import the data as follows:

[dspace]/bin/dspace dsrun org.dspace.administer.MetadataImporter -f [xml file]

The XML file should be structured as follows:

```
<dspace-dc-types>
        <dc-type>
            <schema>dc</schema>
            <element>contributor</element>
            <qualifier>advisor</qualifier>
            <scope_note>Use primarily for thesis advisor.</scope_note>
        </dc-type>
</dspace-dc-type>
```

#### **Bitstream Format Registry**

The bitstream formats recognized by the system and levels of support are similarly stored in the bitstream format registry. This can also be edited at installtime via [dspace]/config/registries/bitstream-formats.xml or by the administration Web UI. The contents of the bitstream format registry are entirely up to you, though the system requires that the following two formats are present:

- Unknown
- License
  - Deleting a format will cause any existing bitstreams of this format to be reverted to the unknown bitstream format.

### **Configuring Usage Instrumentation Plugins**

A usage instrumentation plugin is configured as a Spring bean in the applicationContext.xml for each of the various user interface web applications. It will require the injection of an instance of EventService, which it will use to register itself on the UsageEvent bus. See the configuration file for examples.

More than one such plugin may be configured - each will receive all usage events.

If you wish to write your own, it must extend the abstract class org.dspace.usage.AbstractUsageEventListener.

#### The Passive Plugin

The Passive plugin is provided as the class org.dspace.usage.PassiveUsageEventListener. It absorbs events without effect, and serves as a simple example of how to write a UsageEvent listener.

#### The Tab File Logger Plugin

The Tab File Logger plugin is provided as the class org.dspace.usage.TabFileUsageEventListener. It writes event records to a file in tab-separated column format. If left unconfigured, it will write to [DSpace]/log/usage-events.tsv. To specify the file path, provide an absolute path, or a path relative to log. dir, as the value for usageEvent.tabFileLogger.file in dspace.cfg.

#### Behavior of the workflow system

DSpace contains workflow systems to review submissions as described in detail as part of the architecture of the business logic layer. There is the original workflow systems and a configurable one. The file [dspace]/config/modules/workflow.cfg contains properties to configure details of the workflow systems.

The property workflow.reviewer.file-edit controls whether files may be added/edited/removed during review (set to true) or whether files can be downloaded during review only.

#### [dspace]/config/modules/workflow.cfg

```
#Allow the reviewers to add/edit/remove files from the submission
#When changing this property you might want to alert submitters in the license that reviewers can alter their
files
workflow.reviewer.file-edit=false
```

Both workflow systems send notifications on new Items waiting to be reviewed to all EPersons that may resolve those. Tasks can be taken to avoid that two EPersons work on the same task at the same time without knowing from each other. When a EPerson returns a task to the pool without resolving it (by accepting or rejecting the submission), another E-Mail is sent. In case you only want to be notified of completely new tasks entering a step of the workflow system, you may switch off notifications on tasks returned to the pool by setting workflow.notify.returend.tasks to false in config/modules/workflow.cfg as shown below:

#### [dspace]/config/modules/workflow.cfg

# Notify reviewers about tasks returned to the pool workflow.notify.returned.tasks = false By default notifications are sent for tasks returned to the pool. This configuration works for the original workflow system as well as for the configurable xml workflow system.

### JSPUI: Per item visual indicators for browse and search results

Visual indicators per item allow users to mark items in browse and search results. This could be useful in many scenarios, some of them follow:

- 1. If your repository contains items of different type (articles, book chapters, pictures) you can mark the type of each item using an icon.
- 2. If your repository has items with bitstreams but also has items with no bitstream, you could indicate this fact to the users using the visual indicators
- 3. If you have applied copyright licences in the bitstreams or items, you could notify users about that in the browse or result list
- 4. If you want your users to spot some items out of the list easily or if you want to differentiate some items from the others you could use the visual indicators

The visual indicators extension has the following specs:

- 1. Multiple marks can be added per item (i.e. mark the type of the item and the availability of the bitstreams)
- 2. Easy configuration of the strategy of what mark to display in every item
- 3. Marks based on images or a generic class (i.e. a glyphicon icon for bootstrap)
- 4. Display tooltip when hovering the mark + localization of the tooltip
- 5. Easy addtion of new strategies for any type of mark the user desires
- 6. Add css styles for the user to configure the position of the marks in the list row

#### Some theory:

A mark is an instance of the class: org.dspace.app.itemmarking.ltemMarkingInfo.

Each mark can have the following properties:

- *imageName*: a path to the image that will be displayed for the specific mark
- classInfo: the css class to be applied in the mark (useful if you do not want to add an image but just an icon from the bootstrap glyph icons)
- link: the link to be applied in the mark (optional)
- tooltip: the tooltip to be shown when hovering over the mark (optional)

When you need to add a mark in an Item then you need to create a strategy that determined what mark to display per item. Strategy classes need to implement the interface:

org.dspace.app.itemmarking.ItemMarkingExtractor

Your strategy class just needs to implement the following method from the above Interface:

public ItemMarkingInfo getItemMarkingInfo(Context context, Item item) throws SQLException;

Which is, given an item, return the Mark info to display.

Currently, there are three Strategies included by default:

#### ItemMarkingMetadataStrategy

This strategy decides the mark to display per item based on a value of a metadata field (i.e. dc:type)

It accepts two properties:

- metadataField: the metadata field to be used for searching the value in the form "schema.element.gualifier"
- mapping: a Java Map of Strings to ItemMarkingInfos

If the String (key of the map) is found as a value in the metadataField field, then the mark denoted by the value of the map will be displayed.

#### ItemMarking Collection Strategy

This strategy decides the mark to display per item based on the collection this item belongs to.

It accepts one property:

• mapping: a Java Map of Strings to ItemMarkingInfos

The String (key of the map) is the collection handle (i.e.: 123456789/1) and if an items belongs to this collection, the mark denoted by the object of the map will be displayed

#### It emMarking AvailabilityBit Str eamStrategy

This strategy decides the mark to display per item based on the availability (exists or not) of a bitstream within the item.

It accepts to properties:

- nonAvailableImageName: the image to display for the mark if no bitstreams exist for the item
- ° nonAvailableImageName: the image to display for the mark if at least one bistream exist for the item

Moreover, this strategy add a link in the mark (in case there are bitstreams in the item) to the first bitstream of the item

#### How to:

In order to enable a mark for the result or browse list you need to change the option:

webui.itemlist.columns

#### of the dspace.cfg file.

You need to include a 'mark\_[value]' key in any column order you like. Do not add the brackets and you can replace the "value" with any word has a meaning for your marking type. You may add multiple marks (i.e.: one in the first column and one at the last)

For example, the following line is a valid option value:

```
webui.itemlist.columns = mark_type, dc.date.issued(date), dc.title, dc.contributor.*, mark_availability
```

In the aforementioned case, you just added two marks, one in the first column for the type of the item and one in the last item for the availability.

Now it's time to declare what "mark\_type" and "mark\_availability" means. This is done in the Spring configuration file config/sping/api/item-marking. xml, via the dependency injection feature.

In this file, for each "mark\_[value]" key you add in the *dspace.cfg* file, you need to add a Spring bean with id=org.dspace.app.itemmarking. ItemMarkingExtractor.[value]. The class of this bean must be an implementation of org.dspace.app.itemmarking.ItemMarkingExtractor.

That's all!

```
For our example, we need to declare two beans (one for "mark_type" and one for "mark_availability").
```

For the "mark\_type", we have declared the strategy to be ItemMarkingMetadataStrategy which means that the value of a metadata field (dc.type in our case) will determine the mark of each item. Here is the mapping:

```
<bean class="java.util.HashMap" id="typeMap">
       <constructor-arg>
             <map>
                       <entry>
                    <key>
                                             <value>image</value>
                   </kev>
                    <ref bean="typelMarkingInfo"/>
                </entry>
                <entry>
                    <key>
                                            <value>video</value>
                   </key>
                    <ref bean="type2MarkingInfo"/>
                 </entry>
              </map>
       </constructor-arg>
</bean>
```

Thus, if the value of **dc.type** field is equal to image the "**type1MarkingInfo**" bean will be used for the marking, if it is equal to video the "**type2MarkingInfo**" bean will be used, otherwise, no mark will be displayed.

#### Tooltip property contains the localized key to display.

Keep in mind that the Strategy that you may write can have its own logic on how to create the **ItemMarkingInfo** per item. The only requirement of the feature is to add in the Spring configuration file the initial beans one for each mark you have declared in the dspace.cfg file.

#### Styling:

The title for the column of each mark is titled based on the localized key "itemlist.mark\_[value]", so you just need to add the specific keys in the messages.propertied files.

Moreover, the following CSS styles are applied to the various aspects of the mark:

- mark\_[value]\_th: a style applied to the column header
- mark\_[value]\_tr: a style applied to the each row

Add these classes to the css file and apply any style you like (like centering the text or the image)

### Recognizing Web Spiders (Bots, Crawlers, etc.)

DSpace can often recognize that a given access request comes from a web spider that is indexing your repository. These accesses can be flagged for separate treatment (perhaps exclusion) in usage statistics. This requires patterns to match against incoming requests. These patterns exist in files that you will find in config/spiders.

In the spiders directory itself, you will find a number of files provided by iplists.com. These files contain network address patterns which have been discovered to identify a number of known indexing services and other spiders. You can add your own files here if you wish to exclude more addresses that you know of. You will need to include your files' names in the list configured in config/modules/solr-statistics.cfg. The iplists.com-\*.txt files can be updated using a tool provided by DSpace. See SOLR Statistics for details.

In the spiders directory you will also find two subdirectories. agents contains files filled with regular expressions, one per line. An incoming request's Us er-Agent header is tested with each expression found in any of these files until an expression matches. If there is a match, the request is marked as being from a spider, otherwise not. domains similarly contains files filled with regular expressions which are used to test the domain name from which the request comes. You may add your own files of regular expressions to either directory if you wish to test requests with patterns of your own devising.

You can resolve a configuration property name to its value using the command dspace dsprop -p some.property.name. The output is undecorated and may be suitable for use in scripts.

The dsprop command has these options:

name	argument	meaning
 property	name	the name of the desired configuration property. This option is required.
-р		
 module	name	the name of the module in which the property is found. If omitted, the value ofproperty is the entire name. If used, the name will be composed as module.property. For example, "-m dspace -p url" will look up the value of dspace.url.
-m		
raw		if used, this prevents the substitution of other property values into the value of the requested property.
-r		It is also useful to see all of the propery values when a specific property has an <b>array of values</b> (i.e. the configuration supports specifying multiple values). Otherwise, by default, dsprop may only return the first value in the array.
help		Display help similar to this table.
-h		
-?		