

# Islandora BagIt

## Overview

[BagIt](#) is a specification for packaging content and metadata about that content into a format that can be shared between applications. This module provides a "Create Bag" option that allows the packaging of the datastreams in [Islandora](#) objects. This module is a fork of [BagIt](#).

## Dependencies

This module requires the following modules/libraries:

- [Islandora](#)
- [Tuque](#)
- [Scholars' Lab BagItPHP library](#)
- [Archive\\_Tar](#)
- [Libraries](#)

## Downloads

[Release Notes and Downloads](#)

## Installation

To install the Islandora BagIt module:

1. Install [Archive\\_Tar](#). This package is required by PEAR so if you have PEAR installed on your system, you won't need to install Archive\_Tar separately.
2. Install the [Libraries API](#) contrib module.
3. Unzip this module into your site's modules directory as you would any other contrib module.
4. Install the BagItPHP library by entering your site's sites/all/libraries directory and issuing the following command:

```
git clone git://github.com/scholarslab/BagItPHP.git
```

5. Enable the Libraries and Islandora BagIt modules like you would any other contrib modules.

## Configuration

Set the location for the BagIt library, temporary directory for unserialized Bags, output directory for serialized Bags, Bag name prefix, select Collection batch type, compression type, object plugins, collection plugins, and set Bag Metadata in Administration » Islandora » Islandora BagIt (admin/islandora/bagit).

#### Location of the BagIt library \*

Directory where the Scholars' Lab BagIt for PHP library is installed, relative to sites/all/libraries. Do not use a leading or trailing slash.

#### Temporary directory for unserialized Bags \*

Filesystem directory where the unserialized Bag directories are written, named by PID. Needs to exist and to be writable by the web server. Do not include the trailing slash.

#### Delete unserialized (zipped) Bags.

Check this option if you want to automatically delete unserialized Bags.

#### Output directory for serialized Bags \*

Filesystem directory where serialized (.tgz or .zip) Bags are written, named by PID. Needs to exist and to be writable by the web server. Do not include the trailing slash. If you want users to be able to download the Bags, this directory needs to be below your site's file system directory.

#### Create Bag on object ingest

Check this option if you want to create a Bag for an object when it is ingested.

#### Create Bag on object modification

Check this option if you want to create a Bag for an object when it or any of its datastreams are modified.

#### Provide link to download the Bag

This link will work only if 'Output directory for serialized Bags' is accessible via the web.

#### Collection batch type

Choose whether collection-level batches create one Bag per object or one Bag per collection.

#### Serialize collection Bags.

Check this option if you want to serialize (zip) one-Bag-per-collection Bags.

#### Bag name \*

Base name for the Bags. The object's PID is appended to this value.

#### Display messages

Check this option if you want to display messages associated with Bag creation to the end user.

#### Log the creation of Bags

Check this option if you want to log the creation of Bags to the Drupal watchdog.

#### Compression type

The compression used on serialized Bags.

#### Object plugins

 plugin\_object\_archivematica\_transfers plugin\_object\_ds\_add\_file plugin\_object\_ds\_basic

## Customization

Islandora BagIt uses two different types of plugins, object plugins and collection plugins.

Object plugins add files to an Islandora object's Bag. Object plugins 1) define the source path for datastream files and their destination paths in the Bag relative to the Bag's 'data' directory, and 2) optionally, rename datastream files or create new files for inclusion in the Bag.

The module comes with five object plugins: one that copies all the datastreams in an Islandora object to the top level of the Bag's 'data' directory, one that illustrates how to create an arbitrary file to add to the Bag, one that includes the FOXML for an Islandora object, one that creates an Archivematica (<http://archivematica.org>) 'transfer' Bag, and one that includes a PREMIS preservation metadata file generated by the Islandora PREMIS module ([https://github.com/ruebot/islandora\\_premis](https://github.com/ruebot/islandora_premis)).

Multiple object plugins may be activated, but they all add files to the same Bag. This means you can write a plugin that creates one specific file (for example) and activate it or deactivate it as needed. Plugins are fired in the order in which their filenames sort.

If you have requirements not covered by the supplied object plugins, you can use the plugins described above to base your own on. If you write your own plugins, follow these guidelines:

1. Begin plugin filenames with 'plugin\_object\_' and end in '.inc'.
2. Every plugin has a function that is named the same as the filename prepended with 'islandora\_bagit\_', ending in '\_init()'. All init functions take \$islandora\_object and \$tmp\_ds\_directory parameters.
3. Plugins must complete all file writing and copying tasks before they return the file's source and destination paths to the BagIt module.
4. Plugins return FALSE if there is an error in copying or writing files.

Collection plugins only apply to Bags that contain all the objects in a collection. Whereas object plugins determine what goes in each object-level Bag, collection plugins determine how all the objects that are in a collection-level Bag are arranged in the Bag's 'data' directory. Also, you can only activate one collection plugin at a time, unlike object plugins.

The requirements for collection plugins are the same as those for object plugins except for the requirement a) above: collection plugin filenames being with 'plugin\_collection\_' instead of 'plugin\_object\_'.

The module comes with two collection plugins, one that creates a subdirectory for each object in the Bag's 'data' directory, and one that creates an 'odd' and 'even' subdirectory in the Bag's 'data' directory, and then organizes object-level Bags within those two subdirectories. The odd/even plugin is intended to illustrate alternative ways to organize objects within a collection Bag.

## Modifying a Bag from your own modules

This module provides a `drupal_alter()` hook, which allows other modules to use `hook_islandora_bagit_alter($bag, $islandora_object)`. Your module can modify the current Bag using any of the methods provided by the BagItPHP library. Each implementation of this hook must take `$bag` and `$islandora_object` as parameters; `$islandora_object` is provided so you can access properties of the object in your module easily. A typical implementation looks like this:

```
/**
 * Implementation of hook drupal_alter().
 *
 * @param object $bag
 *   A BagIt object instantiated in the BagIt module.
 *
 * @param object $islandora_object
 *   The current $islandora_object.
 */
function mymodule_islandora_bagit_alter($bag, $islandora_object) {
  // Add some custom metadata to bag-info.txt.
  $bag->bagInfoData('Some-Arbitrary-Field', 'Foo bar baz');
  // Add a file that is not managed by a plugin. Note: extra files
  // should be added by plugins if possible, since files that are
  // added in drupal_alter() hooks are not counted in Payload-Oxum
  // values generated by the Islandora BagIt module.
  $bag->addFile('/path/to/file.txt', 'myfile.txt');
  // Update the Bag (this is required).
  $bag->update();
}
```

Note that implementations of `hook_islandora_bagit_alter()` must call `$bag->update()` themselves, typically at the very end of the function.

## Modifying a batch from your own modules

If you are running a collection-level batch to create a Bag for every object in a collection, or to create a single Bag containing all objects in a collection, you can define filters on which objects get included using `hook_islandora_bagit_filter_batch()`. If you want an object to be excluded from the batch, have your instance of this hook return `TRUE`; if you want an object to be included, return `FALSE` (or don't issue an explicit 'return' at all). This example instance excludes objects with either of two specific PIDs:

```
/**
 * Implementation of hook_islandora_bagit_filter_batch().
 *
 * @param string $pid
 *   A BagIt object instantiated in the BagIt module.
 *
 * @return bool
 */
function mymodule_islandora_bagit_filter_batch($pid) {
  if ($pid == 'islandora:87' || $pid == 'islandora:91') {
    return TRUE;
  }
}
```

If you want to test other attributes of the object, you need to use Islandora's `islandora_object_load($pid)` function to load the object so you can access the attributes.

## Post-Bag-creation hook

Islandora BagIt provides an additional hook, `islandora_bagit_post_create`, that allows other modules to get notifications that a Bag has just been created. A basic implementation is:

```
/**
 * Implements hook_islandora_bagit_post_create().
 *
 * @param string $pid
 *   The PID of the Islandora object that the Bag was just created for.
 *
 * @param string $bag_path
 *   The path to the Bag, relative to the Drupal installation directory.
 */
function mymodule_islandora_bagit_post_create($pid, $bag_path) {
  // Do something interesting.
}
```

This hook can be used to send notification emails after a Bag has been created, to add the Bag to a queue for further processing, or to copy the Bag to a different server.

## Drush integration

Bags can be created for individual Islandora objects or for all objects in a given collection using Drush:

```
drush --user=UID create-islandora-bag [object|collection] PID
```

where UID is the user ID or user name of the fedoraAdmin user (or equivalent), 'object' or 'collection' indicates whether you want to create a Bag for a single object or a Bag for every member of a collection, and PID is the PID of the Islandora object or collection.

## Permissions and security

This module is intended for users who have a fairly high level of permissions on a Drupal site. Because the goal is to package up all or some of the datastreams in an Islandora object, users who can create and download Bags should have access to those datastreams. However, the module does check the current users' access to a datastream before adding it to the Bag.