

DuraCloud Resources

On this page:

- [Methods](#)
 - [GET providerAccounts](#)
 - [GET spaces](#)
- [Media Types](#)
 - [application/vnd.fcrepo-cloudsync.serviceinfo+json](#)
 - [application/vnd.fcrepo-cloudsync.serviceinfo+xml](#)
 - [application/vnd.fcrepo-cloudsync.serviceinit+json](#)
 - [application/vnd.fcrepo-cloudsync.serviceinit+xml](#)

Methods

GET providerAccounts

Gets key information about the storage provider accounts configured for a DuraCloud instance.

Request URI	See <code>providerAccountsUri</code> in GET serviceInfo or POST serviceInit response
Query Parameters	url: DuraStore URL username: The DuraCloud username to connect as password: The DuraCloud password
Request Formats	<i>None</i>
Response Formats	application/vnd.fcrepo-cloudsync.provideraccounts+json application/vnd.fcrepo-cloudsync.provideraccounts+xml
Typical Status Codes	200 Ok 500 Internal Server Error if there is any kind of error querying the DuraCloud instance

Example:

Request:

```
GET /path/to/providerAccounts HTTP/1.1
Accept: application/vnd.fcrepo-cloudsync.provideraccounts+json
```

Response:

```
HTTP/1.1 200 OK
Content-Type: application/vnd.fcrepo-cloudsync.provideraccounts+json
```

```
{
  providerAccounts: [
    {
      id: 38,
      type: "RACKSPACE",
      primary: false
    },
    {
      id: 39,
      type: "AMAZON_S3",
      primary: true
    }
  ]
}
```

GET spaces

Media Types

application/vnd.fcrepo-cloudsync.serviceinfo+json

A JSON object with a `serviceInfo` field whose value is an associative array of the following fields:

Field	Description	Required?
<code>buildDate</code>	The date the CloudSync software was built	Yes
<code>currentUserUri</code>	A URI that can be used to get the current user via GET user	Yes
<code>initialized</code>	true if POST serviceInit has been successfully called on this instance, false otherwise	Yes
<code>objectSetsUri</code>	The URI to be used for GET objectSets and POST objectSet requests	Yes
<code>objectStoresUri</code>	The URI to be used for GET objectStores and POST objectStore requests	Yes
<code>providerAccountsUri</code>	The URI to be used for GET providerAccounts requests	Yes
<code>spacesUri</code>	The URI to be used for GET spaces requests	Yes
<code>taskLogsUri</code>	The URI to be used for GET taskLogs requests	Yes
<code>tasksUri</code>	The URI to be used for GET tasks and POST task requests	Yes
<code>usersUri</code>	The URI to be used for GET users and POST user requests	Yes
<code>version</code>	The version of the CloudSync software	Yes

Example:

```
{
  serviceInfo: {
    buildDate: "2011-10-26 11:50:56 UTC-0400",
    currentUserUri: "https://example.org/path/to/user",
    initialized: false,
    objectSetsUri: "https://example.org/path/to/objectSets",
    objectStoresUri: "https://example.org/path/to/objectStores",
    providerAccountsUri: "https://example.org/path/to/providerAccounts",
    spacesUri: "https://example.org/path/to/spaces",
    taskLogsUri: "https://example.org/path/to/taskLogs",
    tasksUri: "https://example.org/path/to/tasks",
    usersUri: "https://example.org/path/to/users",
    version: "1.0.0"
  }
}
```

application/vnd.fcrepo-cloudsync.serviceinfo+xml

An XML encoding of the above.

Example:

```
<serviceInfo>
  <buildDate>2011-10-26 11:50:56 UTC-0400</buildDate>
  <currentUserUri>https://example.org/path/to/user</currentUserUri>
  <initialized>false</initialized>
  <objectSetsUri>https://example.org/path/to/objectSets</objectSetsUri>
  <objectStoresUri>https://example.org/path/to/objectStores</objectStoresUri>
  <providerAccountsUri>https://example.org/path/to/providerAccounts</providerAccountsUri>
  <spacesUri>https://example.org/path/to/spaces</spacesUri>
  <taskLogsUri>https://example.org/path/to/taskLogs</taskLogsUri>
  <tasksUri>https://example.org/path/to/tasks</tasksUri>
  <usersUri>https://example.org/path/to/users</usersUri>
  <version>1.0.0</version>
</serviceInfo>
```

application/vnd.fcrepo-cloudsync.serviceinit+json

A JSON object with a `serviceInit` field whose value is an associative array of the following fields:

Field	Description	Required?
<code>initialAdminUsername</code>	The username of the initial admin user.	Yes
<code>initialAdminPassword</code>	The password of the initial admin user.	Yes

Example:

```
{
  serviceInit: {
    initialAdminUsername: "fwilson",
    initialAdminPassword: "PuppiesRgr8!"
  }
}
```

application/vnd.fcrepo-cloudsync.serviceinit+xml

An XML encoding of the above.

Example:

```
<serviceInit>
  <initialAdminUsername>fwilson</initialAdminUsername>
  <initialAdminPassword>PuppiesRgr8!</initialAdminPassword>
</serviceInit>
```