

Configuration

Arguments Listing

Fetch

PubmedSOAPFetch

```
**emailAddress (-m | --email)
**location (-l | --location)
**outputRecordHandler (-o | --output)
```

- searchTerm (-t | --termSearch)
 - default - all records
- numRecords (-n | --numRecords)
 - default - all records
- batchSize (-b | --batchSize)
 - default - 1000

OAIFetch

```
**repositoryURL (-u | --url)
**outputRecordHandler (-o | --output)
**rangeStartDate (-s --start)
```

- - default - yr1
- rangeEndDate (-e --end)
 - default - yr8000

JDBCFetch

```
**jdbcDriverClass (-d | --driver)
**jdbcConnLine (-c | --connection)
**dbUser (-u | --user)
**dbPass (-p | --password)
**outputRecordHandler (-o | --output)
```

- Table Data
 - (how to compress this?)

Qualify

SPARQLQualify

- model (-j | --jenaConfig)
- dataType (-d | --dataType)
- matchRegex (-r | --regexMatch)
- matchExact (-t | --textMatch)
- newValue (-v | --value)

Score

Score

i rdfRecordHandler rdfRecordHandler config filename

V vivoJenaConfig vivoJenaConfig config filename

T tempModelConfig tempModelConfig config filename

O outputModelConfig outputModelConfig config filename

e exactMatch perform an exact match scoring

p pairWise perform a pairwise scoring

a authorName perform a author name scoring

p create-authors create people from ingested publications

d dateFilter add a date filter threshold that will only match year XXXX or greater

r regex perform a regular expression scoring

t tempModel temporary working model name

o outputModel output model name

f force-process If set, this will reprocess all RDF – even if it's been processed before

n allow-non-empty-working-model If set, this will not clear the working model before scoring begins

k keep-working-model If set, this will not clear the working model after scoring is complete

Transfer

Transfer

- i input config file for input jena model
- o output config file for output jena model
- I input model name for input (overrides config file)
- O output model name for output (overrides config file)
- d dumptofile dump file
- k keep-transferred-model If set, this will not clear the input model after transfer is complete

Translate

BebtexTranslator

- a

GlozeTranslator

```
**inputRecordHandler (-i | --input)
**outputRecordHandler (-o | --output)
```

- schema (-z | --xmlSchema)
 - default - null
- uriBase (-u | --uriBase)
 - default - <http://vivoweb.org/glozeTranslation/noURI/>

RDFTranslator

- a

VCardTranslator

- a

XSLTranslator

```
**inputRecordHandler (-i | --input)
**outputRecordHandler (-o | --output)
**xslFile (-x | --xslFile)
```

- - Denotes Required Argument