

# Feature Tour - Action - Update Properties

When viewing a [resource](#), you can add or delete properties using the "Update Properties" form.

The form is conveniently pre-populated with registered namespaces and a skeleton SPARQL update.

## Update Properties

```
PREFIX dc: <http://purl.org/dc/elements/1.1/>
PREFIX nt: <http://www.jcp.org/jcr/nt/1.0>
PREFIX foaf: <http://xmlns.com/foaf/0.1/>
PREFIX fcrepo: <http://fedora.info/definitions/v4/repository#>
PREFIX test: <info:fedora/test/>
PREFIX fedoraconfig: <http://fedora.info/definitions/v4/config#>
PREFIX image: <http://www.modeshape.org/images/1.0>
PREFIX xs: <http://www.w3.org/2001/XMLSchema>
PREFIX xml: <http://www.w3.org/XML/1998/namespace>
PREFIX xmlns: <http://www.w3.org/2000/xmlns/>
PREFIX fedorarelsext: <http://fedora.info/definitions/v4/rels-ext#>
PREFIX mix: <http://www.jcp.org/jcr/mix/1.0>
PREFIX premis: <http://www.loc.gov/premis/rdf/v1#>
PREFIX mode: <http://www.modeshape.org/1.0>
PREFIX rdf: <http://www.w3.org/1999/02/22-rdf-syntax-ns#>
PREFIX sv: <http://www.jcp.org/jcr/sv/1.0>
PREFIX authz: <http://fedora.info/definitions/v4/authorization#>
PREFIX fedora: <http://fedora.info/definitions/v4/rest-api#>
PREFIX xsi: <http://www.w3.org/2001/XMLSchema-instance>
```

  

```
DELETE { }
INSERT { }
WHERE { }
```

Update

To add a new property to the current resource, simply move to the bottom of the form and type in the SPARQL, then click the Update button.

Example: Add a dc:title property to the current resource:

```
INSERT {<> dc:title "My Title" .}
WHERE { }
```

Example: Delete the inserted dc:title "My Title":

```
DELETE {<> dc:title "My Title" .}
WHERE { }
```

Update the inserted dc:title "My Title" to "My Test Title":

```
INSERT {<> dc:title "My Test Title" .} WHERE { };
DELETE {<> dc:title "My Title" .}
WHERE { }
```

## More Information

- [SPARQL Update specification](#)
- [REST API guide](#)