# **APPENDIX G - All About Tuque**

Please check the original GitHub Working With Fedora Objects Programmatically Via Tuque reference for updates on these notes.:

https://github.com/Islandora/islandora/wiki/Working-With-Fedora-Objects-Programmatically-Via-Tuque

Islandora introduces support for a Fedora repository to be connected to and manipulated using the Tuque PHP library. This library can be accessed using functions included with Islandora, available inside a properly-bootstrapped Drupal environment. It can also be accessed directly outside of an Islandora environment.

Tuque is an API, written and accessible via PHP, that connects with a Fedora repository and mirrors its functionality. Tuque can be used to work with objects inside a Fedora repository, accessing their properties, manipulating them, and working with datastreams.

This guide will highlight methods of working with Fedora and Fedora objects using Tuque both by itself and from a Drupal environment.

**Tuque download** 

milestone 4 - Installing The "Tuque" library

# Variables repeated often in this guide

From here on out, we're going to be repeating the use of a few specific PHP variables after the guide demonstrates how they are instantiated or constructed:

Variable	PHP Class	Description
\$repository	FedoraRepository	A PHP object representation of the Fedora repository itself.
\$object	FedoraObject	A generic Fedora object.
\$datastream	FedoraDatastream	A generic Fedora object datastream.

# Accessing the Fedora Repository

## Connecting to Fedora

#### **Tuque or Islandora**

\$connection = new RepositoryConnection(\$fedora\_url, \$username, \$password)

#### Islandora Only (via module)

\$connection = islandora\_get\_tuque\_connection(\$user)

## Accessing the repository

# Tuque or Islandora /\*\* \* Assuming our \$connection has been instantiated as a new RepositoryConnection object. \*/ \$api = new FedoraApi(\$connection); \$repository = new FedoraRepository(\$api, new simpleCache(););

Islandora only, manually, using the Islandora Tuque wrapper:

```
/**
 * Assuming our $connection has been instantiated as a new RepositoryConnection object.
 */
module_load_include('inc', 'islandora', 'includes/tuque');
module_load_include('inc', 'islandora', 'includes/tuque_wrapper');
$api = new IslandoraFedoraApi($connection);
$repository = new IslandoraFedoraRepository($api, new SimpleCache());
```

Islandora only, automatically, using the Islandora module:

```
/**
 * Assuming $connection has been created via islandora_get_tuque_connection().
 */
$repository = $connection->repository;
```

Islandora only, using the IslandoraFedoraObject wrapper:

```
/**
 * This method tends to be the most reliable when working with a single object,
 * since it builds on the success of the attempt to load that object.
 */
$pid = 'object:pid';
$object = islandora_object_load($pid);
if ($object) {
    $repository = $object->repository;
}
```

From here, all Fedora repository functionality supported by Tuque is available to you through *\$repository*. This functionality is described in the rest of this document.

As of Islandora 7.x, there is a wrapper object, IslandoraFedoraObject, that handles some errors and fires some hooks in includes/tuque.inc. More error handling is available if one uses the wrapper functions in islandora.module.

# Working with existing objects

#### Loading an object

Method	Code	On Success	On Fail
Tuque or Islandora, from aFedoraRep ository	<pre>\$object = \$this-&gt;repository- &gt;getObject(\$pid);</pre>	Returns aFedoraObject loaded from the given \$pid.	Throws a 'Not Found'Reposito ryException.
Islandora only, from anIslandoraFed oraRepository	<pre>\$object = \$this-&gt;repository- &gt;getObject(\$pid);</pre>	Returns anIslandoraFedoraObjectloaded from the given\$pid.	Throws a 'Not Found'Reposito ryException.
Islandora only, using the module itself	<pre>\$object = islandora_object_load (\$pid);</pre>	Returns anIslandoraFedoraObjectloaded from the given\$pid.	Returns FALSE

Because the third method returns FALSE on failure, you can check if the object loaded correctly using ! sobject, e.g.:

```
$object = islandora_object_load($pid);
if (!$object) {
    /**
 * Logic for object load failure would go here.
 */
 return;
}
/**
 * Logic for object load success would continue through the rest of the method here.
 */
```

In the case of the other two methods, try to load the object and catch the load failure exception, e.g.:

```
try {
   $object = $this->repository->getObject($pid);
}
catch (Exception $e) {
   /**
   * Logic for object load failure would go here.
   */
}
/**
   * Logic for object load success would continue through the rest of the method here.
   */
```

Objects loaded via Tuque (either through Islandora or directly) have the following properties and can be manipulated using the following methods:

Name	Туре	Description
createdDa te	FedoraDate	The object's date of creation.
forceUpda te	bool	Whether or not Tuque should respect Fedora object locking on this object (FALSE to uphold locking). Defaults to FALSE.
id	string	The PID of the object. When constructing a new object, this can also be set to a namespace instead, to simply use the next available ID for that namespace.
label	string	The object's label.
lastModif iedDate	FedoraDate	When the object was last modified.
logMessage	string	The log message associated with the creation of the object in Fedora.
models	array	An array of content model PIDs (e.g. 'islandora:collectionCModel') applied to the object.
owner	string	The object's owner.
relations hips	FedoraRel sExt	A FedoraRelsExt object allowing for working with the object's relationship metadata. This is described in another section below.
repository	FedoraRep ository	The FedoraRepository object this particular object was loaded from. This functions precisely the same as the <pre>\$repo</pre> <pre>sitorycreated in the "Accessing the repository" section above.</pre>
state	string	The object's state (A/I/D).

#### Properties

#### Methods

Name	Description	Parameters	Return Value
<pre>constructD atastream (\$id, \$control_g roup)</pre>	Constructs an empty datastream. Note that this does not ingest a datastream into the object, but merely instantiates one as anA bstractDatastreamObject. Ingesting is done viaingestDat astream(), described below.	\$id - the PID of the object; <pre>\$control_group-</pre> the Fedora control group the datastream will belong to, whether Inline (X)ML, (M)anaged Content, (R)edirect, or (E)xternal Referenced. Defaults to 'M'.	An emptyAbstractDatas treamobject from the given information.

count()	The number of datastreams this object contains.	None	The number of datastreams, as anint.
delete()	Sets the object's state to 'D' (deleted).	None	None
getDatastr eam(\$dsid)	Gets a datastream from the object based on its DSID. <pre>\$object -&gt;getDatastream(\$dsid)</pre> works effectively the same as <pre>\$object[\$dsid].</pre>	$\operatorname{Sdsid}$ - the datastream identifier for the datastream to be loaded.	AnAbstractDatastream objeect representing the datastream that was gotten, orFALSE on failure.
getParents ()	Gets the IDs of the object's parents using itsisMemberOfColl ectionand isMemberOfrelationships.	None	An array of PIDs of parent objects.
<pre>ingestData stream (&amp;\$abstrac t_datastre am)</pre>	Takes a constructed datastream, with the properties you've given it, and ingests it into the object. This should be the last thing you do when creating a new datastream.	Technically takes\$abstract_datastreamas a parameter, but this should be passed to it by reference after constructing a datastream withconstructDatast ream().	A FedoraDatastreamobj ect representing the object that was just ingested.
purgeDatas tream (\$dsid)	Purges the datastream identified by the given DSID.	$\operatorname{sdsid}$ - The datastream identifier of the object.	TRUE on success, FALSE on failure.
refresh()	Clears the object cache so that fresh information can be requested from Fedora.	None	None

## Purging an object

A loaded object can be purged from the repository using:

```
$repository->purgeObject($object);
```

# Working with datastreams

Datastreams can be accessed from a loaded object like so:

#### **Tuque or Islandora**

\$datastream = \$object['DSID'];

#### Islandora Only

```
$datastream = islandora_datastream_load($dsid, $object);
```

where \$dsid is the datastream identifier as a string, and \$object is either an object PID or a loaded Fedora object.

This loads the datastream as a FedoraDatastream object. From there, it can be manipulated using the following properties and methods:where \$dsid is the datastream identifier as a string, and \$object is a loaded Fedora object.

#### **Properties**

Name	Туре	Description
checksum	string	The datastream's base64-encoded checksum.
checksu mType	string	The type of checksum for this datastream, either DISABLED, MD5, SHA-1, SHA-256, SHA-384, SHA-512. Defaults to DISABLED.
content	string	The binary content of the datastream, as a string. Can be used to set the content directly if it is an (I)nternal or (M) anaged datastream.
control Group	string	The control group for this datastream , whether Inline (X)ML, (M)anaged Content, (R)edirect, or (E)xternal Referenced

created Date	FedoraDate	The date the datastream was created.
forceUp date	bool	Whether or not Tuque should respect Fedora object locking on this datastream (FALSE to uphold locking). Defaults to FALSE.
format	string	The format URI of the datastream, if it has one. This is rarely used, but does apply to RELS-EXT.
id	string	The datastream identifier.
label	string	The datastream label.
location	string	A combination of the object ID, the DSID, and the DSID version ID.
logMess age	string	The log message associated with actions in the Fedora audit datastream.
mimetype	string	The datastream's mimetype.
parent	AbstractFedo raObject	The object that the datastream was loaded from.
relatio nships	FedoraRelsInt	The relationships that datastream holds internally within the object.
reposit ory	FedoraReposi tory	The FedoraRepository object this particular datastream was loaded from. This functions precisely the same as the pository created in the "Accessing the repository" section above.
size	int	The size of the datastream, in bytes. This is only available to ingested datastreams, not ones that have been constructed as objects but are yet to be ingested.
state	string	The state of the datastream (A/I/D).
url	string	The URL of the datastream, if it is a (R)edirected or (E)xternally-referrenced datastream.
version able	bool	Whether or not the datastream is versionable.

#### Methods

Name	Description	Parameters	Return Value
count()	The number of revisions in the datastream's history.	None	An intrepresenting the number of revisions in the datastream history.
getContent (\$path)	Writes the the binary content of the datastream to the given file.	<pre>\$path - the path to a file that the contents will be written to.</pre>	A boolean asserting the success or failure of writing the contents.
refresh()	Clears the object cache so that fresh information can be requested from Fedora.	None	None
<pre>setContentFromFi le(\$path)</pre>	Sets the content of a datastream from the contents of a local file.	spath - the path to the file to be used.	None
<pre>setContentFromSt ring(\$string)</pre>	Sets the content of a datastream from astring.	<pre>\$string - the string to set the content from.</pre>	None
<pre>setContentFromUr l(\$url)</pre>	Attempts to set the content of a datastream from content downloaded using a standatd HTTP request (NOT HTTPS).	<pre>\$url - the URL to grab the data from.</pre>	None

## Iterating over all of an object's datastreams

Since they exist on an object as an array, datastreams can be iterated over using standard array iteration methods, e.g.:

```
foreach ($object as $datastream) {
  strtoupper($datastream->id);
  $datastream->label = "new label";
  $datastream_content = $datastream->content();
}
```

```
$dsid = 'DSID';
// Before we do anything, check if the datastream exists. If it does, load it; otherwise construct it.
// The easiest way to do this, as opposed to a string of cases or if/then/elses, is the ternary operator, e.g.
// $variable = isThisThingTrueOrFalse($thing) ? setToThisIfTrue() : setToThisIfFalse();
$datastream = isset($object[$dsid]) ? $object[$dsid] : $object->constructDatastream($dsid);
$datastream->label = 'Datastream Label';
$datastream->mimeType = 'datastream/mimetype';
$datastream->setContentFromFile('path/to/file');
// There's no harm in doing this if the datastream is already ingested or if the object is only constructed.
$object->ingestDatastream($datastream);
// If the object IS only constructed, ingesting it here also ingests the datastream.
$repository->ingestObject($object);
```

# Creating new objects and datastreams

When using Tuque, Fedora objects and datastreams must first be constructed as PHP objects before being ingested into Fedora. Un-ingested, PHPconstructed Fedora objects and datastreams function nearly identically to their ingested counterparts, as far as Tuque is concerned, with only a few exceptions noted in the properties and methods tables below.

#### Constructing and ingesting an object

#### Constructing and ingesting an object \$object = \$repository->constructObject(\$pid); // \$pid may also be a namespace. /\*\* \* Here, you can manipulate the constructed object using the properties and methods described above. \*/ \$repository->ingestObject(\$object);

#### Constructing and ingesting a datastream

```
$datastream = $object->constructDatastream($dsid) // You may also set the $control_group.
/**
 * Here, you can manipulate the constructed datastream using the properties and methods described above.
 */
$object->ingestDatastream($dsid, $object);
```

# Accessing an object's relationships

Once an object is loaded, its relationships can be accessed via the object's relationships property:

```
$relationships = $object->relationships;
```

From there, the object's relationships can be viewed and manipulated using the following properties and methods:

#### Properties

Name	Туре	Description
autoCo mmit	bool	Whether or not changes to the RELS should be automatically committed. <b>WARNING</b> : Probably don't touch this if you're not absolutely sure what you're doing.
datast ream	AbstractFedoraDat astream	The datastream that this relationship is manipulating, if any.

## Methods

Name	Description	Parameters	Return Value
<pre>add (\$predicat e_uri, \$predicate , \$object, \$type)</pre>	Adds a relationship to the object.	<pre>\$predicate_uri - the namespace of the relationship predicate (if this is to be added via XML, use the registerNamespace()function described below first);\$predicate - the predicate tag to be added; \$ object - the object to add the relationship to (not required if this is called using\$object- &gt;relationships-&gt;add()); \$type - the type of the attribute to add (defaults torels_TYPE_URI).</pre>	None
changeObje ctID(\$id)	Changes the ID referenced in therdf:aboutattribute.	\$id - the new ID to use.	None
<pre>commitRela tionships (\$set_auto _commit)</pre>	Forces the committal of any relationships cached while the autoCommitproperty was set toFALSE (or for whatever other reason).	<pre>\$set_auto_commit - determines the state of autoCommit after this method is run (defaults to TRUE).</pre>	None
<pre>get (\$predicat e_uri, \$predicate , \$object, \$type)</pre>	Queries an object's relationships based on the parameters given. See below for an example of filtering relationships using parameters.	<pre>\$predicate_uri - the URI to use as the namespace predicate, or NULLfor any predicate (defaults to N ULL);\$predicate - the predicate tag to filter by, or 'NULL' for any tag (defaults toNULL); \$object - the object to filter the relationship by (not required if this is called using\$object-&gt;relationships- &gt;get()); \$type - what typeRELS_TYPE_XXXattribute the retrieved should be (defaults toRELS_TYPE_ URI).</pre>	The relationships as anarray. See the note below for an example.
registerNa mespace (\$alias, \$uri)	Registers a namespace to be used by predicate URIs.	alias - the namespace alias; $uri$ - the URI to associate with that alias.	None
<pre>remove (\$predicat e_uri, \$predicate , \$object, \$type)</pre>	Removes a relationship from the object.	<pre>\$predicate_uri - the namespace of the relationship predicate to be removed, or NULL to ignore (defaults toNULL); \$predicate - the predicate tag to filter removed results by. or NULL to remove all (defaults to NULL); \$object - the object to add the relationship to (not required if this is called using\$ob ject-&gt;relationships-&gt;remove()); \$type - what typeRELS_TYPE_XXXattribute the removed should be (defaults toRELS_TYPE_URI).</pre>	None

## Example of retrieving a filtered relationship

\$object\_content\_models = \$object->relationships->get('info:fedora/fedora-system:def/model#', 'hasModel');

This would return an array containing only the object's  ${\tt hasModel}$  relationships.

#### Example of setting an isMemberOfCollection relationship

Islandora provides the constant FEDORA\_RELS\_EXT\_URI to make it easy to set the predicate as the first variable here:

#### Example of a retrieved relationship array

```
Array
(
    [0] => Array
        (
            [predicate] => Array
                (
                    [value] => isMemberOfCollection
                    [alias] => fedora
                    [namespace] => info:fedora/fedora-system:def/relations-external#
                )
            [object] => Array
                (
                    [literal] => FALSE
                    [value] => islandora:sp_basic_image_collection
                )
        )
    [1] => Array
        (
            [predicate] => Array
                (
                    [value] => hasModel
                    [alias] => fedora-model
                    [namespace] => info:fedora/fedora-system:def/model#
                )
            [object] => Array
                (
                    [literal] => FALSE
                    [value] => islandora:sp_basic_image
                )
        )
)
```

# Using the Fedora A and M APIs

Tuque can work with the Fedora repository's "Access" and "Manage" API services in much the same way one would using standard Fedora API requests. This functionality is mimicked using an instantiated *srepository's api* property.

Note that the methods above provide a much more PHP-friendly way of performing many of the tasks provided by API-A and API-M. They are nonetheless listed in full below for documentation purposes. When a method in this section and a method above share functionality, it is **always** recommended to use the method above, as not only is it nearly guaranteed to be easier to work with, but also we cannot predict the nature of the Fedora APIs in the future; if any Fedora functionality changes or is removed, your code may also lose functionality. For example:

```
/**
* Adding a relationship to an object. The API method is clunky and requires information you wouldn't
 * need if you did things the tuque way, which is more Drupal-friendly as well.
*/
// API method.
$repository->api->m->addRelationship();
// Tuque method.
$object->relationships->add();
/**
\star Iterating through datastreams. The API method only gives you an associative array of DSIDs
\ast containing the label and mimetype - you would have to load each datastream if you wanted to
 * work with it. Working through tuque is faster.
*/
// API method.
$array = $repository->api->a->listDatastreams($object->id);
foreach ($array as $dsid => $properties) {
$datastream = islandora_datastream_load($dsid, $object);
// Now you can do stuff with the datastream.
}
// Tuque method.
foreach ($object as $datastream) {
// Do stuff with the datastream.
}
```

Documentation for the most current versions of each API can be found at:

- https://wiki.duraspace.org/display/FEDORA37/API-A
- https://wiki.duraspace.org/display/FEDORA37/API-M
- https://wiki.duraspace.org/display/FEDORA38/API-A
- https://wiki.duraspace.org/display/FEDORA38/API-M

Each API exists as a PHP object through Tuque, and can be created using:

```
$api_a = $repository->api->a; // For an Access API.
$api_m = $repository->api->m; // For a Management API.
```

From here, the functionality provided by each API mimics the functionality provided by the actual Fedora APIs, where the standard Fedora endpoints can be called as API object methods, e.g.:

```
$datastreams = $api_a->listDatastreams('islandora:1');
```

The following methods are available for each type of API:

#### FedoraApiA

All of these return results described in an array.

Method	Description
describeRepository()	Returns repository information.
<pre>findObjects(\$type, \$query, \$max_results, \$display_fields)</pre>	Finds objects based on the input parameters.
<pre>getDatastreamDissemination(\$pid, \$dsid, \$as_of_date_time, \$file)</pre>	Gets the content of a datastream.
<pre>getDissemination(\$pid, \$sdef_pid, \$method, \$method_parameters)</pre>	Gets a dissemination based on the provided method.

getObjectHistory(\$pid)	Gets the history of the specified object.
getObjectProfile(\$pid, \$as_of_date_time)	Gets the Fedora profile of an object.
<pre>listDatastreams(\$pid, \$as_of_date_time)</pre>	Lists an object's datastreams.
<pre>listMethods(\$pid, \$sdef_pid, \$as_of_date_time)</pre>	Lists the methods that an object can use for dissemination.
<pre>resumeFindObjects(\$session_token)</pre>	Resumes a findObjects() call that returned a resumption token.
userAttributes()	Authenticates and provides information about a user's Fedora attributes.

## FedoraApiM

All of these return results described in an array.

Method	Description	
addDatastream(\$pid, \$dsid, \$type, \$file, \$params)	Adds a datastream to the object specified.	
<pre>addRelationship(\$pid, \$relationship, \$is_literal, \$datatype)</pre>	Adds a relationship to the object specified.	
export(\$pid, \$params)	Exports information about an object.	
<pre>getDatastream(\$pid, \$dsid, \$params)</pre>	Returns information about the specified datastream.	
getDatastreamHistory(\$pid, \$dsid)	Returns the datastream's history information.	
getNextPid(\$namespace, \$numpids)	Gets a new, unused PID, incrementing Fedora's PID counter for that namespace.	
getObjectXml(\$pid)	Returns the object's FOXML.	
<pre>getRelationships(\$pid, \$relationship)</pre>	Returns the object's relationships.	
<pre>ingest(\$params)</pre>	Ingests an object.	
<pre>modifyDatastream(\$pid, \$dsid, \$params)</pre>	Makes specified modifications to an object's datastream.	
<pre>modifyObject(\$pid, \$params)</pre>	Makes specified modifications to an object.	
<pre>purgeDatastream(\$pid, \$dsid, \$params)</pre>	Purges the specified datastream.	
<pre>purgeObject(\$pid, \$log_message)</pre>	Purges the specified object.	
upload(\$file)	Uploads a file to the server.	
<pre>validate(\$pid, \$as_of_date_time)</pre>	Validates an object.	

# Using the Resource Index

The resource index can be queried from the repository using:

```
$ri = $repository->ri;
```

From there, queries can be made to the resource index. It is generally best to use SPARQL queries for forwards compatibility:

```
$itql_query_results = $ri->itqlQuery($query, $limit); // For an iTQL query.
$sparql_query_results = $ri->sparqlQuery($query, $limit); // For a SPARQL query.
```

# Methods

Method	Description	Parameters	Return Value
itqlQuery (\$query, \$limit)	Executes an iTQL query to the resource index.	query - a stringcontaining the query parameters; $limit$ - an int representing the number of hits to return (defaults to -1 for unlimited).	An array containing query results.
sparqlQuery (\$query, \$limit)	Executes a SparQL query to the resource index.	query - a stringcontaining the query parameters; $limit - an int$ representing the number of hits to return (defaults to -1 for unlimited).	An array containing query results.