

DuraCloud Administration

- [Naming restrictions](#)
- [Access Control Lists \(ACLs\)](#)

This document details some of the considerations of concern to a DuraCloud administrator.

Naming restrictions

1. Space names
 - a. The following restrictions apply to user-defined space names
 - only lowercase letters, numbers, periods, and dashes
 - no adjacent pair of "-" and/or "."
 - no number immediately following the last "."
 - between 3 and 42 characters
 - must start with a letter
 - may not end with a dash
 - b. Note: Users can provide space names through the [REST-API](#) that do not follow these conventions, but the space actually created will have a different name under the covers.
2. Reserved space names
 - a. Due to some specific operations exposed through the durastore [REST-API](#), the following names are unavailable as user-defined space names
 - init
 - stores
 - spaces
 - security
 - task
3. Content object names
 - a. The only restrictions are that a content object name
 - cannot include a question mark '?' character
 - cannot include a reverse solidus (backslash) '\' character
 - is limited to 1024 bytes (byte count is checked after URL and UTF-8 encoding)

Access Control Lists (ACLs)

Access control in DuraCloud is set at the space level. Users and groups can be provided read and write access to a space.

1. Users and Groups
 - a. Access is granted to *users*, *groups*, or combinations thereof
 - b. *Users* are those with credentials to access an account
 - c. *Groups* are collections of users that are created in the Management Console
2. Rights
 - a. When assigning a space ACL, *users* and/or *groups* are granted one of two rights
 - i. *READ* allows reading any content within that space
 - ii. *WRITE* allows reading, adding, and modifying any content within that space
3. Public (anonymous) Access
 - a. There is a special group named 'public' that can only be granted *READ* access to a space
 - b. If the 'public' group has *READ* access, then unauthenticated (anonymous) reads of content are permitted on that space
4. Use
 - a. REST API can be used to programmatically create, update, and delete space ACLs
 - [Get Space ACLs](#)
 - [Set Space ACLs](#)
 - b. DurAdmin provides authorized users to update space ACLs in the web interface