

How VIVO creates a page

- [The home page](#)
- [A profile page](#)
- [The People page](#)
- [A back-end page](#)

The home page

Like the title page of a book, it is not unusual for the home page of a web site to be different from all other pages. In the default VIVO theme, the most significant difference is that the search box is moved from the header to a more prominent location on the page.



The following templates are used in the home page.

```

pageSetup.ftl
page-home.ftl
    head.ftl
        stylesheets.ftl
        headScripts.ftl
    identity.ftl
        languageSelector.ftl
    menu.ftl
        developer.ftl
    footer.ftl
        scripts.ftl
        googleAnalytics.ftl

```

Template	Purpose	From
pageSetup.ftl	Sets some class and formatting parameters.	Included in every page, by TemplateProcessingHelper.java
page-home.ftl	The special template used for the home page.	Specified as the page template by HomePageController.java, overriding the default page.ftl.
head.ftl	Creates the HTML <HEAD> tag.	Included by page-home.ftl.
stylesheets.ftl	Inserts links to CSS stylesheets.	Included by head.ftl.
headScripts.ftl	Inserts links to JavaScript files that must appear in the <HEAD> section of the page. These are somewhat unusual, since most JavaScript links appear at the end of the page.	Included by head.ftl.
identity.ftl	Draws the heading of the page, including the VIVO logo and the Index and Log in links.	Included by page-home.ftl.
languageSelector.ftl	Allows the user to select their preferred language. If the site supports only one language, this template has no effect.	Included by identity.ftl.
menu.ftl	Displays the page links (Home, People, etc.) at the top of the page.	Included by page-home.ftl.
developer.ftl	Displays the developer panel, used when testing and monitoring VIVO operation. If developer mode has not been enabled, this templates produces nothing.	Included by menu.ftl.
footer.ftl	Draws the footer of the page, including the copyright notice, and the About and Support links.	Included by page-home.ftl.
scripts.ftl	Inserts links to JavaScript files. Compare to headScripts.ftl.	Included by footer.ftl.
googleAnalytics.ftl	Inserts JavaScript code to work with Google Analytics. By default, this is commented out, since each site will need to insert their own ID values in order to produce meaningful results.	Included by footer.ftl.

A profile page

By numbers, the vast majority of pages on a VIVO site are profile pages. These are all likely to be structured around the properties of each individual. However, the format can be very different depending on whether that individual is a person, an organization, or a research grant.


```

pageSetup.ftl
page.ftl
    head.ftl
        stylesheets.ftl
        headScripts.ftl
    identity.ftl
        languageSelector.ftl
    search.ftl
    menu.ftl
        developer.ftl
    individual--foaf-person.ftl
        individual-setup.ftl
        individual-orcidInterface.ftl
        individual-contactInfo.ftl
        individual-webpage.ftl
            propStatement-webpage.ftl
        individual-visualizationFoafPerson.ftl
        individual-adminPanel.ftl
        individual-positions.ftl
            propStatement-personInPosition.ftl
        individual-overview.ftl
        individual-researchAreas.ftl
        individual-geographicFocus.ftl
    individual-openSocial.ftl
    individual-property-group-tabs.ftl
        individual-properties.ftl
            propStatement-hasRole.ftl
        individual-properties.ftl
            propStatement-dataDefault.ftl
            propStatement-hasInvestigatorRole.ftl
            propStatement-hasInvestigatorRole.ftl
        individual-properties.ftl
            propStatement-fullName.ftl
    footer.ftl
        scripts.ftl
        googleAnalytics.ftl

```

Template	Purpose	From
pageSetup.ftl	as above.	
page.ftl	The master template for most VIVO pages.	Specified by FreemarkerHttpServlet.java.
head.ftl stylesheets.ftl headScripts.ftl identity.ftl languageSelector.ftl	as above.	
search.ftl	Draws the search box in the header of the page.	Included by page.ftl.
menu.ftl developer.ftl	as above.	
individual--foaf-person.ftl	The main body of the profile page.	VIVO is configured to use this template as the body of a profile page for any foaf:Person. You can change this configuration: see Class-specific templates for profile pages. This is specified in initialTBoxAnnotations.n3, and recognized by IndividualResponseBuilder.java and IndividualTemplateLocator.java.

individual-setup.ftl	Sets some basic values for the following templates to use.	Included by individual--foaf-person.ftl.
individual-orcidInterface.ftl	Implements the VIVO integration to ORCID. If this integration is not enabled, this template has no effect.	Included by individual--foaf-person.ftl.
individual-contactInfo.ftl	Displays the person's phone numbers and email addresses.	Included by individual--foaf-person.ftl.
individual-webpage.ftl	Displays the person's preferred web pages.	Included by individual--foaf-person.ftl.
propStatement-webpage.ftl	Displays a link to one of the person's preferred web pages.	VIVO is configured to use this template when displaying preferred web pages. You can change this configuration: see Custom List View Configurations. This is specified in listViewConfig-webpage.xml, which is specified in PropertyConfig.n3 and vivoListViewConfig.rdf.
individual-visualizationFofPerson.ftl	Displays the visualization links for co-authors, co-investigators	Included by individual--foaf-person.ftl.
individual-adminPanel.ftl	Displays links for a VIVO administrator to use when editing this person's information	Included by individual--foaf-person.ftl.
individual-positions.ftl	Displays the positions that this person currently holds.	Included by individual--foaf-person.ftl.
propStatement-personInPosition.ftl	Displays one position that this person currently holds.	VIVO is configured to use this template when displaying positions. You can change this configuration: see Custom List View Configurations. This is specified in listViewConfig-personInPosition.xml, which is specified in PropertyConfig.n3.
individual-overview.ftl individual-researchAreas.ftl individual-geographicFocus.ftl	Display additional information about the person.	Included by individual--foaf-person.ftl.
individual-openSocial.ftl	Implements the VIVO integration to OpenSocial gadgets. If this integration is not enabled, this template has no effect.	You can configure VIVO to display OpenSocial gadgets on profile pages: see Using OpenSocial Gadgets. Included by individual--foaf-person.ftl.
individual-property-group-tabs.ftl	Displays the groups of properties for this person.	Included by individual--foaf-person.ftl.

individual-properties.ftl propStatement-hasRole.ftl individual-properties.ftl propStatement-dataDefault.ftl propStatement-hasInvestigatorRole.ftl propStatement-hasInvestigatorRole.ftl individual-properties.ftl propStatement-fullName.ftl	Each invocation of individual-properties.ftl displays a property group. Each subordinate template displays one property for this person.	Each reference to individual-properties.ftl is included by individual-property-group-tabs.ftl. VIVO is configured to use these subordinate templates when displaying research overview, roles, and names. You can change this configuration: see Custom List View Configurations.
footer.ftl scripts.ftl googleAnalytics.ftl	as above.	

The People page

The page management GUI provides an easy way for VIVO administrators to create simple pages. These pages may also be added to the menu bar. By default, VIVO is configured with eleven such pages. Five of them are listed in the menu.



The following templates are used in the People page, and in other pages that allow users to browse through a class group.

```

pageSetup.ftl
page.ftl
  head.ftl
    stylesheets.ftl
    headScripts.ftl
  identity.ftl
    languageSelector.ftl
  search.ftl
  menu.ftl
    developer.ftl
  page-classgroup.ftl
    menupage-checkForData.ftl
    menupage-browse.ftl
    menupage-scripts.ftl
  footer.ftl
    scripts.ftl
    googleAnalytics.ftl

```

Template	Purpose	From
----------	---------	------

pageSetup.ftl page.ftl head.ftl ftl stylesheets.ftl headScripts.ftl identity.ftl languageSelector.ftl search.ftl menu.ftl developer.ftl	as above.	
page-classgroup.ftl	Combines the components to create an AJAX-driven page that browses among the classes in a class group.	VIVO is configured to use this template in the People menu page page. You can change this configuration: see Menu and page management. This template is invoked by ClassGroupPageData.java, which is assigned to the People page in menu.n3.
menupage-checkForData.ftl	Checks to see if the page will be empty. Displays messages suitable to a VIVO administrator or to another user, depending on who is viewing the page.	Included by page-classgroup.ftl.
menupage-browse.ftl	Creates the page context that will be filled by AJAX calls.	Included by page-classgroup.ftl.
menupage-scripts.ftl	Creates or links to the JavaScripts used in browsing among classes of individuals.	Included by page-classgroup.ftl.
footer.ftl scripts.ftl googleAnalytics.ftl	as above.	

A back-end page

VIVO provides several pages that allow administrators to edit the classes and properties in the ontology, and to create or adjust class groups and property groups. These pages are built around the older JSP (Java Server Pages) technology, although the header and footer are created from the same Freemarker templates as other pages.



The following templates and JSPs are used in creating this page.

```

basicPage.jsp
  head.ftl
    stylesheets.ftl
    headScripts.ftl
  identity.ftl
    languageSelector.ftl
  search.ftl
  menu.ftl
    developer.ftl
  formBasic.jsp
    classgroup_retry.jsp
  footer.ftl
    scripts.ftl
    googleAnalytics.ftl

```

Template	Purpose	From
basicPage.jsp	The master template for the VIVO back-end pages.	Specified by ClassgroupRetryController.java.
head.ftl stylesheets.ftl headScripts.ftl identity.ftl languageSelector.ftl search.ftl menu.ftl developer.ftl	as above.	
formBasic.jsp	A generic frame that provides title and buttons for an edit.	Specified by ClassgroupRetryController.java.

classgroup_retry.jsp	Shows the fields that may be edited for a class group.	Specified by ClassgroupRetryController.java.
footer.ftl scripts.ftl googleAnalytics.ftl	as above.	